

libximc

2.10.5

Generated by Doxygen 1.8.2

Fri Jun 8 2018 13:14:15

Contents

1	libximc library	1
1.1	About ximc	1
1.2	About libximc	1
2	Introduction	2
2.1	About	2
2.2	System requirements	2
2.2.1	For rebuilding library	2
2.2.2	For using library	3
3	How to rebuild library	4
3.1	Building on generic UNIX	4
3.2	Building on debian-based linux systems	4
3.3	Building on redhat-based linux systems	4
3.4	Buliding on Mac OS X	5
3.5	Buliding on Windows	5
3.6	Source code access	5
4	How to use with...	6
4.1	Usage with C	6
4.1.1	Visual C++	6
4.1.2	CodeBlocks	6
4.1.3	MinGW	6
4.1.4	C++ Builder	6
4.1.5	XCode	7
4.1.6	GCC	7
4.2	.NET	7
4.3	Delphi	7
4.4	Java	8
4.5	Python	8
4.6	MATLAB	8
4.7	Generic logging facility	9

4.8	Required permissions	9
4.9	C-profiles	9
5	Data Structure Documentation	10
5.1	accessories_settings.t Struct Reference	10
5.1.1	Detailed Description	10
5.1.2	Field Documentation	11
5.1.2.1	LimitSwitchesSettings	11
5.1.2.2	MagneticBrakeInfo	11
5.1.2.3	MBRatedCurrent	11
5.1.2.4	MBRatedVoltage	11
5.1.2.5	MBSettings	11
5.1.2.6	MBTorque	11
5.1.2.7	TemperatureSensorInfo	11
5.1.2.8	TSGrad	11
5.1.2.9	TSMax	11
5.1.2.10	TSMin	11
5.1.2.11	TSSettings	11
5.2	analog_data.t Struct Reference	12
5.2.1	Detailed Description	13
5.2.2	Field Documentation	13
5.2.2.1	A1Voltage	13
5.2.2.2	A1Voltage_ADC	13
5.2.2.3	A2Voltage	13
5.2.2.4	A2Voltage_ADC	13
5.2.2.5	ACurrent	13
5.2.2.6	ACurrent_ADC	13
5.2.2.7	B1Voltage	14
5.2.2.8	B1Voltage_ADC	14
5.2.2.9	B2Voltage	14
5.2.2.10	B2Voltage_ADC	14
5.2.2.11	BCurrent	14
5.2.2.12	BCurrent_ADC	14
5.2.2.13	FullCurrent	14
5.2.2.14	FullCurrent_ADC	14
5.2.2.15	Joy	14
5.2.2.16	Joy_ADC	14
5.2.2.17	L	14
5.2.2.18	L5	14
5.2.2.19	L5_ADC	15

5.2.2.20	Pot	15
5.2.2.21	R	15
5.2.2.22	SupVoltage	15
5.2.2.23	SupVoltage_ADC	15
5.2.2.24	Temp	15
5.2.2.25	Temp_ADC	15
5.3	brake_settings.t Struct Reference	15
5.3.1	Detailed Description	16
5.3.2	Field Documentation	16
5.3.2.1	BrakeFlags	16
5.3.2.2	t1	16
5.3.2.3	t2	16
5.3.2.4	t3	16
5.3.2.5	t4	16
5.4	calibration_settings.t Struct Reference	16
5.4.1	Detailed Description	17
5.4.2	Field Documentation	17
5.4.2.1	CSS1_A	17
5.4.2.2	CSS1_B	17
5.4.2.3	CSS2_A	17
5.4.2.4	CSS2_B	17
5.4.2.5	FullCurrent_A	17
5.4.2.6	FullCurrent_B	17
5.5	calibration.t Struct Reference	17
5.5.1	Detailed Description	18
5.6	chart_data.t Struct Reference	18
5.6.1	Detailed Description	18
5.6.2	Field Documentation	18
5.6.2.1	DutyCycle	18
5.6.2.2	Joy	19
5.6.2.3	Pot	19
5.6.2.4	WindingCurrentA	19
5.6.2.5	WindingCurrentB	19
5.6.2.6	WindingCurrentC	19
5.6.2.7	WindingVoltageA	19
5.6.2.8	WindingVoltageB	19
5.6.2.9	WindingVoltageC	19
5.7	command_add_sync_in_action_calb.t Struct Reference	19
5.7.1	Field Documentation	20
5.7.1.1	Position	20

5.7.1.2	Time	20
5.8	command_add_sync_in_action.t Struct Reference	20
5.8.1	Detailed Description	20
5.8.2	Field Documentation	20
5.8.2.1	Time	20
5.8.2.2	uPosition	20
5.9	command_change_motor.t Struct Reference	20
5.9.1	Detailed Description	21
5.10	control_settings_calb.t Struct Reference	21
5.10.1	Field Documentation	21
5.10.1.1	Flags	21
5.10.1.2	MaxClickTime	21
5.10.1.3	MaxSpeed	21
5.10.1.4	Timeout	21
5.11	control_settings.t Struct Reference	21
5.11.1	Detailed Description	22
5.11.2	Field Documentation	22
5.11.2.1	Flags	22
5.11.2.2	MaxClickTime	22
5.11.2.3	MaxSpeed	22
5.11.2.4	Timeout	23
5.11.2.5	uDeltaPosition	23
5.11.2.6	uMaxSpeed	23
5.12	controller_name.t Struct Reference	23
5.12.1	Detailed Description	23
5.12.2	Field Documentation	23
5.12.2.1	ControllerName	23
5.12.2.2	CtrlFlags	23
5.13	ctp_settings.t Struct Reference	23
5.13.1	Detailed Description	24
5.13.2	Field Documentation	24
5.13.2.1	CTPFlags	24
5.13.2.2	CTPMinError	24
5.14	debug_read.t Struct Reference	24
5.14.1	Detailed Description	24
5.14.2	Field Documentation	25
5.14.2.1	DebugData	25
5.15	debug_write.t Struct Reference	25
5.15.1	Detailed Description	25
5.15.2	Field Documentation	25

5.15.2.1	DebugData	25
5.16	device_information_t Struct Reference	25
5.16.1	Detailed Description	26
5.16.2	Field Documentation	26
5.16.2.1	Major	26
5.16.2.2	Minor	26
5.16.2.3	Release	26
5.17	device_network_information_t Struct Reference	26
5.17.1	Detailed Description	27
5.18	edges_settings_calb_t Struct Reference	27
5.18.1	Field Documentation	27
5.18.1.1	BorderFlags	27
5.18.1.2	EnderFlags	27
5.18.1.3	LeftBorder	27
5.18.1.4	RightBorder	27
5.19	edges_settings_t Struct Reference	27
5.19.1	Detailed Description	28
5.19.2	Field Documentation	28
5.19.2.1	BorderFlags	28
5.19.2.2	EnderFlags	28
5.19.2.3	LeftBorder	28
5.19.2.4	RightBorder	28
5.19.2.5	uLeftBorder	28
5.19.2.6	uRightBorder	28
5.20	encoder_information_t Struct Reference	28
5.20.1	Detailed Description	29
5.20.2	Field Documentation	29
5.20.2.1	Manufacturer	29
5.20.2.2	PartNumber	29
5.21	encoder_settings_t Struct Reference	29
5.21.1	Detailed Description	30
5.21.2	Field Documentation	30
5.21.2.1	EncoderSettings	30
5.21.2.2	MaxCurrentConsumption	30
5.21.2.3	MaxOperatingFrequency	30
5.21.2.4	SupplyVoltageMax	30
5.21.2.5	SupplyVoltageMin	30
5.22	engine_settings_calb_t Struct Reference	30
5.22.1	Field Documentation	31
5.22.1.1	Antiplay	31

5.22.1.2	EngineFlags	31
5.22.1.3	MicrostepMode	31
5.22.1.4	NomCurrent	31
5.22.1.5	NomSpeed	31
5.22.1.6	NomVoltage	31
5.22.1.7	StepsPerRev	31
5.23	engine_settings_t Struct Reference	31
5.23.1	Detailed Description	32
5.23.2	Field Documentation	32
5.23.2.1	Antiplay	32
5.23.2.2	EngineFlags	32
5.23.2.3	MicrostepMode	32
5.23.2.4	NomCurrent	33
5.23.2.5	NomSpeed	33
5.23.2.6	NomVoltage	33
5.23.2.7	StepsPerRev	33
5.23.2.8	uNomSpeed	33
5.24	entype_settings_t Struct Reference	33
5.24.1	Detailed Description	33
5.24.2	Field Documentation	34
5.24.2.1	DriverType	34
5.24.2.2	EngineType	34
5.25	extio_settings_t Struct Reference	34
5.25.1	Detailed Description	34
5.25.2	Field Documentation	34
5.25.2.1	EXTIOModeFlags	34
5.25.2.2	EXTIOSetupFlags	34
5.26	feedback_settings_t Struct Reference	34
5.26.1	Detailed Description	35
5.26.2	Field Documentation	35
5.26.2.1	CountsPerTurn	35
5.26.2.2	FeedbackFlags	35
5.26.2.3	FeedbackType	35
5.26.2.4	IPS	35
5.27	gear_information_t Struct Reference	35
5.27.1	Detailed Description	36
5.27.2	Field Documentation	36
5.27.2.1	Manufacturer	36
5.27.2.2	PartNumber	36
5.28	gear_settings_t Struct Reference	36

5.28.1 Detailed Description	37
5.28.2 Field Documentation	37
5.28.2.1 Efficiency	37
5.28.2.2 InputInertia	37
5.28.2.3 MaxOutputBacklash	37
5.28.2.4 RatedInputSpeed	37
5.28.2.5 RatedInputTorque	37
5.28.2.6 ReductionIn	37
5.28.2.7 ReductionOut	37
5.29 get_position_calb_t Struct Reference	38
5.29.1 Field Documentation	38
5.29.1.1 EncPosition	38
5.29.1.2 Position	38
5.30 get_position_t Struct Reference	38
5.30.1 Detailed Description	38
5.30.2 Field Documentation	38
5.30.2.1 EncPosition	38
5.31 globally_unique_identifier_t Struct Reference	38
5.31.1 Detailed Description	39
5.31.2 Field Documentation	39
5.31.2.1 UniqueID0	39
5.31.2.2 UniqueID1	39
5.31.2.3 UniqueID2	39
5.31.2.4 UniqueID3	39
5.32 hallsensor_information_t Struct Reference	39
5.32.1 Detailed Description	40
5.32.2 Field Documentation	40
5.32.2.1 Manufacturer	40
5.32.2.2 PartNumber	40
5.33 hallsensor_settings_t Struct Reference	40
5.33.1 Detailed Description	40
5.33.2 Field Documentation	41
5.33.2.1 MaxCurrentConsumption	41
5.33.2.2 MaxOperatingFrequency	41
5.33.2.3 SupplyVoltageMax	41
5.33.2.4 SupplyVoltageMin	41
5.34 home_settings_calb_t Struct Reference	41
5.34.1 Field Documentation	41
5.34.1.1 FastHome	41
5.34.1.2 HomeDelta	41

5.34.1.3	HomeFlags	41
5.34.1.4	SlowHome	42
5.35	home_settings.t Struct Reference	42
5.35.1	Detailed Description	42
5.35.2	Field Documentation	42
5.35.2.1	FastHome	42
5.35.2.2	HomeDelta	42
5.35.2.3	HomeFlags	42
5.35.2.4	SlowHome	43
5.35.2.5	uFastHome	43
5.35.2.6	uHomeDelta	43
5.35.2.7	uSlowHome	43
5.36	init_random.t Struct Reference	43
5.36.1	Detailed Description	43
5.36.2	Field Documentation	43
5.36.2.1	key	43
5.37	joystick_settings.t Struct Reference	43
5.37.1	Detailed Description	44
5.37.2	Field Documentation	44
5.37.2.1	DeadZone	44
5.37.2.2	ExpFactor	44
5.37.2.3	JoyCenter	44
5.37.2.4	JoyFlags	44
5.37.2.5	JoyHighEnd	45
5.37.2.6	JoyLowEnd	45
5.38	measurements.t Struct Reference	45
5.38.1	Detailed Description	45
5.38.2	Field Documentation	45
5.38.2.1	Error	45
5.38.2.2	Length	45
5.38.2.3	Speed	45
5.39	motor_information.t Struct Reference	46
5.39.1	Detailed Description	46
5.39.2	Field Documentation	46
5.39.2.1	Manufacturer	46
5.39.2.2	PartNumber	46
5.40	motor_settings.t Struct Reference	46
5.40.1	Detailed Description	47
5.40.2	Field Documentation	48
5.40.2.1	DetentTorque	48

5.40.2.2	MaxCurrent	48
5.40.2.3	MaxCurrentTime	48
5.40.2.4	MaxSpeed	48
5.40.2.5	MechanicalTimeConstant	48
5.40.2.6	MotorType	48
5.40.2.7	NoLoadCurrent	48
5.40.2.8	NoLoadSpeed	48
5.40.2.9	NominalCurrent	48
5.40.2.10	NominalPower	49
5.40.2.11	NominalSpeed	49
5.40.2.12	NominalTorque	49
5.40.2.13	NominalVoltage	49
5.40.2.14	Phases	49
5.40.2.15	Poles	49
5.40.2.16	RotorInertia	49
5.40.2.17	SpeedConstant	49
5.40.2.18	SpeedTorqueGradient	49
5.40.2.19	StallTorque	49
5.40.2.20	TorqueConstant	50
5.40.2.21	WindingInductance	50
5.40.2.22	WindingResistance	50
5.41	move_settings_calb.t Struct Reference	50
5.41.1	Field Documentation	50
5.41.1.1	Accel	50
5.41.1.2	AntiplaySpeed	50
5.41.1.3	Decel	50
5.41.1.4	Speed	50
5.42	move_settings.t Struct Reference	51
5.42.1	Detailed Description	51
5.42.2	Field Documentation	51
5.42.2.1	Accel	51
5.42.2.2	AntiplaySpeed	51
5.42.2.3	Decel	51
5.42.2.4	Speed	51
5.42.2.5	uAntiplaySpeed	52
5.42.2.6	uSpeed	52
5.43	nonvolatile_memory.t Struct Reference	52
5.43.1	Detailed Description	52
5.43.2	Field Documentation	52
5.43.2.1	UserData	52

5.44	pid_settings_t Struct Reference	52
5.44.1	Detailed Description	53
5.45	power_settings_t Struct Reference	53
5.45.1	Detailed Description	53
5.45.2	Field Documentation	53
5.45.2.1	CurrentSetTime	53
5.45.2.2	CurrReductDelay	54
5.45.2.3	HoldCurrent	54
5.45.2.4	PowerFlags	54
5.45.2.5	PowerOffDelay	54
5.46	secure_settings_t Struct Reference	54
5.46.1	Detailed Description	54
5.46.2	Field Documentation	55
5.46.2.1	Criticalpwr	55
5.46.2.2	Criticalusb	55
5.46.2.3	CriticalT	55
5.46.2.4	CriticalUpwr	55
5.46.2.5	CriticalUusb	55
5.46.2.6	Flags	55
5.46.2.7	LowUpwrOff	55
5.46.2.8	MinimumUusb	55
5.47	serial_number_t Struct Reference	55
5.47.1	Detailed Description	56
5.47.2	Field Documentation	56
5.47.2.1	Key	56
5.47.2.2	Major	56
5.47.2.3	Minor	56
5.47.2.4	Release	56
5.47.2.5	SN	56
5.48	set_position_calb_t Struct Reference	56
5.48.1	Field Documentation	56
5.48.1.1	EncPosition	56
5.48.1.2	PosFlags	57
5.48.1.3	Position	57
5.49	set_position_t Struct Reference	57
5.49.1	Detailed Description	57
5.49.2	Field Documentation	57
5.49.2.1	EncPosition	57
5.49.2.2	PosFlags	57
5.50	stage_information_t Struct Reference	57

5.50.1 Detailed Description	58
5.50.2 Field Documentation	58
5.50.2.1 Manufacturer	58
5.50.2.2 PartNumber	58
5.51 stage_name.t Struct Reference	58
5.51.1 Detailed Description	58
5.51.2 Field Documentation	59
5.51.2.1 PositionerName	59
5.52 stage_settings.t Struct Reference	59
5.52.1 Detailed Description	59
5.52.2 Field Documentation	59
5.52.2.1 HorizontalLoadCapacity	59
5.52.2.2 LeadScrewPitch	60
5.52.2.3 MaxCurrentConsumption	60
5.52.2.4 MaxSpeed	60
5.52.2.5 SupplyVoltageMax	60
5.52.2.6 SupplyVoltageMin	60
5.52.2.7 TravelRange	60
5.52.2.8 Units	60
5.52.2.9 VerticalLoadCapacity	60
5.53 status_calb.t Struct Reference	60
5.53.1 Field Documentation	61
5.53.1.1 CmdBufFreeSpace	61
5.53.1.2 CurPosition	61
5.53.1.3 CurSpeed	61
5.53.1.4 CurT	61
5.53.1.5 EncPosition	61
5.53.1.6 EncSts	62
5.53.1.7 Flags	62
5.53.1.8 GPIOFlags	62
5.53.1.9 Ipwr	62
5.53.1.10 Iusb	62
5.53.1.11 MoveSts	62
5.53.1.12 MvCmdSts	62
5.53.1.13 PWRSts	62
5.53.1.14 Upwr	62
5.53.1.15 Uusb	62
5.53.1.16 WindSts	62
5.54 status.t Struct Reference	62
5.54.1 Detailed Description	63

5.54.2	Field Documentation	63
5.54.2.1	CmdBufFreeSpace	63
5.54.2.2	CurPosition	64
5.54.2.3	CurSpeed	64
5.54.2.4	CurT	64
5.54.2.5	EncPosition	64
5.54.2.6	EncSts	64
5.54.2.7	Flags	64
5.54.2.8	GPIOFlags	64
5.54.2.9	Ipwr	64
5.54.2.10	Iusb	64
5.54.2.11	MoveSts	64
5.54.2.12	MvCmdSts	64
5.54.2.13	PWRSts	64
5.54.2.14	uCurPosition	65
5.54.2.15	uCurSpeed	65
5.54.2.16	Upwr	65
5.54.2.17	Uusb	65
5.54.2.18	WindSts	65
5.55	sync_in.settings_calb.t Struct Reference	65
5.55.1	Field Documentation	65
5.55.1.1	ClutterTime	65
5.55.1.2	Position	65
5.55.1.3	Speed	65
5.55.1.4	SyncInFlags	66
5.56	sync_in.settings.t Struct Reference	66
5.56.1	Detailed Description	66
5.56.2	Field Documentation	66
5.56.2.1	ClutterTime	66
5.56.2.2	Speed	66
5.56.2.3	SyncInFlags	66
5.56.2.4	uPosition	67
5.56.2.5	uSpeed	67
5.57	sync_out.settings_calb.t Struct Reference	67
5.57.1	Field Documentation	67
5.57.1.1	Accuracy	67
5.57.1.2	SyncOutFlags	67
5.57.1.3	SyncOutPeriod	67
5.57.1.4	SyncOutPulseSteps	67
5.58	sync_out.settings.t Struct Reference	68

5.58.1	Detailed Description	68
5.58.2	Field Documentation	68
5.58.2.1	Accuracy	68
5.58.2.2	SyncOutFlags	68
5.58.2.3	SyncOutPeriod	68
5.58.2.4	SyncOutPulseSteps	68
5.58.2.5	uAccuracy	69
5.59	uart_settings_t Struct Reference	69
5.59.1	Detailed Description	69
5.59.2	Field Documentation	69
5.59.2.1	UARTSetupFlags	69
6	File Documentation	70
6.1	ximc.h File Reference	70
6.1.1	Detailed Description	91
6.1.2	Macro Definition Documentation	91
6.1.2.1	ALARM_ON_DRIVER_OVERHEATING	91
6.1.2.2	BORDER.IS_ENCODER	92
6.1.2.3	BORDER.STOP_LEFT	92
6.1.2.4	BORDER.STOP_RIGHT	92
6.1.2.5	BORDERS.SWAP_MISSET_DETECTION	92
6.1.2.6	BRAKE.ENABLED	92
6.1.2.7	BRAKE_ENG.PWROFF	92
6.1.2.8	CONTROL_BTN_LEFT.PUSHED_OPEN	92
6.1.2.9	CONTROL_BTN_RIGHT.PUSHED_OPEN	92
6.1.2.10	CONTROL.MODE.BITS	92
6.1.2.11	CONTROL.MODE.JOY	92
6.1.2.12	CONTROL.MODE.LR	92
6.1.2.13	CONTROL.MODE.OFF	92
6.1.2.14	CTP.ALARM_ON.ERROR	93
6.1.2.15	CTP.BASE	93
6.1.2.16	CTP.ENABLED	93
6.1.2.17	CTP.ERROR.CORRECTION	93
6.1.2.18	DRIVER.TYPE.DISCRETE.FET	93
6.1.2.19	DRIVER.TYPE.EXTERNAL	93
6.1.2.20	DRIVER.TYPE.INTEGRATE	93
6.1.2.21	EEPROM.PRECEDENCE	93
6.1.2.22	ENC.STATE.ABSENT	93
6.1.2.23	ENC.STATE.MALFUNC	93
6.1.2.24	ENC.STATE.OK	93

6.1.2.25	ENC.STATE.REVERS	93
6.1.2.26	ENC.STATE.UNKNOWN	94
6.1.2.27	ENDER.SW1.ACTIVE_LOW	94
6.1.2.28	ENDER.SW2.ACTIVE_LOW	94
6.1.2.29	ENDER.SWAP	94
6.1.2.30	ENGINE.ACCEL_ON	94
6.1.2.31	ENGINE.ANTIPLAY	94
6.1.2.32	ENGINE.CURRENT_AS_RMS	94
6.1.2.33	ENGINE.LIMIT_CURR	94
6.1.2.34	ENGINE.LIMIT_RPM	94
6.1.2.35	ENGINE.LIMIT_VOLT	94
6.1.2.36	ENGINE.MAX_SPEED	95
6.1.2.37	ENGINE.REVERSE	95
6.1.2.38	ENGINE.TYPE_2DC	95
6.1.2.39	ENGINE.TYPE_BRUSHLESS	95
6.1.2.40	ENGINE.TYPE_DC	95
6.1.2.41	ENGINE.TYPE_NONE	95
6.1.2.42	ENGINE.TYPE_STEP	95
6.1.2.43	ENGINE.TYPE_TEST	95
6.1.2.44	ENUMERATE.PROBE	95
6.1.2.45	EXTIO.SETUP.INVERT	95
6.1.2.46	EXTIO.SETUP.MODE.IN.ALARM	96
6.1.2.47	EXTIO.SETUP.MODE.IN.BITS	96
6.1.2.48	EXTIO.SETUP.MODE.IN.HOME	96
6.1.2.49	EXTIO.SETUP.MODE.IN.MOVR	96
6.1.2.50	EXTIO.SETUP.MODE.IN.NOP	96
6.1.2.51	EXTIO.SETUP.MODE.IN.PWOF	96
6.1.2.52	EXTIO.SETUP.MODE.IN.STOP	96
6.1.2.53	EXTIO.SETUP.MODE.OUT.ALARM	96
6.1.2.54	EXTIO.SETUP.MODE.OUT.BITS	96
6.1.2.55	EXTIO.SETUP.MODE.OUT.MOTOR_FOUND	96
6.1.2.56	EXTIO.SETUP.MODE.OUT.MOTOR_ON	96
6.1.2.57	EXTIO.SETUP.MODE.OUT.MOVING	96
6.1.2.58	EXTIO.SETUP.MODE.OUT.OFF	97
6.1.2.59	EXTIO.SETUP.MODE.OUT.ON	97
6.1.2.60	EXTIO.SETUP.OUTPUT	97
6.1.2.61	FEEDBACK.EMF	97
6.1.2.62	FEEDBACK.ENC.REVERSE	97
6.1.2.63	FEEDBACK.ENC.TYPE.AUTO	97
6.1.2.64	FEEDBACK.ENC.TYPE.BITS	97

6.1.2.65	FEEDBACK_ENC_TYPE_DIFFERENTIAL	97
6.1.2.66	FEEDBACK_ENC_TYPE_SINGLE_ENDED	97
6.1.2.67	FEEDBACK_ENCODER	97
6.1.2.68	FEEDBACK_NONE	97
6.1.2.69	H_BRIDGE_ALERT	97
6.1.2.70	HOME_DIR_FIRST	98
6.1.2.71	HOME_DIR_SECOND	98
6.1.2.72	HOME_HALF_MV	98
6.1.2.73	HOME_MV_SEC_EN	98
6.1.2.74	HOME_STOP_FIRST_BITS	98
6.1.2.75	HOME_STOP_FIRST_LIM	98
6.1.2.76	HOME_STOP_FIRST_REV	98
6.1.2.77	HOME_STOP_FIRST_SYN	98
6.1.2.78	HOME_STOP_SECOND_BITS	98
6.1.2.79	HOME_STOP_SECOND_LIM	98
6.1.2.80	HOME_STOP_SECOND_REV	98
6.1.2.81	HOME_STOP_SECOND_SYN	98
6.1.2.82	HOME_USE_FAST	99
6.1.2.83	JOY_REVERSE	99
6.1.2.84	LOW_UPWR_PROTECTION	99
6.1.2.85	MICROSTEP_MODE_FRAC_128	99
6.1.2.86	MICROSTEP_MODE_FRAC_16	99
6.1.2.87	MICROSTEP_MODE_FRAC_2	99
6.1.2.88	MICROSTEP_MODE_FRAC_256	99
6.1.2.89	MICROSTEP_MODE_FRAC_32	99
6.1.2.90	MICROSTEP_MODE_FRAC_4	99
6.1.2.91	MICROSTEP_MODE_FRAC_64	99
6.1.2.92	MICROSTEP_MODE_FRAC_8	99
6.1.2.93	MICROSTEP_MODE_FULL	99
6.1.2.94	MOVE_STATE_ANTIPLAY	100
6.1.2.95	MOVE_STATE_MOVING	100
6.1.2.96	MOVE_STATE_TARGET_SPEED	100
6.1.2.97	MVCMD_ERROR	100
6.1.2.98	MVCMD_HOME	100
6.1.2.99	MVCMD_LEFT	100
6.1.2.100	MVCMD_LOFT	100
6.1.2.101	MVCMD_MOVE	100
6.1.2.102	MVCMD_MOVR	100
6.1.2.103	MVCMD_NAME_BITS	100
6.1.2.104	MVCMD_RIGHT	100

6.1.2.105 MVCMD_RUNNING	101
6.1.2.106 MVCMD_SSTP	101
6.1.2.107 MVCMD_STOP	101
6.1.2.108 MVCMD_UKNWN	101
6.1.2.109 POWER_OFF_ENABLED	101
6.1.2.110 POWER_REDUCT_ENABLED	101
6.1.2.111 POWER_SMOOTH_CURRENT	101
6.1.2.112 PWR_STATE_MAX	101
6.1.2.113 PWR_STATE_NORM	101
6.1.2.114 PWR_STATE_OFF	101
6.1.2.115 PWR_STATE_REDUCT	101
6.1.2.116 PWR_STATE_UNKNOWN	101
6.1.2.117 REV_SENS_INV	102
6.1.2.118 SETPOS_IGNORE_ENCODER	102
6.1.2.119 SETPOS_IGNORE_POSITION	102
6.1.2.120 STATE_ALARM	102
6.1.2.121 STATE_BORDERS_SWAP_MISSET	102
6.1.2.122 STATE_BRAKE	102
6.1.2.123 STATE_BUTTON_LEFT	102
6.1.2.124 STATE_BUTTON_RIGHT	102
6.1.2.125 STATE_CONTR	102
6.1.2.126 STATE_CONTROLLER_OVERHEAT	102
6.1.2.127 STATE_CTP_ERROR	102
6.1.2.128 STATE_CURRENT_MOTOR0	102
6.1.2.129 STATE_CURRENT_MOTOR1	103
6.1.2.130 STATE_CURRENT_MOTOR2	103
6.1.2.131 STATE_CURRENT_MOTOR3	103
6.1.2.132 STATE_CURRENT_MOTOR_BITS	103
6.1.2.133 STATE_DIG_SIGNAL	103
6.1.2.134 STATE_EEPROM_CONNECTED	103
6.1.2.135 STATE_ENC_A	103
6.1.2.136 STATE_ENC_B	103
6.1.2.137 STATE_ERRC	103
6.1.2.138 STATE_ERRD	103
6.1.2.139 STATE_ERRV	103
6.1.2.140 STATE_GPIO_LEVEL	103
6.1.2.141 STATE_GPIO_PINOUT	104
6.1.2.142 STATE_LEFT_EDGE	104
6.1.2.143 STATE_LOW_USB_VOLTAGE	104
6.1.2.144 STATE_OVERLOAD_POWER_CURRENT	104

6.1.2.145	STATE_OVERLOAD_POWER_VOLTAGE	104
6.1.2.146	STATE_OVERLOAD_USB_CURRENT	104
6.1.2.147	STATE_OVERLOAD_USB_VOLTAGE	104
6.1.2.148	STATE_POWER_OVERHEAT	104
6.1.2.149	STATE_REV_SENSOR	104
6.1.2.150	STATE_RIGHT_EDGE	104
6.1.2.151	STATE_SECUR	104
6.1.2.152	STATE_SYNC_INPUT	104
6.1.2.153	STATE_SYNC_OUTPUT	105
6.1.2.154	SYNCIN_ENABLED	105
6.1.2.155	SYNCIN_GOTOPOSITION	105
6.1.2.156	SYNCIN_INVERT	105
6.1.2.157	SYNCOUT_ENABLED	105
6.1.2.158	SYNCOUT_IN_STEPS	105
6.1.2.159	SYNCOUT_INVERT	105
6.1.2.160	SYNCOUT_ONPERIOD	105
6.1.2.161	SYNCOUT_ONSTART	105
6.1.2.162	SYNCOUT_ONSTOP	105
6.1.2.163	SYNCOUT_STATE	105
6.1.2.164	UART_PARITY_BITS	105
6.1.2.165	WIND_A_STATE_ABSENT	106
6.1.2.166	WIND_A_STATE_MALFUNC	106
6.1.2.167	WIND_A_STATE_OK	106
6.1.2.168	WIND_A_STATE_UNKNOWN	106
6.1.2.169	WIND_B_STATE_ABSENT	106
6.1.2.170	WIND_B_STATE_MALFUNC	106
6.1.2.171	WIND_B_STATE_OK	106
6.1.2.172	WIND_B_STATE_UNKNOWN	106
6.1.2.173	XIMC_API	106
6.1.3	Typedef Documentation	106
6.1.3.1	logging_callback_t	106
6.1.4	Function Documentation	107
6.1.4.1	close_device	107
6.1.4.2	command_add_sync_in_action	107
6.1.4.3	command_change_motor	107
6.1.4.4	command_clear_fram	107
6.1.4.5	command_eeread_settings	107
6.1.4.6	command_eesave_settings	108
6.1.4.7	command_home	108
6.1.4.8	command_homezero	108

6.1.4.9	command_left	108
6.1.4.10	command_loft	109
6.1.4.11	command_move	109
6.1.4.12	command_movr	109
6.1.4.13	command_power_off	109
6.1.4.14	command_read_robust_settings	110
6.1.4.15	command_read_settings	110
6.1.4.16	command_reset	110
6.1.4.17	command_right	110
6.1.4.18	command_save_robust_settings	110
6.1.4.19	command_save_settings	110
6.1.4.20	command_sstp	111
6.1.4.21	command_start_measurements	111
6.1.4.22	command_stop	111
6.1.4.23	command_update_firmware	111
6.1.4.24	command_wait_for_stop	111
6.1.4.25	command_zero	112
6.1.4.26	enumerate_devices	112
6.1.4.27	free_enumerate_devices	112
6.1.4.28	get_accessories_settings	112
6.1.4.29	get_analog_data	112
6.1.4.30	get_bootloader_version	113
6.1.4.31	get_brake_settings	113
6.1.4.32	get_calibration_settings	113
6.1.4.33	get_chart_data	113
6.1.4.34	get_control_settings	114
6.1.4.35	get_controller_name	114
6.1.4.36	get_ctp_settings	114
6.1.4.37	get_debug_read	114
6.1.4.38	get_device_count	115
6.1.4.39	get_device_information	115
6.1.4.40	get_device_name	115
6.1.4.41	get_edges_settings	115
6.1.4.42	get_encoder_information	116
6.1.4.43	get_encoder_settings	116
6.1.4.44	get_engine_settings	116
6.1.4.45	get_entype_settings	116
6.1.4.46	get_enumerate_device_controller_name	116
6.1.4.47	get_enumerate_device_information	117
6.1.4.48	get_enumerate_device_network_information	117

6.1.4.49	get_enumerate_device_serial	117
6.1.4.50	get_enumerate_device_stage_name	117
6.1.4.51	get_extio_settings	118
6.1.4.52	get_feedback_settings	118
6.1.4.53	get_firmware_version	118
6.1.4.54	get_gear_information	119
6.1.4.55	get_gear_settings	119
6.1.4.56	get_globally_unique_identifier	119
6.1.4.57	get_hallsensor_information	119
6.1.4.58	get_hallsensor_settings	119
6.1.4.59	get_home_settings	120
6.1.4.60	get_init_random	120
6.1.4.61	get_joystick_settings	120
6.1.4.62	get_measurements	120
6.1.4.63	get_motor_information	121
6.1.4.64	get_motor_settings	121
6.1.4.65	get_move_settings	121
6.1.4.66	get_nonvolatile_memory	121
6.1.4.67	get_pid_settings	121
6.1.4.68	get_position	122
6.1.4.69	get_power_settings	122
6.1.4.70	get_secure_settings	122
6.1.4.71	get_serial_number	122
6.1.4.72	get_stage_information	123
6.1.4.73	get_stage_name	123
6.1.4.74	get_stage_settings	123
6.1.4.75	get_status	123
6.1.4.76	get_status_calb	123
6.1.4.77	get_sync_in_settings	124
6.1.4.78	get_sync_out_settings	124
6.1.4.79	get_uart_settings	124
6.1.4.80	goto_firmware	124
6.1.4.81	has_firmware	125
6.1.4.82	logging_callback_stderr_narrow	125
6.1.4.83	logging_callback_stderr_wide	125
6.1.4.84	msec_sleep	125
6.1.4.85	open_device	125
6.1.4.86	probe_device	126
6.1.4.87	service_command_updf	126
6.1.4.88	set_accessories_settings	126

6.1.4.89	set_bindy_key	126
6.1.4.90	set_brake_settings	126
6.1.4.91	set_calibration_settings	127
6.1.4.92	set_control_settings	127
6.1.4.93	set_controller_name	127
6.1.4.94	set_ctp_settings	127
6.1.4.95	set_debug_write	128
6.1.4.96	set_edges_settings	128
6.1.4.97	set_encoder_information	128
6.1.4.98	set_encoder_settings	128
6.1.4.99	set_engine_settings	129
6.1.4.100	set_entype_settings	129
6.1.4.101	set_extio_settings	129
6.1.4.102	set_feedback_settings	129
6.1.4.103	set_gear_information	130
6.1.4.104	set_gear_settings	130
6.1.4.105	set_hallsensor_information	130
6.1.4.106	set_hallsensor_settings	130
6.1.4.107	set_home_settings	131
6.1.4.108	set_joystick_settings	131
6.1.4.109	set_logging_callback	131
6.1.4.110	set_motor_information	131
6.1.4.111	set_motor_settings	132
6.1.4.112	set_move_settings	132
6.1.4.113	set_nonvolatile_memory	132
6.1.4.114	set_pid_settings	132
6.1.4.115	set_position	133
6.1.4.116	set_power_settings	133
6.1.4.117	set_secure_settings	133
6.1.4.118	set_serial_number	133
6.1.4.119	set_stage_information	133
6.1.4.120	set_stage_name	134
6.1.4.121	set_stage_settings	134
6.1.4.122	set_sync_in_settings	134
6.1.4.123	set_sync_out_settings	134
6.1.4.124	set_uart_settings	135
6.1.4.125	write_key	135
6.1.4.126	ximc_fix_usbser_sys	135
6.1.4.127	ximc_version	135

Index**135**

Chapter 1

libximc library

Documentation for libximc library.

Libximc is cross-platform library for working with ximc 8SMC4 and 8SMC5 controllers.

Full documentation about ximc controllers is [there](#)

Full documentation about libximc API is available on the page [ximc.h](#).

1.1 About ximc

We offer an inexpensive and ultra-compact servo-drive with USB interface for stepper motors with external power supply. Forget about cumbersome and expensive servo-drives! All you need is a stepper motor, a controller, a USB cable and any stabilized external power supply. That is all! Forget about active coolers as well. Controller's board is about the same size as a notepad or a cellphone, therefore, you may just put it down on the worktable without any assembly procedures. The controller works with any type of compact stepper motors with the rated winding current of up to 3A. Controller works with stepper motors with no feedback as well as with ones equipped with encoders in feedback loop, including linear encoders on the stages. The motor connector on the controller board is the same as one used by Standa company and it fits to all the Standa stages. USB connector provides easy communication and work with computer. Several controllers can be connected to one computer either via USB ports or through a special backplane supplied with multiaxis systems. The controller is fully compatible with the majority of operating systems, e.g., Windows, Mac OS X, Linux, etc.

1.2 About libximc

Congratulations on choosing XIMC multi-platform programming library! This document contains all information about XIMC library. It utilizes well known virtual COM-port interface, so you can use it on Windows 7, Windows Vista, Windows XP, Windows Server 2003, Windows 2000, Linux, Mac OS X. XIMC multi-platform programming library supports plug/unplug on the fly. Each device can be controlled only by one program at once. Multiple processes (programs) that control one device simultaneously are not allowed.

Please read the [Introduction](#) to start work with library.

To use libximc in your project please consult with [How to use with...](#)

Chapter 2

Introduction

2.1 About

Congratulations on choosing XIMC multi-platform programming library! This document contains all information about XIMC library. It utilizes well known virtual COM-port interface, so you can use it on Windows 7, Windows Vista, Windows XP, Windows Server 2003, Windows 2000, Linux, Mac OS X. XIMC multi-platform programming library supports plug/unplug on the fly. Each device can be controlled only by one program at once. Multiple processes (programs) that control one device simultaneously are not allowed.

2.2 System requirements

2.2.1 For rebuilding library

On Windows:

- Windows 2000 or later, 64-bit system (if compiling both architectures) or 32-bit system.
- Microsoft Visual C++ 2013 or later
- cygwin with tar, bison, flex, curl installed
- 7z

On Linux:

- 64-bit or/and 32-bit system
- gcc 4 or later
- common autotools: autoconf, autoheader, aclocal, automake, autoreconf, libtool
- gmake
- doxygen - for building docs
- LaTeX distribution (teTeX or texlive) - for building docs
- flex 2.5.30+
- bison
- mercurial (for building developer version from hg)

On Mac OS X:

- XCode 4
- doxygen
- mactex
- autotools
- mercurial (for building developer version from hg)

If mercurial is used, please enable 'purge' extension by adding to `~/.hgrc` following lines:

```
[extensions]
hgext.purge=
```

2.2.2 For using library

Supported operating systems (32 or 64 bit) and environment requirements:

- Mac OS X 10.6
- Windows 2000 or later
- Autotools-compatible unix. Package is installed from sources.
- Linux debian-based 32 and 64 bit. DEB package is built against Debian Squeeze 7
- Linux debian-based ARM. DEB package is built on Ubuntu 14.04
- Linux rpm-based. RPM is built against OpenSUSE 12
- Java 7 64-bit or 32-bit
- .NET 2.0 (32-bit only)
- Delphi (32-bit only)

Build requirements:

- Windows: Microsoft Visual C++ 2013 or mingw (currently not supported)
- UNIX: gcc 4, gmake
- Mac OS X: XCode 4
- JDK 7

Chapter 3

How to rebuild library

3.1 Building on generic UNIX

Generic version could be built with standard autotools.

```
./build.sh lib
```

Built files (library, headers, documentation) are installed to `./dist/local` directory. It is a generic developer build. Sometimes you need to specify additional parameters to command line for your machine. Please look to following OS sections.

3.2 Building on debian-based linux systems

Requirement: 64-bit and 32-bit debian system, ubuntu Typical set of packages: gcc, autotools, autoconf, libtool, dpkg-dev, flex, bison, doxygen, texlive, mercurial Full set of packages: apt-get install ruby1.9.1 debhelper vim sudo g++ mercurial git curl make cmake autotools-dev automake autoconf libtool default-jre-headless default-jdk openjdk-6-jdk dpkg-dev lintian texlive texlive-latex-extra texlive-lang-cyrillic dh-autoreconf hardening-wrapper bison flex doxygen lsb-release pkg-config check For ARM cross-compiling install gcc-arm-linux-gnueabi from your ARM toolchain.

It's required to match library and host architecture: 64-bit library can be built only at 64-bit host, 32-bit library - only at 32-bit host. ARM library is built with armhf cross-compiler gcc-arm-linux-gnueabi.

To build library and package invoke a script:

```
$ ./build.sh libdeb
```

For ARM library replace 'libdeb' with 'libdebarm'.

Grab packages from `./ximc/deb` and locally installed binaries from `./dist/local`.

3.3 Building on redhat-based linux systems

Requirement: 64-bit redhat-based system (Fedora, Red Hat, SUSE) Typical set of packages: gcc, autotools, autoconf, libtool, flex, bison, doxygen, texlive, mercurial Full set of packages: autoconf automake bison doxygen flex gcc gcc-32bit gcc-c++ gcc-c++-32bit java-1.7.0-openjdk java-1.7.0-openjdk-devel libtool lsb-release make mercurial rpm-build rpm-devel rpmlint texlive texlive-fonts-extra texlive-latex

It's possible to build both 32- and 64-bit libraries on 64-bit host system. 64-bit library can't be built on 32-bit system.

To build library and package invoke a script:

```
$ ./build.sh librpm
```

Grab packages from `./ximc/rpm` and locally installed binaries from `./dist/local`.

3.4 Building on Mac OS X

To build and package a script invoke a script:

```
$ ./build.sh libosx
```

Built library (classical and framework), examples (classical and `.app`), documentation are located at `./ximc/macosex`, locally installed binaries from `./dist/local`.

3.5 Building on Windows

Requirements: 64-bit windows (build script builds both architectures), cygwin (must be installed to a default path), mercurial.

Invoke a script:

```
$ ./build.bat
```

Grab packages from `./deb/win32` and `./deb/win64`

To build debug version of the library set environment variable "DEBUG" to "true" before running the build script.

3.6 Source code access

XIMC source codes are given under special request.

Chapter 4

How to use with...

Library usage can be examined from test application testapp. Non-C languages are supported because library supports stdcall calling convention and so can be used with a variety of languages.

C test project is located at 'examples/testapp' directory, C# test project - at 'examples/testcs', VB.NET - 'examples/testvbnet', Delphi 6 - 'examples/testdelphi', sample bindings for MATLAB - 'examples/testmatlab', for Java - 'examples/testjava', for Python - 'examples/testpython'. Development kit also contains precompiled examples: testapp and testappeasy as 32 and 64-bit applications for Windows and 64-bit application for osx, testcs, testvbnet, testdelphi - 32-bit only, testjava is architecture-independent, testmatlab and testpython are runtime-interpreted.

NOTE: SDK requires Microsoft Visual C++ Redistributable Package (provided with SDK - vc_redist.x86 or vc_redist.x64)

4.1 Usage with C

4.1.1 Visual C++

Testapp can be built using testapp.sln. Library must be compiled with MS Visual C++ too, mingw-library isn't supported. Make sure that Microsoft Visual C++ Redistributable Package is installed.

Open solution examples/testapp/testapp.sln, build and run from the IDE.

4.1.2 CodeBlocks

Testapp can be built using testcodeblocks.cbp. Library must be compiled with MS Visual C++ too, mingw-library isn't supported. Make sure that Microsoft Visual C++ Redistributable Package is installed. *

Open solution examples/testcodeblocks/testcodeblocks.cbp, build and run from the IDE.

4.1.3 MinGW

MinGW is a port of GCC to win32 platform. It's required to install MinGW package. Currently not supported

MinGW-compiled testapp can be built with MS Visual C++ or mingw library.

```
$ mingw32-make -f Makefile.mingw all
```

Then copy library libximc.dll to current directory and launch testapp.exe.

4.1.4 C++ Builder

First of all you should create C++ Builder-style import library. Visual C++ library is not compatible with BCB. Invoke:

```
$ implib libximc.lib libximc.def
```

Then compile test application:

```
$ bcc32 -I..\..\ximc\win32 -L..\..\ximc\win32 -DWIN32 -DNDEBUG -D_WINDOWS
testapp.c libximc.lib
```

4.1.5 XCode

Test app should be built with XCode project testapp.xcodeproj. Library is a Mac OS X framework, and at example application it's bundled inside testapp.app

Then launch application testapp.app and check activity output in Console.app.

4.1.6 GCC

Make sure that libximc (rpm, deb, freebsd package or tarball) is installed at your system. Installation of package should be performed with a package manager of operating system. On OS X a framework is provided.

Note that user should belong to system group which allows access to a serial port (dip or serial, for example).

Copy file /usr/share/libximc/keyfile.sqlite project directory:

```
$ cp /usr/share/libximc/keyfile.sqlite .
```

Test application can be built with the installed library with the following script:

```
$ make
```

In case of cross-compilation (target architecture differs from the current system architecture) feed -m64 or -m32 flag to compiler. On OS X it's needed to use -arch flag instead to build an universal binary. Please consult a compiler documentation.

Then launch the application as:

```
$ make run
```

Note: make run on OS X copies a library to the current directory. If you want to use library from the custom directory please be sure to specify LD_LIBRARY_PATH or DYLD_LIBRARY_PATH to the directory with the library.

4.2 .NET

Wrapper assembly for libximc.dll is wrappers/csharp/ximcnet.dll. It is provided with two different architectures and depends on .NET 2.0.

Test .NET applications for Visual Studio 2013 is located at testcs (for C#) and testvbnet (for VB.NET) respectively. Open solutions and build.

4.3 Delphi

Wrapper for libximc.dll is a unit wrappers/delphi/ximc.pas

Console test application for is located at testdelphi. Tested with Delphi 6 and only 32-bit version.

Just compile, place DLL near the executable and run program.

4.4 Java

How to run example on Linux. Navigate to `ximc-2.x.x/examples/testjava/compiled/` and run:

```
$ cp /usr/share/libximc/keyfile.sqlite .
$ java -cp /usr/share/java/libximc.jar:testjava.jar ru.ximc.TestJava
```

How to run example on Windows or Mac. Navigate to `ximc-2.x.x/examples/testjava/compiled/`. Copy contents of `ximc-2.x.x/ximc/win64` or `ximc-2.x.x/ximc/macosx` accordingly to the current directory. Then run:

```
$ java -classpath libximc.jar -classpath testjava.jar ru.ximc.TestJava
```

How to modify and recompile an example. Navigate to `examples/testjava/compiled`. Sources are embedded in a `testjava.jar`. Extract them:

```
$ jar xvf testjava.jar ru META-INF
```

Then rebuild sources:

```
$ javac -classpath /usr/share/java/libximc.jar -Xlint ru/ximc/TestJava.java
```

or for windows or mac

```
$ javac -classpath libximc.jar -Xlint ru/ximc/TestJava.java
```

Then build a jar:

```
$ jar cmf META-INF/MANIFEST.MF testjava.jar ru
```

4.5 Python

Change current directory to the `examples/testpython`.

Before launch:

On OS X: copy library `ximc/macosx/libximc.framework` to the current directory.

On Linux: you may need to set `LD_LIBRARY_PATH` so Python can locate libraries with `RPATH`. For example, you may need:

```
export LD_LIBRARY_PATH=$LD_LIBRARY_PATH:`pwd`
```

On Windows before the start nothing needs to be done

Launch Python 2 or Python 3:

```
python testpython.py
```

4.6 MATLAB

Sample MATLAB program `testximc.m` is provided at the directory `examples/testmatlab`. On windows copy [ximc.h](#), `libximc.dll`, `bindy.dll`, `xiwrapper.dll` and contents of `ximc/(win32,win64)/wrappers/matlab/` directory to the current directory.

Before launch:

On OS X: copy `ximc/macosx/libximc.framework`, `ximc/macosx/wrappers/ximcm.h`, `ximc/ximc.h` * to the directory `examples/matlab`. Install XCode compatible with Matlab.

On Linux: install `libximc*deb` and `libximc-dev*dev` of target architecture. Then copy `ximc/macosx/wrappers/ximcm.h` to the directory `examples/matlab`. Install gcc compatible with Matlab.

For XCode and gcc version compability check document https://www.mathworks.com/content/dam/mathworks/matlab/systemrequirements/Release2014a_SupportedCompilers.pdf or similar.

On Windows before the start nothing needs to be done

Change current directory in the MATLAB to the `examples/matlab`. Then launch in MATLAB prompt:

```
testximc
```

4.7 Generic logging facility

If you want to turn on file logging, you should run the program that uses `libximc` library with the "XILOG" environment variable set to desired file name. This file will be opened for writing on the first log event and will be closed when the program which uses `libximc` terminates. Data which is sent to/received from the controller is logged along with port open and close events.

4.8 Required permissions

`libximc` generally does not require special permissions to work, it only needs read/write access to USB-serial ports on the system. An exception to this rule is a Windows-only "`fix_usbser_sys()`" function - it needs elevation and will produce null result if run as a regular user.

4.9 C-profiles

C-profiles are header files distributed with the `libximc` library. They enable one to set all controller settings for any of the supported stages with a single function call in a C/C++ program. You may see how to use C-profiles in "`testcprofile`" example directory.

Chapter 5

Data Structure Documentation

5.1 accessories_settings_t Struct Reference

Additional accessories information.

Data Fields

- char [MagneticBrakeInfo](#) [25]
The manufacturer and the part number of magnetic brake, the maximum string length is 24 characters.
- float [MBRatedVoltage](#)
Rated voltage for controlling the magnetic brake (B).
- float [MBRatedCurrent](#)
Rated current for controlling the magnetic brake (A).
- float [MBTorque](#)
Retention moment (mN m).
- unsigned int [MBSettings](#)
Magnetic brake settings flags.
- char [TemperatureSensorInfo](#) [25]
The manufacturer and the part number of the temperature sensor, the maximum string length: 24 characters.
- float [TSMIn](#)
The minimum measured temperature (degrees Celsius) Data type: float.
- float [TSMaX](#)
The maximum measured temperature (degrees Celsius) Data type: float.
- float [TSGrad](#)
The temperature gradient (V/degrees Celsius).
- unsigned int [TSSettings](#)
Temperature sensor settings flags.
- unsigned int [LimitSwitchesSettings](#)
Temperature sensor settings flags.

5.1.1 Detailed Description

Additional accessories information.

See Also

[set_accessories_settings](#)
[get_accessories_settings](#)
[get_accessories_settings](#), [set_accessories_settings](#)

5.1.2 Field Documentation

5.1.2.1 unsigned int LimitSwitchesSettings

[Temperature sensor settings flags.](#)

5.1.2.2 char MagneticBrakeInfo[25]

The manufacturer and the part number of magnetic brake, the maximum string length is 24 characters.

5.1.2.3 float MBRatedCurrent

Rated current for controlling the magnetic brake (A).

Data type: float.

5.1.2.4 float MBRatedVoltage

Rated voltage for controlling the magnetic brake (B).

Data type: float.

5.1.2.5 unsigned int MBSettings

[Magnetic brake settings flags.](#)

5.1.2.6 float MBTorque

Retention moment (mN m).

Data type: float.

5.1.2.7 char TemperatureSensorInfo[25]

The manufacturer and the part number of the temperature sensor, the maximum string length: 24 characters.

5.1.2.8 float TSGrad

The temperature gradient (V/degrees Celsius).

Data type: float.

5.1.2.9 float TSMax

The maximum measured temperature (degrees Celsius) Data type: float.

5.1.2.10 float TSMin

The minimum measured temperature (degrees Celsius) Data type: float.

5.1.2.11 unsigned int TSSettings

[Temperature sensor settings flags.](#)

5.2 analog_data_t Struct Reference

Analog data.

Data Fields

- unsigned int [A1Voltage_ADC](#)
"Voltage on pin 1 winding A" raw data from ADC.
- unsigned int [A2Voltage_ADC](#)
"Voltage on pin 2 winding A" raw data from ADC.
- unsigned int [B1Voltage_ADC](#)
"Voltage on pin 1 winding B" raw data from ADC.
- unsigned int [B2Voltage_ADC](#)
"Voltage on pin 2 winding B" raw data from ADC.
- unsigned int [SupVoltage_ADC](#)
"Voltage on the top of MOSFET full bridge" raw data from ADC.
- unsigned int [ACurrent_ADC](#)
"Winding A current" raw data from ADC.
- unsigned int [BCurrent_ADC](#)
"Winding B current" raw data from ADC.
- unsigned int [FullCurrent_ADC](#)
"Full current" raw data from ADC.
- unsigned int [Temp_ADC](#)
Voltage from temperature sensor, raw data from ADC.
- unsigned int [Joy_ADC](#)
Joystick raw data from ADC.
- unsigned int [Pot_ADC](#)
Voltage on analog input, raw data from ADC.
- unsigned int [L5_ADC](#)
USB supply voltage after the current sense resistor, from ADC.
- unsigned int [H5_ADC](#)
Power supply USB from ADC.
- int [A1Voltage](#)
"Voltage on pin 1 winding A" calibrated data.
- int [A2Voltage](#)
"Voltage on pin 2 winding A" calibrated data.
- int [B1Voltage](#)
"Voltage on pin 1 winding B" calibrated data.
- int [B2Voltage](#)
"Voltage on pin 2 winding B" calibrated data.
- int [SupVoltage](#)
"Voltage on the top of MOSFET full bridge" calibrated data.
- int [ACurrent](#)
"Winding A current" calibrated data.
- int [BCurrent](#)
"Winding B current" calibrated data.
- int [FullCurrent](#)
"Full current" calibrated data.
- int [Temp](#)
Temperature, calibrated data.

- int [Joy](#)
Joystick, calibrated data.
- int [Pot](#)
Analog input, calibrated data.
- int [L5](#)
USB supply voltage after the current sense resistor.
- int [H5](#)
Power supply USB.
- unsigned int **deprecated**
- int [R](#)
Motor winding resistance in mOhms(is only used with stepper motor).
- int [L](#)
Motor winding pseudo inductance in uHn(is only used with stepper motor).

5.2.1 Detailed Description

Analog data.

This structure contains raw analog data from ADC embedded on board. These data used for device testing and deep recalibration by manufacturer only.

See Also

[get_analog_data](#)
[get_analog_data](#)

5.2.2 Field Documentation

5.2.2.1 int A1Voltage

"Voltage on pin 1 winding A" calibrated data.

5.2.2.2 unsigned int A1Voltage_ADC

"Voltage on pin 1 winding A" raw data from ADC.

5.2.2.3 int A2Voltage

"Voltage on pin 2 winding A" calibrated data.

5.2.2.4 unsigned int A2Voltage_ADC

"Voltage on pin 2 winding A" raw data from ADC.

5.2.2.5 int ACurrent

"Winding A current" calibrated data.

5.2.2.6 unsigned int ACurrent_ADC

"Winding A current" raw data from ADC.

5.2.2.7 int B1Voltage

"Voltage on pin 1 winding B" calibrated data.

5.2.2.8 unsigned int B1Voltage_ADC

"Voltage on pin 1 winding B" raw data from ADC.

5.2.2.9 int B2Voltage

"Voltage on pin 2 winding B" calibrated data.

5.2.2.10 unsigned int B2Voltage_ADC

"Voltage on pin 2 winding B" raw data from ADC.

5.2.2.11 int BCurrent

"Winding B current" calibrated data.

5.2.2.12 unsigned int BCurrent_ADC

"Winding B current" raw data from ADC.

5.2.2.13 int FullCurrent

"Full current" calibrated data.

5.2.2.14 unsigned int FullCurrent_ADC

"Full current" raw data from ADC.

5.2.2.15 int Joy

Joystick, calibrated data.

Range: 0..10000

5.2.2.16 unsigned int Joy_ADC

Joystick raw data from ADC.

5.2.2.17 int L

Motor winding pseudo inductance in uHn(is only used with stepper motor).

5.2.2.18 int L5

USB supply voltage after the current sense resistor.

5.2.2.19 unsigned int L5_ADC

USB supply voltage after the current sense resistor, from ADC.

5.2.2.20 int Pot

Analog input, calibrated data.

Range: 0..10000

5.2.2.21 int R

Motor winding resistance in mOhms(is only used with stepper motor).

5.2.2.22 int SupVoltage

"Voltage on the top of MOSFET full bridge" calibrated data.

5.2.2.23 unsigned int SupVoltage_ADC

"Voltage on the top of MOSFET full bridge" raw data from ADC.

5.2.2.24 int Temp

Temperature, calibrated data.

5.2.2.25 unsigned int Temp_ADC

Voltage from temperature sensor, raw data from ADC.

5.3 brake_settings_t Struct Reference

Brake settings.

Data Fields

- unsigned int [t1](#)
Time in ms between turn on motor power and turn off brake.
- unsigned int [t2](#)
Time in ms between turn off brake and moving readiness.
- unsigned int [t3](#)
Time in ms between motor stop and turn on brake.
- unsigned int [t4](#)
Time in ms between turn on brake and turn off motor power.
- unsigned int [BrakeFlags](#)
Brake settings flags.

5.3.1 Detailed Description

Brake settings.

This structure contains parameters of brake control.

See Also

[set_brake_settings](#)
[get_brake_settings](#)
[get_brake_settings](#), [set_brake_settings](#)

5.3.2 Field Documentation

5.3.2.1 unsigned int BrakeFlags

[Brake settings flags](#).

5.3.2.2 unsigned int t1

Time in ms between turn on motor power and turn off brake.

5.3.2.3 unsigned int t2

Time in ms between turn off brake and moving readiness.

All moving commands will execute after this interval.

5.3.2.4 unsigned int t3

Time in ms between motor stop and turn on brake.

5.3.2.5 unsigned int t4

Time in ms between turn on brake and turn off motor power.

5.4 calibration_settings_t Struct Reference

Calibration settings.

Data Fields

- float [CSS1_A](#)
Scaling factor for the analogue measurements of the winding A current.
- float [CSS1_B](#)
Shift factor for the analogue measurements of the winding A current.
- float [CSS2_A](#)
Scaling factor for the analogue measurements of the winding B current.
- float [CSS2_B](#)
Shift factor for the analogue measurements of the winding B current.
- float [FullCurrent_A](#)
Scaling factor for the analogue measurements of the full current.

- float [FullCurrent_B](#)

Shift factor for the analogue measurements of the full current.

5.4.1 Detailed Description

Calibration settings.

This structure contains calibration settings.

See Also

[get_calibration_settings](#)
[set_calibration_settings](#)
[get_calibration_settings](#), [set_calibration_settings](#)

5.4.2 Field Documentation

5.4.2.1 float CSS1_A

Scaling factor for the analogue measurements of the winding A current.

5.4.2.2 float CSS1_B

Shift factor for the analogue measurements of the winding A current.

5.4.2.3 float CSS2_A

Scaling factor for the analogue measurements of the winding B current.

5.4.2.4 float CSS2_B

Shift factor for the analogue measurements of the winding B current.

5.4.2.5 float FullCurrent_A

Scaling factor for the analogue measurements of the full current.

5.4.2.6 float FullCurrent_B

Shift factor for the analogue measurements of the full current.

5.5 calibration_t Struct Reference

Calibration companion structure.

Data Fields

- double [A](#)
Multitplier.
- unsigned int [MicrostepMode](#)
Microstep mode.

5.5.1 Detailed Description

Calibration companion structure.

5.6 `chart_data_t` Struct Reference

Additional device state.

Data Fields

- int [WindingVoltageA](#)
In the case step motor, the voltage across the winding A; in the case of a brushless, the voltage on the first coil, in the case of the only DC.
- int [WindingVoltageB](#)
In the case step motor, the voltage across the winding B; in case of a brushless, the voltage on the second winding, and in the case of DC is not used.
- int [WindingVoltageC](#)
In the case of a brushless, the voltage on the third winding, in the case step motor and DC is not used.
- int [WindingCurrentA](#)
In the case step motor, the current in the coil A; brushless if the current in the first coil, and in the case of a single DC.
- int [WindingCurrentB](#)
In the case step motor, the current in the coil B; brushless if the current in the second coil, and in the case of DC is not used.
- int [WindingCurrentC](#)
In the case of a brushless, the current in the third winding, in the case step motor and DC is not used.
- unsigned int [Pot](#)
Analog input value in ten-thousandths.
- unsigned int [Joy](#)
The joystick position in the ten-thousandths.
- int [DutyCycle](#)
Duty cycle of PWM.

5.6.1 Detailed Description

Additional device state.

This structure contains additional values such as winding's voltages, currents and temperature.

See Also

[get_chart_data](#)
[get_chart_data](#)

5.6.2 Field Documentation

5.6.2.1 int DutyCycle

Duty cycle of PWM.

5.6.2.2 unsigned int Joy

The joystick position in the ten-thousandths.

Range: 0..10000

5.6.2.3 unsigned int Pot

Analog input value in ten-thousandths.

Range: 0..10000

5.6.2.4 int WindingCurrentA

In the case step motor, the current in the coil A; brushless if the current in the first coil, and in the case of a single DC.

5.6.2.5 int WindingCurrentB

In the case step motor, the current in the coil B; brushless if the current in the second coil, and in the case of DC is not used.

5.6.2.6 int WindingCurrentC

In the case of a brushless, the current in the third winding, in the case step motor and DC is not used.

5.6.2.7 int WindingVoltageA

In the case step motor, the voltage across the winding A; in the case of a brushless, the voltage on the first coil, in the case of the only DC.

5.6.2.8 int WindingVoltageB

In the case step motor, the voltage across the winding B; in case of a brushless, the voltage on the second winding, and in the case of DC is not used.

5.6.2.9 int WindingVoltageC

In the case of a brushless, the voltage on the third winding, in the case step motor and DC is not used.

5.7 `command_add_sync_in_action_calb_t` Struct Reference

Data Fields

- float [Position](#)
Desired position or shift.
- unsigned int [Time](#)
Time for which you want to achieve the desired position in microseconds.

5.7.1 Field Documentation

5.7.1.1 float Position

Desired position or shift.

5.7.1.2 unsigned int Time

Time for which you want to achieve the desired position in microseconds.

5.8 `command_add_sync_in_action_t` Struct Reference

This command adds one element of the FIFO commands.

Data Fields

- int [Position](#)
Desired position or shift (whole steps)
- int [uPosition](#)
The fractional part of a position or shift in microsteps.
- unsigned int [Time](#)
Time for which you want to achieve the desired position in microseconds.

5.8.1 Detailed Description

This command adds one element of the FIFO commands.

See Also

[command_add_sync_in_action](#)

5.8.2 Field Documentation

5.8.2.1 unsigned int Time

Time for which you want to achieve the desired position in microseconds.

5.8.2.2 int uPosition

The fractional part of a position or shift in microsteps.

Is only used with stepper motor. Range: -255..255.

5.9 `command_change_motor_t` Struct Reference

Change motor - command for switching output relay.

Data Fields

- unsigned int [Motor](#)
Motor number which it should be switch relay on [0..1].

5.9.1 Detailed Description

Change motor - command for switching output relay.

See Also

[command_change_motor](#)

5.10 control_settings_calb_t Struct Reference

Data Fields

- float [MaxSpeed](#) [10]
Array of speeds using with joystick and button control.
- unsigned int [Timeout](#) [9]
timeout[i] is time in ms, after that max_speed[i+1] is applying.
- unsigned int [MaxClickTime](#)
Maximum click time.
- unsigned int [Flags](#)
Control flags.
- float [DeltaPosition](#)
Shift (delta) of position.

5.10.1 Field Documentation

5.10.1.1 unsigned int Flags

[Control flags.](#)

5.10.1.2 unsigned int MaxClickTime

Maximum click time.

Prior to the expiration of this time the first speed isn't enabled.

5.10.1.3 float MaxSpeed[10]

Array of speeds using with joystick and button control.

5.10.1.4 unsigned int Timeout[9]

timeout[i] is time in ms, after that max_speed[i+1] is applying.

It is using with buttons control only.

5.11 control_settings_t Struct Reference

Control settings.

Data Fields

- unsigned int [MaxSpeed](#) [10]
Array of speeds (full step) using with joystick and button control.
- unsigned int [uMaxSpeed](#) [10]
Array of speeds (1/256 microstep) using with joystick and button control.
- unsigned int [Timeout](#) [9]
timeout[i] is time in ms, after that max_speed[i+1] is applying.
- unsigned int [MaxClickTime](#)
Maximum click time.
- unsigned int [Flags](#)
Control flags.
- int [DeltaPosition](#)
Shift (delta) of position.
- int [uDeltaPosition](#)
Fractional part of the shift in micro steps.

5.11.1 Detailed Description

Control settings.

This structure contains control parameters. When choosing CTL_MODE=1 switches motor control with the joystick. In this mode, the joystick to the maximum engine tends Move at MaxSpeed [i], where i=0 if the previous use This mode is not selected another i. Buttons switch the room rate i. When CTL_MODE=2 is switched on motor control using the Left / right. When you click on the button motor starts to move in the appropriate direction at a speed MaxSpeed [0], at the end of time Timeout[i] motor move at a speed MaxSpeed [i+1]. at Transition from MaxSpeed [i] on MaxSpeed [i+1] to acceleration, as usual. The figure above shows the sensitivity of the joystick feature on its position.

See Also

[set_control_settings](#)
[get_control_settings](#)
[get_control_settings](#), [set_control_settings](#)

5.11.2 Field Documentation

5.11.2.1 unsigned int Flags

[Control flags.](#)

5.11.2.2 unsigned int MaxClickTime

Maximum click time.

Prior to the expiration of this time the first speed isn't enabled.

5.11.2.3 unsigned int MaxSpeed[10]

Array of speeds (full step) using with joystick and button control.

Range: 0..100000.

5.11.2.4 unsigned int Timeout[9]

timeout[i] is time in ms, after that max_speed[i+1] is applying.

It is using with buttons control only.

5.11.2.5 int uDeltaPosition

Fractional part of the shift in micro steps.

Is only used with stepper motor. Range: -255..255.

5.11.2.6 unsigned int uMaxSpeed[10]

Array of speeds (1/256 microstep) using with joystick and button control.

5.12 controller_name_t Struct Reference

Controller user name and flags of setting.

Data Fields

- char [ControllerName](#) [17]
User controller name.
- unsigned int [CtrlFlags](#)
Flags of internal controller settings.

5.12.1 Detailed Description

Controller user name and flags of setting.

See Also

[get_controller_name](#), [set_controller_name](#)

5.12.2 Field Documentation

5.12.2.1 char ControllerName[17]

User controller name.

Can be set by user for his/her convinience. Max string length: 16 chars.

5.12.2.2 unsigned int CtrlFlags

[Flags of internal controller settings.](#)

5.13 ctp_settings_t Struct Reference

Control position settings(is only used with stepper motor).

Data Fields

- unsigned int [CTPMinError](#)
Minimum contrast steps from step motor encoder position, wich set STATE_CTP_ERROR flag.
- unsigned int [CTPFlags](#)
Position control flags.

5.13.1 Detailed Description

Control position settings(is only used with stepper motor).

When controlling the step motor with encoder (CTP_BASE 0) it is possible to detect the loss of steps. The controller knows the number of steps per revolution (GENG :: StepsPerRev) and the encoder resolution (GFBS :: IPT). When the control (flag CTP_ENABLED), the controller stores the current position in the footsteps of SM and the current position of the encoder. Further, at each step of the position encoder is converted into steps and if the difference is greater CTPMinError, a flag STATE_CTP_ERROR and set ALARM state. When controlling the step motor with speed sensor (CTP_BASE 1), the position is controlled by him. The active edge of input clock controller stores the current value of steps. Further, at each turn checks how many steps shifted. When a mismatch CTPMinError a flag STATE_CTP_ERROR and set ALARM state.

See Also

[set.ctp_settings](#)
[get.ctp_settings](#)
[get.ctp_settings, set.ctp_settings](#)

5.13.2 Field Documentation

5.13.2.1 unsigned int CTPFlags

[Position control flags.](#)

5.13.2.2 unsigned int CTPMinError

Minimum contrast steps from step motor encoder position, wich set STATE_CTP_ERROR flag.

Measured in steps step motor.

5.14 debug_read_t Struct Reference

Debug data.

Data Fields

- uint8_t [DebugData](#) [128]
Arbitrary debug data.

5.14.1 Detailed Description

Debug data.

These data are used for device debugging by manufacturer only.

See Also

[get.debug.read](#)

5.14.2 Field Documentation

5.14.2.1 uint8_t DebugData[128]

Arbitrary debug data.

5.15 debug_write_t Struct Reference

Debug data.

Data Fields

- uint8_t [DebugData](#) [128]
Arbitrary debug data.

5.15.1 Detailed Description

Debug data.

These data are used for device debugging by manufacturer only.

See Also

[set.debug.write](#)

5.15.2 Field Documentation

5.15.2.1 uint8_t DebugData[128]

Arbitrary debug data.

5.16 device_information_t Struct Reference

Read command controller information.

Data Fields

- char [Manufacturer](#) [5]
Manufacturer.
- char [ManufacturerId](#) [3]
Manufacturer id.
- char [ProductDescription](#) [9]
Product description.
- unsigned int [Major](#)
The major number of the hardware version.
- unsigned int [Minor](#)

Minor number of the hardware version.

- unsigned int [Release](#)

Number of edits this release of hardware.

5.16.1 Detailed Description

Read command controller information.

The controller responds to this command in any state. Manufacturer field for all XI** devices should contain the string "XIMC" (validation is performed on it) The remaining fields contain information about the device.

See Also

[get_device_information](#)
[get_device_information_impl](#)

5.16.2 Field Documentation

5.16.2.1 unsigned int Major

The major number of the hardware version.

5.16.2.2 unsigned int Minor

Minor number of the hardware version.

5.16.2.3 unsigned int Release

Number of edits this release of hardware.

5.17 device_network_information_t Struct Reference

Device network information structure.

Data Fields

- uint32_t [ipv4](#)
IPv4 address, passed in network byte order (big-endian byte order)
- char [nodename](#) [16]
Name of the Bindy node which hosts the device.
- uint32_t [axis_state](#)
Flags representing device state.
- char [locker_username](#) [16]
Name of the user who locked the device (if any)
- char [locker_nodename](#) [16]
Bindy node name, which was used to lock the device (if any)
- time_t [locked_time](#)
Time the lock was acquired at (UTC, microseconds since the epoch)

5.17.1 Detailed Description

Device network information structure.

5.18 edges_settings_calb_t Struct Reference

Data Fields

- unsigned int [BorderFlags](#)
Border flags.
- unsigned int [EnderFlags](#)
Limit switches flags.
- float [LeftBorder](#)
Left border position, used if BORDER.IS.ENCODER flag is set.
- float [RightBorder](#)
Right border position, used if BORDER.IS.ENCODER flag is set.

5.18.1 Field Documentation

5.18.1.1 unsigned int BorderFlags

[Border flags.](#)

5.18.1.2 unsigned int EnderFlags

[Limit switches flags.](#)

5.18.1.3 float LeftBorder

Left border position, used if BORDER.IS.ENCODER flag is set.

5.18.1.4 float RightBorder

Right border position, used if BORDER.IS.ENCODER flag is set.

5.19 edges_settings_t Struct Reference

Edges settings.

Data Fields

- unsigned int [BorderFlags](#)
Border flags.
- unsigned int [EnderFlags](#)
Limit switches flags.
- int [LeftBorder](#)
Left border position, used if BORDER.IS.ENCODER flag is set.
- int [uLeftBorder](#)

- *Left border position in 1/256 microsteps(used with stepper motor only).*
int [RightBorder](#)
Right border position, used if BORDER.IS.ENCODER flag is set.
- int [uRightBorder](#)
Right border position in 1/256 microsteps.

5.19.1 Detailed Description

Edges settings.

This structure contains border and limit switches settings. Please load new engine settings when you change positioner etc. Please note that wrong engine settings lead to device malfunction, can lead to irreversible damage of board.

See Also

[set_edges_settings](#)
[get_edges_settings](#)
[get_edges_settings](#), [set_edges_settings](#)

5.19.2 Field Documentation

5.19.2.1 unsigned int BorderFlags

[Border flags.](#)

5.19.2.2 unsigned int EnderFlags

[Limit switches flags.](#)

5.19.2.3 int LeftBorder

Left border position, used if BORDER.IS.ENCODER flag is set.

5.19.2.4 int RightBorder

Right border position, used if BORDER.IS.ENCODER flag is set.

5.19.2.5 int uLeftBorder

Left border position in 1/256 microsteps(used with stepper motor only).

Range: -255..255.

5.19.2.6 int uRightBorder

Right border position in 1/256 microsteps.

Used with stepper motor only. Range: -255..255.

5.20 encoder_information_t Struct Reference

Encoder information.

Data Fields

- char [Manufacturer](#) [17]
Manufacturer.
- char [PartNumber](#) [25]
Series and PartNumber.

5.20.1 Detailed Description

Encoder information.

See Also

[set_encoder_information](#)
[get_encoder_information](#)
[get_encoder_information](#), [set_encoder_information](#)

5.20.2 Field Documentation

5.20.2.1 char Manufacturer[17]

Manufacturer.

Max string length: 16 chars.

5.20.2.2 char PartNumber[25]

Series and PartNumber.

Max string length: 24 chars.

5.21 encoder_settings_t Struct Reference

Encoder settings.

Data Fields

- float [MaxOperatingFrequency](#)
Max operation frequency (kHz).
- float [SupplyVoltageMin](#)
Minimum supply voltage (V).
- float [SupplyVoltageMax](#)
Maximum supply voltage (V).
- float [MaxCurrentConsumption](#)
Max current consumption (mA).
- unsigned int [PPR](#)
The number of counts per revolution.
- unsigned int [EncoderSettings](#)
Encoder settings flags.

5.21.1 Detailed Description

Encoder settings.

See Also

[set_encoder_settings](#)
[get_encoder_settings](#)
[get_encoder_settings](#), [set_encoder_settings](#)

5.21.2 Field Documentation

5.21.2.1 unsigned int EncoderSettings

[Encoder settings flags](#).

5.21.2.2 float MaxCurrentConsumption

Max current consumption (mA).

Data type: float.

5.21.2.3 float MaxOperatingFrequency

Max operation frequency (kHz).

Data type: float.

5.21.2.4 float SupplyVoltageMax

Maximum supply voltage (V).

Data type: float.

5.21.2.5 float SupplyVoltageMin

Minimum supply voltage (V).

Data type: float.

5.22 engine_settings_calb_t Struct Reference

Data Fields

- unsigned int [NomVoltage](#)
Rated voltage in tens of mV.
- unsigned int [NomCurrent](#)
Rated current.
- float [NomSpeed](#)
Nominal speed.
- unsigned int [EngineFlags](#)
Flags of engine settings.
- float [Antiplay](#)

Number of pulses or steps for backlash (play) compensation procedure.

- unsigned int [MicrostepMode](#)

Flags of microstep mode.

- unsigned int [StepsPerRev](#)

Number of full steps per revolution(Used with stepper motor only).

5.22.1 Field Documentation

5.22.1.1 float Antiplay

Number of pulses or steps for backlash (play) compensation procedure.

Used if ENGINE_ANTIPLAY flag is set.

5.22.1.2 unsigned int EngineFlags

[Flags of engine settings.](#)

5.22.1.3 unsigned int MicrostepMode

[Flags of microstep mode.](#)

5.22.1.4 unsigned int NomCurrent

Rated current.

Controller will keep current consumed by motor below this value if ENGINE_LIMIT_CURR flag is set. Range: 15..8000

5.22.1.5 float NomSpeed

Nominal speed.

Controller will keep motor speed below this value if ENGINE_LIMIT_RPM flag is set.

5.22.1.6 unsigned int NomVoltage

Rated voltage in tens of mV.

Controller will keep the voltage drop on motor below this value if ENGINE_LIMIT_VOLT flag is set (used with DC only).

5.22.1.7 unsigned int StepsPerRev

Number of full steps per revolution(Used with stepper motor only).

Range: 1..65535.

5.23 engine_settings_t Struct Reference

Movement limitations and settings, related to the motor.

Data Fields

- unsigned int [NomVoltage](#)
Rated voltage in tens of mV.
- unsigned int [NomCurrent](#)
Rated current.
- unsigned int [NomSpeed](#)
Nominal (maximum) speed (in whole steps/s or rpm for DC and stepper motor as a master encoder).
- unsigned int [uNomSpeed](#)
The fractional part of a nominal speed in microsteps (is only used with stepper motor).
- unsigned int [EngineFlags](#)
Flags of engine settings.
- int [Antiplay](#)
Number of pulses or steps for backlash (play) compensation procedure.
- unsigned int [MicrostepMode](#)
Flags of microstep mode.
- unsigned int [StepsPerRev](#)
Number of full steps per revolution(Used with stepper motor only).

5.23.1 Detailed Description

Movement limitations and settings, related to the motor.

This structure contains useful motor settings. These settings specify motor shaft movement algorithm, list of limitations and rated characteristics. All boards are supplied with standard set of engine setting on controller's flash memory. Please load new engine settings when you change motor, encoder, positioner etc. Please note that wrong engine settings lead to device malfunction, can lead to irreversible damage of board.

See Also

[set_engine_settings](#)
[get_engine_settings](#)
[get_engine_settings](#), [set_engine_settings](#)

5.23.2 Field Documentation

5.23.2.1 int Antiplay

Number of pulses or steps for backlash (play) compensation procedure.

Used if ENGINE.ANTIPLAY flag is set.

5.23.2.2 unsigned int EngineFlags

[Flags of engine settings.](#)

5.23.2.3 unsigned int MicrostepMode

[Flags of microstep mode.](#)

5.23.2.4 unsigned int NomCurrent

Rated current.

Controller will keep current consumed by motor below this value if ENGINE_LIMIT_CURR flag is set. Range: 15..8000

5.23.2.5 unsigned int NomSpeed

Nominal (maximum) speed (in whole steps/s or rpm for DC and stepper motor as a master encoder).

Controller will keep motor shaft RPM below this value if ENGINE_LIMIT_RPM flag is set. Range: 1..100000.

5.23.2.6 unsigned int NomVoltage

Rated voltage in tens of mV.

Controller will keep the voltage drop on motor below this value if ENGINE_LIMIT_VOLT flag is set (used with DC only).

5.23.2.7 unsigned int StepsPerRev

Number of full steps per revolution(Used with stepper motor only).

Range: 1..65535.

5.23.2.8 unsigned int uNomSpeed

The fractional part of a nominal speed in microsteps (is only used with stepper motor).

5.24 entype_settings_t Struct Reference

Engine type and driver type settings.

Data Fields

- unsigned int [EngineType](#)
Flags of engine type.
- unsigned int [DriverType](#)
Flags of driver type.

5.24.1 Detailed Description

Engine type and driver type settings.

Parameters

<i>id</i>	an identifier of device
<i>EngineType</i>	engine type
<i>DriverType</i>	driver type

See Also

[get_entype_settings](#), [set_entype_settings](#)

5.24.2 Field Documentation

5.24.2.1 unsigned int DriverType

[Flags of driver type.](#)

5.24.2.2 unsigned int EngineType

[Flags of engine type.](#)

5.25 extio_settings_t Struct Reference

EXTIO settings.

Data Fields

- unsigned int [EXTIOSetupFlags](#)
[External IO setup flags.](#)
- unsigned int [EXTIOModeFlags](#)
[External IO mode flags.](#)

5.25.1 Detailed Description

EXTIO settings.

This structure contains all EXTIO settings. By default input event are signalled through rising front and output states are signalled by high logic state.

See Also

[get_extio_settings](#)
[set_extio_settings](#)
[get_extio_settings](#), [set_extio_settings](#)

5.25.2 Field Documentation

5.25.2.1 unsigned int EXTIOModeFlags

[External IO mode flags.](#)

5.25.2.2 unsigned int EXTIOSetupFlags

[External IO setup flags.](#)

5.26 feedback_settings_t Struct Reference

Feedback settings.

Data Fields

- unsigned int [IPS](#)
The number of encoder counts per shaft revolution.
- unsigned int [FeedbackType](#)
Feedback type.
- unsigned int [FeedbackFlags](#)
Describes feedback flags.
- unsigned int [CountsPerTurn](#)
The number of encoder counts per shaft revolution.

5.26.1 Detailed Description

Feedback settings.

This structure contains feedback settings.

See Also

[get_feedback_settings](#), [set_feedback_settings](#)

5.26.2 Field Documentation

5.26.2.1 unsigned int CountsPerTurn

The number of encoder counts per shaft revolution.

Range: 1..4294967295. To use the CountsPerTurn field, write 0 in the IPS field, otherwise the value from the IPS field will be used.

5.26.2.2 unsigned int FeedbackFlags

[Describes feedback flags.](#)

5.26.2.3 unsigned int FeedbackType

[Feedback type.](#)

5.26.2.4 unsigned int IPS

The number of encoder counts per shaft revolution.

Range: 1..65535. The field is obsolete, it is recommended to write 0 to IPS and use the extended CountsPerTurn field. You may need to update the controller firmware to the latest version.

5.27 gear_information_t Struct Reference

Gear information.

Data Fields

- char [Manufacturer](#) [17]
Manufacturer.
- char [PartNumber](#) [25]
Series and PartNumber.

5.27.1 Detailed Description

Gear information.

See Also

[set_gear_information](#)
[get_gear_information](#)
[get_gear_information](#), [set_gear_information](#)

5.27.2 Field Documentation

5.27.2.1 char Manufacturer[17]

Manufacturer.

Max string length: 16 chars.

5.27.2.2 char PartNumber[25]

Series and PartNumber.

Max string length: 24 chars.

5.28 gear_settings_t Struct Reference

Gear settings.

Data Fields

- float [ReductionIn](#)
Input reduction coefficient.
- float [ReductionOut](#)
Output reduction coefficient.
- float [RatedInputTorque](#)
Max continuous torque (N m).
- float [RatedInputSpeed](#)
Max speed on the input shaft (rpm).
- float [MaxOutputBacklash](#)
Output backlash of the reduction gear(degree).
- float [InputInertia](#)
Equivalent input gear inertia (g cm2).
- float [Efficiency](#)
Reduction gear efficiency (%).

5.28.1 Detailed Description

Gear settings.

See Also

[set_gear_settings](#)
[get_gear_settings](#)
[get_gear_settings](#), [set_gear_settings](#)

5.28.2 Field Documentation

5.28.2.1 float Efficiency

Reduction gear efficiency (%).

Data type: float.

5.28.2.2 float InputInertia

Equivalent input gear inertia (g cm²).

Data type: float.

5.28.2.3 float MaxOutputBacklash

Output backlash of the reduction gear(degree).

Data type: float.

5.28.2.4 float RatedInputSpeed

Max speed on the input shaft (rpm).

Data type: float.

5.28.2.5 float RatedInputTorque

Max continuous torque (N m).

Data type: float.

5.28.2.6 float ReductionIn

Input reduction coefficient.

(Output = (ReductionOut / ReductionIn) * Input) Data type: float.

5.28.2.7 float ReductionOut

Output reduction coefficient.

(Output = (ReductionOut / ReductionIn) * Input) Data type: float.

5.29 `get_position_calb_t` Struct Reference

Data Fields

- float [Position](#)
The position in the engine.
- long_t [EncPosition](#)
Encoder position.

5.29.1 Field Documentation

5.29.1.1 long_t EncPosition

Encoder position.

5.29.1.2 float Position

The position in the engine.

5.30 `get_position_t` Struct Reference

Position information.

Data Fields

- int [Position](#)
The position of the whole steps in the engine.
- int [uPosition](#)
Microstep position is only used with stepper motors.
- long_t [EncPosition](#)
Encoder position.

5.30.1 Detailed Description

Position information.

Useful structure that contains position value in steps and micro for stepper motor and encoder steps of all engines.

See Also

[get_position](#)

5.30.2 Field Documentation

5.30.2.1 long_t EncPosition

Encoder position.

5.31 `globally_unique_identifer_t` Struct Reference

Globally unique identifier.

Data Fields

- unsigned int [UniqueID0](#)
Unique ID 0.
- unsigned int [UniqueID1](#)
Unique ID 1.
- unsigned int [UniqueID2](#)
Unique ID 2.
- unsigned int [UniqueID3](#)
Unique ID 3.

5.31.1 Detailed Description

Globally unique identifier.

See Also

[get_globally_unique_identifier](#)

5.31.2 Field Documentation

5.31.2.1 unsigned int UniqueID0

Unique ID 0.

5.31.2.2 unsigned int UniqueID1

Unique ID 1.

5.31.2.3 unsigned int UniqueID2

Unique ID 2.

5.31.2.4 unsigned int UniqueID3

Unique ID 3.

5.32 hallsensor_information_t Struct Reference

Hall sensor information.

Data Fields

- char [Manufacturer](#) [17]
Manufacturer.
- char [PartNumber](#) [25]
Series and PartNumber.

5.32.1 Detailed Description

Hall sensor information.

See Also

[set_hallsensor_information](#)
[get_hallsensor_information](#)
[get_hallsensor_information](#), [set_hallsensor_information](#)

5.32.2 Field Documentation

5.32.2.1 char Manufacturer[17]

Manufacturer.

Max string length: 16 chars.

5.32.2.2 char PartNumber[25]

Series and PartNumber.

Max string length: 24 chars.

5.33 hallsensor_settings_t Struct Reference

Hall sensor settings.

Data Fields

- float [MaxOperatingFrequency](#)
Max operation frequency (kHz).
- float [SupplyVoltageMin](#)
Minimum supply voltage (V).
- float [SupplyVoltageMax](#)
Maximum supply voltage (V).
- float [MaxCurrentConsumption](#)
Max current consumption (mA).
- unsigned int [PPR](#)
The number of counts per revolution.

5.33.1 Detailed Description

Hall sensor settings.

See Also

[set_hallsensor_settings](#)
[get_hallsensor_settings](#)
[get_hallsensor_settings](#), [set_hallsensor_settings](#)

5.33.2 Field Documentation

5.33.2.1 float MaxCurrentConsumption

Max current consumption (mA).

Data type: float.

5.33.2.2 float MaxOperatingFrequency

Max operation frequency (kHz).

Data type: float.

5.33.2.3 float SupplyVoltageMax

Maximum supply voltage (V).

Data type: float.

5.33.2.4 float SupplyVoltageMin

Minimum supply voltage (V).

Data type: float.

5.34 home_settings_calb_t Struct Reference

Data Fields

- float [FastHome](#)
Speed used for first motion.
- float [SlowHome](#)
Speed used for second motion.
- float [HomeDelta](#)
Distance from break point.
- unsigned int [HomeFlags](#)
Home settings flags.

5.34.1 Field Documentation

5.34.1.1 float FastHome

Speed used for first motion.

5.34.1.2 float HomeDelta

Distance from break point.

5.34.1.3 unsigned int HomeFlags

[Home settings flags.](#)

5.34.1.4 float SlowHome

Speed used for second motion.

5.35 home_settings_t Struct Reference

Position calibration settings.

Data Fields

- unsigned int [FastHome](#)
Speed used for first motion.
- unsigned int [uFastHome](#)
Part of the speed for first motion, microsteps.
- unsigned int [SlowHome](#)
Speed used for second motion.
- unsigned int [uSlowHome](#)
Part of the speed for second motion, microsteps.
- int [HomeDelta](#)
Distance from break point.
- int [uHomeDelta](#)
Part of the delta distance, microsteps.
- unsigned int [HomeFlags](#)
Home settings flags.

5.35.1 Detailed Description

Position calibration settings.

This structure contains settings used in position calibrating. It specify behaviour of calibrating position.

See Also

[get_home_settings](#)
[set_home_settings](#)
[command_home](#)
[get_home_settings](#), [set_home_settings](#)

5.35.2 Field Documentation

5.35.2.1 unsigned int FastHome

Speed used for first motion.

Range: 0..100000.

5.35.2.2 int HomeDelta

Distance from break point.

5.35.2.3 unsigned int HomeFlags

[Home settings flags.](#)

5.35.2.4 unsigned int `SlowHome`

Speed used for second motion.

Range: 0..100000.

5.35.2.5 unsigned int `uFastHome`

Part of the speed for first motion, microsteps.

5.35.2.6 int `uHomeDelta`

Part of the delta distance, microsteps.

Range: -255..255.

5.35.2.7 unsigned int `uSlowHome`

Part of the speed for second motion, microsteps.

5.36 `init_random_t` Struct Reference

Random key.

Data Fields

- `uint8_t key` [16]
Random key.

5.36.1 Detailed Description

Random key.

Structure that contains random key used in encryption of WKEY and SSER command contents.

See Also

[get_init_random](#)

5.36.2 Field Documentation

5.36.2.1 `uint8_t key`[16]

Random key.

5.37 `joystick_settings_t` Struct Reference

Joystick settings.

Data Fields

- unsigned int [JoyLowEnd](#)
Joystick lower end position.
- unsigned int [JoyCenter](#)
Joystick center position.
- unsigned int [JoyHighEnd](#)
Joystick higher end position.
- unsigned int [ExpFactor](#)
Exponential nonlinearity factor.
- unsigned int [DeadZone](#)
Joystick dead zone.
- unsigned int [JoyFlags](#)
Joystick flags.

5.37.1 Detailed Description

Joystick settings.

This structure contains joystick parameters. If joystick position is outside DeadZone limits from the central position a movement with speed, defined by the joystick DeadZone edge to 100% deviation, begins. Joystick positions inside DeadZone limits correspond to zero speed (soft stop of motion) and positions beyond Low and High limits correspond MaxSpeed [i] or -MaxSpeed [i] (see command SCTL), where i = 0 by default and can be changed with left/right buttons (see command SCTL). If next speed in list is zero (both integer and microstep parts), the button press is ignored. First speed in list shouldn't be zero. The relationship between the deviation and the rate is exponential, allowing no switching speed combine high mobility and accuracy.

See Also

[set_joystick_settings](#)
[get_joystick_settings](#)
[get_joystick_settings](#), [set_joystick_settings](#)

5.37.2 Field Documentation

5.37.2.1 unsigned int DeadZone

Joystick dead zone.

5.37.2.2 unsigned int ExpFactor

Exponential nonlinearity factor.

5.37.2.3 unsigned int JoyCenter

Joystick center position.

Range: 0..10000.

5.37.2.4 unsigned int JoyFlags

[Joystick flags](#).

5.37.2.5 unsigned int JoyHighEnd

Joystick higher end position.

Range: 0..10000.

5.37.2.6 unsigned int JoyLowEnd

Joystick lower end position.

Range: 0..10000.

5.38 measurements_t Struct Reference

The buffer holds no more than 25 points.

Data Fields

- int [Speed](#) [25]
Current speed.
- int [Error](#) [25]
Current error.
- unsigned int [Length](#)
Length of actual data in buffer.

5.38.1 Detailed Description

The buffer holds no more than 25 points.

The exact length of the received buffer is reflected in the Length field.

See Also

[measurements](#)
[get_measurements](#)

5.38.2 Field Documentation

5.38.2.1 int Error[25]

Current error.

5.38.2.2 unsigned int Length

Length of actual data in buffer.

5.38.2.3 int Speed[25]

Current speed.

5.39 motor_information_t Struct Reference

motor information.

Data Fields

- char [Manufacturer](#) [17]
Manufacturer.
- char [PartNumber](#) [25]
Series and PartNumber.

5.39.1 Detailed Description

motor information.

See Also

[set_motor_information](#)
[get_motor_information](#)
[get_motor_information](#), [set_motor_information](#)

5.39.2 Field Documentation

5.39.2.1 char Manufacturer[17]

Manufacturer.

Max string length: 16 chars.

5.39.2.2 char PartNumber[25]

Series and PartNumber.

Max string length: 24 chars.

5.40 motor_settings_t Struct Reference

Physical characteristics and limitations of the motor.

Data Fields

- unsigned int [MotorType](#)
Motor Type flags.
- unsigned int [ReservedField](#)
Reserved.
- unsigned int [Poles](#)
Number of pole pairs for DC or BLDC motors or number of steps per rotation for stepper motor.
- unsigned int [Phases](#)
Number of phases for BLDC motors.
- float [NominalVoltage](#)
Nominal voltage on winding (B).

- float [NominalCurrent](#)
Maximum direct current in winding for DC and BLDC engines, nominal current in windings for stepper motor (A).
- float [NominalSpeed](#)
Not used.
- float [NominalTorque](#)
Nominal torque(mN m).
- float [NominalPower](#)
Nominal power(W).
- float [WindingResistance](#)
Resistance of windings for DC engine, each of two windings for stepper motor or each of there windings for BLDC engine(Ohm).
- float [WindingInductance](#)
Inductance of windings for DC engine, each of two windings for stepper motor or each of there windings for BLDC engine(mH).
- float [RotorInertia](#)
Rotor inertia(g cm2).
- float [StallTorque](#)
Torque hold position for a stepper motor or torque at a motionless rotor for other types of engines (mN m).
- float [DetentTorque](#)
Holding torque position with un-powered coils (mN m).
- float [TorqueConstant](#)
Torque constant, which determines the aspect ratio of maximum moment of force from the rotor current flowing in the coil (mN m / A).
- float [SpeedConstant](#)
Velocity constant, which determines the value or amplitude of the induced voltage on the motion of DC or BLDC motor (rpm / V) or stepper motor (steps/s / V).
- float [SpeedTorqueGradient](#)
Speed torque gradient (rpm / mN m).
- float [MechanicalTimeConstant](#)
Mechanical time constant (ms).
- float [MaxSpeed](#)
The maximum speed for stepper motors (steps/s) or DC and BLDC motors (rmp).
- float [MaxCurrent](#)
The maximum current in the winding (A).
- float [MaxCurrentTime](#)
Safe duration of overcurrent in the winding (ms).
- float [NoLoadCurrent](#)
The current consumption in idle mode (A).
- float [NoLoadSpeed](#)
Idle speed (rpm).

5.40.1 Detailed Description

Physical characteristics and limitations of the motor.

See Also

[set_motor_settings](#)
[get_motor_settings](#)
[get_motor_settings](#), [set_motor_settings](#)

5.40.2 Field Documentation

5.40.2.1 float DetentTorque

Holding torque position with un-powered coils (mN m).

Data type: float.

5.40.2.2 float MaxCurrent

The maximum current in the winding (A).

Data type: float.

5.40.2.3 float MaxCurrentTime

Safe duration of overcurrent in the winding (ms).

Data type: float.

5.40.2.4 float MaxSpeed

The maximum speed for stepper motors (steps/s) or DC and BLDC motors (rpm).

Data type: float.

5.40.2.5 float MechanicalTimeConstant

Mechanical time constant (ms).

Data type: float.

5.40.2.6 unsigned int MotorType

[Motor Type flags](#).

5.40.2.7 float NoLoadCurrent

The current consumption in idle mode (A).

Used for DC and BLDC motors. Data type: float.

5.40.2.8 float NoLoadSpeed

Idle speed (rpm).

Used for DC and BLDC motors. Data type: float.

5.40.2.9 float NominalCurrent

Maximum direct current in winding for DC and BLDC engines, nominal current in windings for stepper motor (A).

Data type: float.

5.40.2.10 float NominalPower

Nominal power(W).

Used for DC and BLDC engine. Data type: float.

5.40.2.11 float NominalSpeed

Not used.

Nominal speed(rpm). Used for DC and BLDC engine. Data type: float.

5.40.2.12 float NominalTorque

Nominal torque(mN m).

Used for DC and BLDC engine. Data type: float.

5.40.2.13 float NominalVoltage

Nominal voltage on winding (B).

Data type: float

5.40.2.14 unsigned int Phases

Number of phases for BLDC motors.

5.40.2.15 unsigned int Poles

Number of pole pairs for DC or BLDC motors or number of steps per rotation for stepper motor.

5.40.2.16 float RotorInertia

Rotor inertia(g cm²).

Data type: float.

5.40.2.17 float SpeedConstant

Velocity constant, which determines the value or amplitude of the induced voltage on the motion of DC or BLDC motor (rpm / V) or stepper motor (steps/s / V).

Data type: float.

5.40.2.18 float SpeedTorqueGradient

Speed torque gradient (rpm / mN m).

Data type: float.

5.40.2.19 float StallTorque

Torque hold position for a stepper motor or torque at a motionless rotor for other types of engines (mN m).

Data type: float.

5.40.2.20 float TorqueConstant

Torque constant, which determines the aspect ratio of maximum moment of force from the rotor current flowing in the coil (mN m / A).

Used mainly for DC motors. Data type: float.

5.40.2.21 float WindingInductance

Inductance of windings for DC engine, each of two windings for stepper motor or each of there windings for BLDC engine(mH).

Data type: float.

5.40.2.22 float WindingResistance

Resistance of windings for DC engine, each of two windings for stepper motor or each of there windings for BLDC engine(Ohm).

Data type: float.

5.41 move_settings_calb_t Struct Reference

Data Fields

- float [Speed](#)
Target speed.
- float [Accel](#)
Motor shaft acceleration, steps/s²(stepper motor) or RPM/s(DC).
- float [Decel](#)
Motor shaft deceleration, steps/s²(stepper motor) or RPM/s(DC).
- float [AntiplaySpeed](#)
Speed in antiplay mode.

5.41.1 Field Documentation

5.41.1.1 float Accel

Motor shaft acceleration, steps/s²(stepper motor) or RPM/s(DC).

5.41.1.2 float AntiplaySpeed

Speed in antiplay mode.

5.41.1.3 float Decel

Motor shaft deceleration, steps/s²(stepper motor) or RPM/s(DC).

5.41.1.4 float Speed

Target speed.

5.42 move_settings_t Struct Reference

Move settings.

Data Fields

- unsigned int [Speed](#)
Target speed (for stepper motor: steps/s, for DC: rpm).
- unsigned int [uSpeed](#)
Target speed in microstep fractions/s.
- unsigned int [Accel](#)
Motor shaft acceleration, steps/s²(stepper motor) or RPM/s(DC).
- unsigned int [Decel](#)
Motor shaft deceleration, steps/s²(stepper motor) or RPM/s(DC).
- unsigned int [AntiplaySpeed](#)
Speed in antiplay mode, full steps/s(stepper motor) or RPM(DC).
- unsigned int [uAntiplaySpeed](#)
Speed in antiplay mode, 1/256 microsteps/s.

5.42.1 Detailed Description

Move settings.

See Also

[set_move_settings](#)
[get_move_settings](#)
[get_move_settings](#), [set_move_settings](#)

5.42.2 Field Documentation

5.42.2.1 unsigned int Accel

Motor shaft acceleration, steps/s²(stepper motor) or RPM/s(DC).

Range: 1..65535.

5.42.2.2 unsigned int AntiplaySpeed

Speed in antiplay mode, full steps/s(stepper motor) or RPM(DC).

Range: 0..100000.

5.42.2.3 unsigned int Decel

Motor shaft deceleration, steps/s²(stepper motor) or RPM/s(DC).

Range: 1..65535.

5.42.2.4 unsigned int Speed

Target speed (for stepper motor: steps/s, for DC: rpm).

Range: 0..100000.

5.42.2.5 unsigned int uAntiplaySpeed

Speed in antiplay mode, 1/256 microsteps/s.

Used with stepper motor only.

5.42.2.6 unsigned int uSpeed

Target speed in microstep fractions/s.

Using with stepper motor only.

5.43 nonvolatile_memory_t Struct Reference

Userdata for save into FRAM.

Data Fields

- unsigned int [UserData](#) [7]
User data.

5.43.1 Detailed Description

Userdata for save into FRAM.

See Also

[get_nonvolatile_memory](#), [set_nonvolatile_memory](#)

5.43.2 Field Documentation

5.43.2.1 unsigned int UserData[7]

User data.

Can be set by user for his/her convinience. Each element of the array stores only 32 bits of user data. This is important on systems where an int type contains more than 4 bytes. For example that all amd64 systems.

5.44 pid_settings_t Struct Reference

PID settings.

Data Fields

- unsigned int [KpU](#)
Proportional gain for voltage PID routine.
- unsigned int [KiU](#)
Integral gain for voltage PID routine.
- unsigned int [KdU](#)
Differential gain for voltage PID routine.
- float [Kpf](#)

- float [Kif](#)
Proportional gain for BLDC position PID routine.
- float [Kdf](#)
Integral gain for BLDC position PID routine.
- float [Kdf](#)
Differential gain for BLDC position PID routine.

5.44.1 Detailed Description

PID settings.

This structure contains factors for PID routine. It specify behaviour of PID routine for voltage. These factors are slightly different for different positioners. All boards are supplied with standard set of PID setting on controller's flash memory. Please load new PID settings when you change positioner. Please note that wrong PID settings lead to device malfunction.

See Also

[set_pid_settings](#)
[get_pid_settings](#)
[get_pid_settings](#), [set_pid_settings](#)

5.45 power_settings_t Struct Reference

Step motor power settings.

Data Fields

- unsigned int [HoldCurrent](#)
Current in holding regime, percent of nominal.
- unsigned int [CurrReductDelay](#)
Time in ms from going to STOP state to reducing current.
- unsigned int [PowerOffDelay](#)
Time in s from going to STOP state to turning power off.
- unsigned int [CurrentSetTime](#)
Time in ms to reach nominal current.
- unsigned int [PowerFlags](#)
Flags of power settings of stepper motor.

5.45.1 Detailed Description

Step motor power settings.

See Also

[set_move_settings](#)
[get_move_settings](#)
[get_power_settings](#), [set_power_settings](#)

5.45.2 Field Documentation

5.45.2.1 unsigned int CurrentSetTime

Time in ms to reach nominal current.

5.45.2.2 unsigned int CurrReductDelay

Time in ms from going to STOP state to reducing current.

5.45.2.3 unsigned int HoldCurrent

Current in holding regime, percent of nominal.

Range: 0..100.

5.45.2.4 unsigned int PowerFlags

Flags of power settings of stepper motor.

5.45.2.5 unsigned int PowerOffDelay

Time in s from going to STOP state to turning power off.

5.46 `secure_settings_t` Struct Reference

This structure contains raw analog data from ADC embedded on board.

Data Fields

- unsigned int [LowUpwrOff](#)
Lower voltage limit to turn off the motor, tens of mV.
- unsigned int [CriticalIpwr](#)
Maximum motor current which triggers ALARM state, in mA.
- unsigned int [CriticalUpwr](#)
Maximum motor voltage which triggers ALARM state, tens of mV.
- unsigned int [CriticalT](#)
Maximum temperature, which triggers ALARM state, in tenths of degrees Celcius.
- unsigned int [CriticalIusb](#)
Maximum USB current which triggers ALARM state, in mA.
- unsigned int [CriticalUusb](#)
Maximum USB voltage which triggers ALARM state, tens of mV.
- unsigned int [MinimumUusb](#)
Minimum USB voltage which triggers ALARM state, tens of mV.
- unsigned int [Flags](#)
Flags of secure settings.

5.46.1 Detailed Description

This structure contains raw analog data from ADC embedded on board.

These data used for device testing and deep recalibration by manufacturer only.

See Also

[get_secure_settings](#)
[set_secure_settings](#)
[get_secure_settings](#), [set_secure_settings](#)

5.46.2 Field Documentation

5.46.2.1 unsigned int CriticalPwr

Maximum motor current which triggers ALARM state, in mA.

5.46.2.2 unsigned int CriticalUsb

Maximum USB current which triggers ALARM state, in mA.

5.46.2.3 unsigned int CriticalT

Maximum temperature, which triggers ALARM state, in tenths of degrees Celcius.

5.46.2.4 unsigned int CriticalUpwr

Maximum motor voltage which triggers ALARM state, tens of mV.

5.46.2.5 unsigned int CriticalUusb

Maximum USB voltage which triggers ALARM state, tens of mV.

5.46.2.6 unsigned int Flags

[Flags of secure settings.](#)

5.46.2.7 unsigned int LowUpwrOff

Lower voltage limit to turn off the motor, tens of mV.

5.46.2.8 unsigned int MinimumUusb

Minimum USB voltage which triggers ALARM state, tens of mV.

5.47 serial_number_t Struct Reference

Serial number structure and hardware version.

Data Fields

- unsigned int [SN](#)
New board serial number.
- uint8_t [Key](#) [32]
Protection key (256 bit).
- unsigned int [Major](#)
The major number of the hardware version.
- unsigned int [Minor](#)
Minor number of the hardware version.
- unsigned int [Release](#)
Number of edits this release of hardware.

5.47.1 Detailed Description

Serial number structure and hardware version.

The structure keep new serial number, hardware version and valid key. The SN and hardware version are changed and saved when transmitted key matches stored key. Can be used by manufacturer only.

See Also

[set_serial_number](#)

5.47.2 Field Documentation

5.47.2.1 `uint8_t Key[32]`

Protection key (256 bit).

5.47.2.2 `unsigned int Major`

The major number of the hardware version.

5.47.2.3 `unsigned int Minor`

Minor number of the hardware version.

5.47.2.4 `unsigned int Release`

Number of edits this release of hardware.

5.47.2.5 `unsigned int SN`

New board serial number.

5.48 `set_position_calb_t` Struct Reference

Data Fields

- `float` [Position](#)
The position in the engine.
- `long_t` [EncPosition](#)
Encoder position.
- `unsigned int` [PosFlags](#)
Position setting flags.

5.48.1 Field Documentation

5.48.1.1 `long_t EncPosition`

Encoder position.

5.48.1.2 unsigned int PosFlags

[Position setting flags.](#)

5.48.1.3 float Position

The position in the engine.

5.49 `set_position_t` Struct Reference

Position information.

Data Fields

- int [Position](#)
The position of the whole steps in the engine.
- int [uPosition](#)
Microstep position is only used with stepper motors.
- long_t [EncPosition](#)
Encoder position.
- unsigned int [PosFlags](#)
Position setting flags.

5.49.1 Detailed Description

Position information.

Useful structure that contains position value in steps and micro for stepper motor and encoder steps of all engines.

See Also

[set_position](#)

5.49.2 Field Documentation

5.49.2.1 long_t EncPosition

Encoder position.

5.49.2.2 unsigned int PosFlags

[Position setting flags.](#)

5.50 `stage_information_t` Struct Reference

Stage information.

Data Fields

- char [Manufacturer](#) [17]
Manufacturer.
- char [PartNumber](#) [25]
Series and PartNumber.

5.50.1 Detailed Description

Stage information.

See Also

[set_stage_information](#)
[get_stage_information](#)
[get_stage_information](#), [set_stage_information](#)

5.50.2 Field Documentation

5.50.2.1 char Manufacturer[17]

Manufacturer.

Max string length: 16 chars.

5.50.2.2 char PartNumber[25]

Series and PartNumber.

Max string length: 24 chars.

5.51 stage_name_t Struct Reference

Stage user name.

Data Fields

- char [PositionerName](#) [17]
User positioner name.

5.51.1 Detailed Description

Stage user name.

See Also

[get_stage_name](#), [set_stage_name](#)

5.51.2 Field Documentation

5.51.2.1 char PositionerName[17]

User positioner name.

Can be set by user for his/her convinience. Max string length: 16 chars.

5.52 stage_settings_t Struct Reference

Stage settings.

Data Fields

- float [LeadScrewPitch](#)
Lead screw pitch (mm).
- char [Units](#) [9]
Units for MaxSpeed and TravelRange fields of the structure (steps, degrees, mm, ...).
- float [MaxSpeed](#)
Max speed (Units/c).
- float [TravelRange](#)
Travel range (Units).
- float [SupplyVoltageMin](#)
Supply voltage minimum (V).
- float [SupplyVoltageMax](#)
Supply voltage maximum (V).
- float [MaxCurrentConsumption](#)
Max current consumption (A).
- float [HorizontalLoadCapacity](#)
Horizontal load capacity (kg).
- float [VerticalLoadCapacity](#)
Vertical load capacity (kg).

5.52.1 Detailed Description

Stage settings.

See Also

[set_stage_settings](#)
[get_stage_settings](#)
[get_stage_settings](#), [set_stage_settings](#)

5.52.2 Field Documentation

5.52.2.1 float HorizontalLoadCapacity

Horizontal load capacity (kg).

Data type: float.

5.52.2.2 float LeadScrewPitch

Lead screw pitch (mm).

Data type: float.

5.52.2.3 float MaxCurrentConsumption

Max current consumption (A).

Data type: float.

5.52.2.4 float MaxSpeed

Max speed (Units/c).

Data type: float.

5.52.2.5 float SupplyVoltageMax

Supply voltage maximum (V).

Data type: float.

5.52.2.6 float SupplyVoltageMin

Supply voltage minimum (V).

Data type: float.

5.52.2.7 float TravelRange

Travel range (Units).

Data type: float.

5.52.2.8 char Units[9]

Units for MaxSpeed and TravelRange fields of the structure (steps, degrees, mm, ...).

Max string length: 8 chars.

5.52.2.9 float VerticalLoadCapacity

Vertical load capacity (kg).

Data type: float.

5.53 status_calb_t Struct Reference

Data Fields

- unsigned int [MoveSts](#)
Flags of move state.
- unsigned int [MvCmdSts](#)

- *Move command state.*
unsigned int [PWRSts](#)
Flags of power state of stepper motor.
- unsigned int [EncSts](#)
Encoder state.
- unsigned int [WindSts](#)
Winding state.
- float [CurPosition](#)
Current position.
- long_t [EncPosition](#)
Current encoder position.
- float [CurSpeed](#)
Motor shaft speed.
- int [lpwr](#)
Engine current.
- int [Upwr](#)
Power supply voltage, tens of mV.
- int [lusb](#)
USB current consumption.
- int [Uusb](#)
USB voltage, tens of mV.
- int [CurT](#)
Temperature in tenths of degrees C.
- unsigned int [Flags](#)
Status flags.
- unsigned int [GPIOFlags](#)
Status flags.
- unsigned int [CmdBufFreeSpace](#)
This field shows the amount of free cells buffer synchronization chain.

5.53.1 Field Documentation

5.53.1.1 unsigned int CmdBufFreeSpace

This field shows the amount of free cells buffer synchronization chain.

5.53.1.2 float CurPosition

Current position.

5.53.1.3 float CurSpeed

Motor shaft speed.

5.53.1.4 int CurT

Temperature in tenths of degrees C.

5.53.1.5 long_t EncPosition

Current encoder position.

5.53.1.6 unsigned int EncSts

[Encoder state.](#)

5.53.1.7 unsigned int Flags

[Status flags.](#)

5.53.1.8 unsigned int GPIOFlags

[Status flags.](#)

5.53.1.9 int Ipwr

Engine current.

5.53.1.10 int Iusb

USB current consumption.

5.53.1.11 unsigned int MoveSts

[Flags of move state.](#)

5.53.1.12 unsigned int MvCmdSts

[Move command state.](#)

5.53.1.13 unsigned int PWRSts

[Flags of power state of stepper motor.](#)

5.53.1.14 int Upwr

Power supply voltage, tens of mV.

5.53.1.15 int Uusb

USB voltage, tens of mV.

5.53.1.16 unsigned int WindSts

[Winding state.](#)

5.54 status_t Struct Reference

Device state.

Data Fields

- unsigned int [MoveSts](#)
Flags of move state.
- unsigned int [MvCmdSts](#)
Move command state.
- unsigned int [PWRSts](#)
Flags of power state of stepper motor.
- unsigned int [EncSts](#)
Encoder state.
- unsigned int [WindSts](#)
Winding state.
- int [CurPosition](#)
Current position.
- int [uCurPosition](#)
Step motor shaft position in 1/256 microsteps.
- long_t [EncPosition](#)
Current encoder position.
- int [CurSpeed](#)
Motor shaft speed.
- int [uCurSpeed](#)
Part of motor shaft speed in 1/256 microsteps.
- int [lpwr](#)
Engine current.
- int [Upwr](#)
Power supply voltage, tens of mV.
- int [lusb](#)
USB current consumption.
- int [Uusb](#)
USB voltage, tens of mV.
- int [CurT](#)
Temperature in tenths of degrees C.
- unsigned int [Flags](#)
Status flags.
- unsigned int [GPIOFlags](#)
Status flags.
- unsigned int [CmdBufFreeSpace](#)
This field shows the amount of free cells buffer synchronization chain.

5.54.1 Detailed Description

Device state.

Useful structure that contains current controller state, including speed, position and boolean flags.

See Also

`get_status_impl`

5.54.2 Field Documentation

5.54.2.1 unsigned int CmdBufFreeSpace

This field shows the amount of free cells buffer synchronization chain.

5.54.2.2 int CurPosition

Current position.

5.54.2.3 int CurSpeed

Motor shaft speed.

5.54.2.4 int CurT

Temperature in tenths of degrees C.

5.54.2.5 long_t EncPosition

Current encoder position.

5.54.2.6 unsigned int EncSts

Encoder state.

5.54.2.7 unsigned int Flags

Status flags.

5.54.2.8 unsigned int GPIOFlags

Status flags.

5.54.2.9 int Ipwr

Engine current.

5.54.2.10 int Iusb

USB current consumption.

5.54.2.11 unsigned int MoveSts

Flags of move state.

5.54.2.12 unsigned int MvCmdSts

Move command state.

5.54.2.13 unsigned int PWRSts

Flags of power state of stepper motor.

5.54.2.14 int uCurPosition

Step motor shaft position in 1/256 microsteps.

Used only with stepper motor.

5.54.2.15 int uCurSpeed

Part of motor shaft speed in 1/256 microsteps.

Used only with stepper motor.

5.54.2.16 int Upwr

Power supply voltage, tens of mV.

5.54.2.17 int Uusb

USB voltage, tens of mV.

5.54.2.18 unsigned int WindSts

[Winding state](#).

5.55 sync_in_settings_calb_t Struct Reference

Data Fields

- unsigned int [SyncInFlags](#)
Flags for synchronization input setup.
- unsigned int [ClutterTime](#)
Input synchronization pulse dead time (mks).
- float [Position](#)
Desired position or shift.
- float [Speed](#)
Target speed.

5.55.1 Field Documentation

5.55.1.1 unsigned int ClutterTime

Input synchronization pulse dead time (mks).

5.55.1.2 float Position

Desired position or shift.

5.55.1.3 float Speed

Target speed.

5.55.1.4 unsigned int SyncInFlags

[Flags for synchronization input setup.](#)

5.56 sync_in_settings_t Struct Reference

Synchronization settings.

Data Fields

- unsigned int [SyncInFlags](#)
Flags for synchronization input setup.
- unsigned int [ClutterTime](#)
Input synchronization pulse dead time (mks).
- int [Position](#)
Desired position or shift (whole steps)
- int [uPosition](#)
The fractional part of a position or shift in microsteps.
- unsigned int [Speed](#)
Target speed (for stepper motor: steps/s, for DC: rpm).
- unsigned int [uSpeed](#)
Target speed in microsteps/s.

5.56.1 Detailed Description

Synchronization settings.

This structure contains all synchronization settings, modes, periods and flags. It specifies behaviour of input synchronization. All boards are supplied with standard set of these settings.

See Also

[get_sync_in_settings](#)
[set_sync_in_settings](#)
[get_sync_in_settings](#), [set_sync_in_settings](#)

5.56.2 Field Documentation

5.56.2.1 unsigned int ClutterTime

Input synchronization pulse dead time (mks).

5.56.2.2 unsigned int Speed

Target speed (for stepper motor: steps/s, for DC: rpm).

Range: 0..100000.

5.56.2.3 unsigned int SyncInFlags

[Flags for synchronization input setup.](#)

5.56.2.4 int uPosition

The fractional part of a position or shift in microsteps.

Is used with stepper motor. Range: -255..255.

5.56.2.5 unsigned int uSpeed

Target speed in microsteps/s.

Using with stepper motor only.

5.57 sync_out_settings_calb_t Struct Reference

Data Fields

- unsigned int [SyncOutFlags](#)
Flags of synchronization output.
- unsigned int [SyncOutPulseSteps](#)
This value specifies duration of output pulse.
- unsigned int [SyncOutPeriod](#)
This value specifies number of encoder pulses or steps between two output synchronization pulses when SYNCOUT_ONPERIOD is set.
- float [Accuracy](#)
This is the neighborhood around the target coordinates, which is getting hit in the target position and the momentum generated by the stop.

5.57.1 Field Documentation

5.57.1.1 float Accuracy

This is the neighborhood around the target coordinates, which is getting hit in the target position and the momentum generated by the stop.

5.57.1.2 unsigned int SyncOutFlags

[Flags of synchronization output.](#)

5.57.1.3 unsigned int SyncOutPeriod

This value specifies number of encoder pulses or steps between two output synchronization pulses when SYNCOUT_ONPERIOD is set.

5.57.1.4 unsigned int SyncOutPulseSteps

This value specifies duration of output pulse.

It is measured microseconds when SYNCOUT_IN_STEPS flag is cleared or in encoder pulses or motor steps when SYNCOUT_IN_STEPS is set.

5.58 sync_out_settings_t Struct Reference

Synchronization settings.

Data Fields

- unsigned int [SyncOutFlags](#)
Flags of synchronization output.
- unsigned int [SyncOutPulseSteps](#)
This value specifies duration of output pulse.
- unsigned int [SyncOutPeriod](#)
This value specifies number of encoder pulses or steps between two output synchronization pulses when SYNCOUT_ONPERIOD is set.
- unsigned int [Accuracy](#)
This is the neighborhood around the target coordinates, which is getting hit in the target position and the momentum generated by the stop.
- unsigned int [uAccuracy](#)
This is the neighborhood around the target coordinates in micro steps (only used with stepper motor).

5.58.1 Detailed Description

Synchronization settings.

This structure contains all synchronization settings, modes, periods and flags. It specifies behaviour of output synchronization. All boards are supplied with standard set of these settings.

See Also

[get_sync_out_settings](#)
[set_sync_out_settings](#)
[get_sync_out_settings](#), [set_sync_out_settings](#)

5.58.2 Field Documentation

5.58.2.1 unsigned int Accuracy

This is the neighborhood around the target coordinates, which is getting hit in the target position and the momentum generated by the stop.

5.58.2.2 unsigned int SyncOutFlags

[Flags of synchronization output.](#)

5.58.2.3 unsigned int SyncOutPeriod

This value specifies number of encoder pulses or steps between two output synchronization pulses when SYNCOUT_ONPERIOD is set.

5.58.2.4 unsigned int SyncOutPulseSteps

This value specifies duration of output pulse.

It is measured microseconds when SYNCOUT_IN_STEPS flag is cleared or in encoder pulses or motor steps when SYNCOUT_IN_STEPS is set.

5.58.2.5 unsigned int `uAccuracy`

This is the neighborhood around the target coordinates in micro steps (only used with stepper motor).

5.59 `uart_settings_t` Struct Reference

UART settings.

Data Fields

- unsigned int [Speed](#)
UART speed.
- unsigned int [UARTSetupFlags](#)
UART parity flags.

5.59.1 Detailed Description

UART settings.

This structure contains UART settings.

See Also

[get_uart_settings](#)
[set_uart_settings](#)
[get_uart_settings](#), [set_uart_settings](#)

5.59.2 Field Documentation

5.59.2.1 unsigned int `UARTSetupFlags`

[UART parity flags.](#)

Chapter 6

File Documentation

6.1 ximc.h File Reference

Header file for libximc library.

Data Structures

- struct [calibration_t](#)
Calibration companion structure.
- struct [device_network_information_t](#)
Device network information structure.
- struct [feedback_settings_t](#)
Feedback settings.
- struct [home_settings_t](#)
Position calibration settings.
- struct [home_settings_calb_t](#)
- struct [move_settings_t](#)
Move settings.
- struct [move_settings_calb_t](#)
- struct [engine_settings_t](#)
Movement limitations and settings, related to the motor.
- struct [engine_settings_calb_t](#)
- struct [entype_settings_t](#)
Engine type and driver type settings.
- struct [power_settings_t](#)
Step motor power settings.
- struct [secure_settings_t](#)
This structure contains raw analog data from ADC embedded on board.
- struct [edges_settings_t](#)
Edges settings.
- struct [edges_settings_calb_t](#)
- struct [pid_settings_t](#)
PID settings.
- struct [sync_in_settings_t](#)
Synchronization settings.
- struct [sync_in_settings_calb_t](#)
- struct [sync_out_settings_t](#)

Synchronization settings.

- struct [sync_out_settings_calb_t](#)
- struct [extio_settings_t](#)

EXTIO settings.

- struct [brake_settings_t](#)

Brake settings.

- struct [control_settings_t](#)

Control settings.

- struct [control_settings_calb_t](#)
- struct [joystick_settings_t](#)

Joystick settings.

- struct [ctp_settings_t](#)

Control position settings(is only used with stepper motor).

- struct [uart_settings_t](#)

UART settings.

- struct [calibration_settings_t](#)

Calibration settings.

- struct [controller_name_t](#)

Controller user name and flags of setting.

- struct [nonvolatile_memory_t](#)

Userdata for save into FRAM.

- struct [command_add_sync_in_action_t](#)

This command adds one element of the FIFO commands.

- struct [command_add_sync_in_action_calb_t](#)
- struct [get_position_t](#)

Position information.

- struct [get_position_calb_t](#)
- struct [set_position_t](#)

Position information.

- struct [set_position_calb_t](#)
- struct [status_t](#)

Device state.

- struct [status_calb_t](#)
- struct [measurements_t](#)

The buffer holds no more than 25 points.

- struct [chart_data_t](#)

Additional device state.

- struct [device_information_t](#)

Read command controller information.

- struct [serial_number_t](#)

Serial number structure and hardware version.

- struct [analog_data_t](#)

Analog data.

- struct [debug_read_t](#)

Debug data.

- struct [debug_write_t](#)

Debug data.

- struct [stage_name_t](#)

Stage user name.

- struct [stage_information_t](#)

Stage information.

- struct [stage_settings_t](#)
Stage settings.
- struct [motor_information_t](#)
motor information.
- struct [motor_settings_t](#)
Physical characteristics and limitations of the motor.
- struct [encoder_information_t](#)
Encoder information.
- struct [encoder_settings_t](#)
Encoder settings.
- struct [hallsensor_information_t](#)
Hall sensor information.
- struct [hallsensor_settings_t](#)
Hall sensor settings.
- struct [gear_information_t](#)
Gear information.
- struct [gear_settings_t](#)
Gear settings.
- struct [accessories_settings_t](#)
Additional accessories information.
- struct [init_random_t](#)
Random key.
- struct [globally_unique_identifier_t](#)
Globally unique identifier.
- struct [command_change_motor_t](#)
Change motor - command for switching output relay.

Macros

- #define [XIMC_API](#)
Library import macro Macros allows to automatically import function from shared library.
- #define [XIMC_CALLCONV](#)
Library calling convention macros.
- #define [XIMC_RETTYPE](#) void*
Thread return type.
- #define [device_undefined](#) -1
Handle specified undefined device.

Result statuses

- #define [result_ok](#) 0
success
- #define [result_error](#) -1
generic error
- #define [result_not_implemented](#) -2
function is not implemented
- #define [result_value_error](#) -3
value error
- #define [result_nodevice](#) -4
device is lost

Logging level

- #define [LOGLEVEL_ERROR](#) 0x01
Logging level - error.
- #define [LOGLEVEL_WARNING](#) 0x02
Logging level - warning.
- #define [LOGLEVEL_INFO](#) 0x03
Logging level - info.
- #define [LOGLEVEL_DEBUG](#) 0x04
Logging level - debug.

Enumerate devices flags

- #define [ENUMERATE_PROBE](#) 0x01
Check if a device with OS name name is XIMC device.
- #define [ENUMERATE_ALL_COM](#) 0x02
Check all COM devices.
- #define [ENUMERATE_NETWORK](#) 0x04
Check network devices.

Flags of move state

Specify move states.

See Also

[get_status](#)
[status_t::move_state](#)
[status_t::MoveSts](#), [get_status_impl](#)

- #define [MOVE_STATE_MOVING](#) 0x01
This flag indicates that controller is trying to move the motor.
- #define [MOVE_STATE_TARGET_SPEED](#) 0x02
Target speed is reached, if flag set.
- #define [MOVE_STATE_ANTIPLAY](#) 0x04
Motor is playing compensation, if flag set.

Flags of internal controller settings

See Also

[set_controller_name](#)
[get_controller_name](#)
[controller_name_t::CtrlFlags](#), [get_controller_name](#), [set_controller_name](#)

- #define [EEPROM_PRECEDENCE](#) 0x01
If the flag is set settings from external EEPROM override controller settings.

Flags of power state of stepper motor

Specify power states.

See Also

[status_t::power_state](#)
[get_status](#)
[status_t::PWRSts](#), [get_status_impl](#)

- #define [PWR_STATE_UNKNOWN](#) 0x00
Unknown state, should never happen.
- #define [PWR_STATE_OFF](#) 0x01
Motor windings are disconnected from the driver.
- #define [PWR_STATE_NORM](#) 0x03
Motor windings are powered by nominal current.

- #define [PWR.STATE.REDUCT](#) 0x04
Motor windings are powered by reduced current to lower power consumption.
- #define [PWR.STATE.MAX](#) 0x05
Motor windings are powered by maximum current driver can provide at this voltage.

Status flags

GPIO state flags returned by device query. Contains boolean part of controller state. May be combined with bitwise OR.

See Also

[status_t::flags](#)
[get_status](#)
[status_t::GPIOFlags](#), [get_status_impl](#)

- #define [STATE.CONTR](#) 0x00003F
Flags of controller states.
- #define [STATE.ERRC](#) 0x000001
Command error encountered.
- #define [STATE.ERRD](#) 0x000002
Data integrity error encountered.
- #define [STATE.ERRV](#) 0x000004
Value error encountered.
- #define [STATE.EEPROM.CONNECTED](#) 0x000010
EEPROM with settings is connected.
- #define [STATE.IS.HOMED](#) 0x000020
Calibration performed.
- #define [STATE.SECUR](#) 0x73FFC0
Flags of security.
- #define [STATE.ALARM](#) 0x000040
Controller is in alarm state indicating that something dangerous had happened.
- #define [STATE.CTP.ERROR](#) 0x000080
Control position error(is only used with stepper motor).
- #define [STATE.POWER.OVERHEAT](#) 0x000100
Power driver overheat.
- #define [STATE.CONTROLLER.OVERHEAT](#) 0x000200
Controller overheat.
- #define [STATE.OVERLOAD.POWER.VOLTAGE](#) 0x000400
Power voltage exceeds safe limit.
- #define [STATE.OVERLOAD.POWER.CURRENT](#) 0x000800
Power current exceeds safe limit.
- #define [STATE.OVERLOAD.USB.VOLTAGE](#) 0x001000
USB voltage exceeds safe limit.
- #define [STATE.LOW.USB.VOLTAGE](#) 0x002000
USB voltage is insufficient for normal operation.
- #define [STATE.OVERLOAD.USB.CURRENT](#) 0x004000
USB current exceeds safe limit.
- #define [STATE.BORDERS.SWAP.MISSET](#) 0x008000
Engine stuck at the wrong edge.
- #define [STATE.LOW.POWER.VOLTAGE](#) 0x010000
Power voltage is lower than Low Voltage Protection limit.
- #define [STATE.H.BRIDGE.FAULT](#) 0x020000
Signal from the driver that fault happened.
- #define [STATE.CURRENT.MOTOR.BITS](#) 0x0C0000
Bits indicating the current operating motor on boards with multiple outputs for engine mounting.
- #define [STATE.CURRENT.MOTOR0](#) 0x000000
Motor 0.
- #define [STATE.CURRENT.MOTOR1](#) 0x040000
Motor 1.

- #define [STATE_CURRENT_MOTOR2](#) 0x080000
Motor 2.
- #define [STATE_CURRENT_MOTOR3](#) 0x0C0000
Motor 3.
- #define [STATE_WINDING_RES_MISMATCH](#) 0x100000
The difference between winding resistances is too large.
- #define [STATE_ENCODER_FAULT](#) 0x200000
Signal from the encoder that fault happened.
- #define [STATE_MOTOR_CURRENT_LIMIT](#) 0x400000
Current limit exceeded.
- #define [STATE_DIG_SIGNAL](#) 0xFFFF
Flags of digital signals.
- #define [STATE_RIGHT_EDGE](#) 0x0001
Engine stuck at the right edge.
- #define [STATE_LEFT_EDGE](#) 0x0002
Engine stuck at the left edge.
- #define [STATE_BUTTON_RIGHT](#) 0x0004
Button "right" state (1 if pressed).
- #define [STATE_BUTTON_LEFT](#) 0x0008
Button "left" state (1 if pressed).
- #define [STATE_GPIO_PINOUT](#) 0x0010
External GPIO works as Out, if flag set; otherwise works as In.
- #define [STATE_GPIO_LEVEL](#) 0x0020
State of external GPIO pin.
- #define [STATE_BRAKE](#) 0x0200
State of Brake pin.
- #define [STATE_REV_SENSOR](#) 0x0400
State of Revolution sensor pin.
- #define [STATE_SYNC_INPUT](#) 0x0800
State of Sync input pin.
- #define [STATE_SYNC_OUTPUT](#) 0x1000
State of Sync output pin.
- #define [STATE_ENC_A](#) 0x2000
State of encoder A pin.
- #define [STATE_ENC_B](#) 0x4000
State of encoder B pin.

Encoder state

Encoder state returned by device query.

See Also

[status_t::encsts](#)
[get_status](#)
[status_t::EncSts](#), [get_status_impl](#)

- #define [ENC_STATE_ABSENT](#) 0x00
Encoder is absent.
- #define [ENC_STATE_UNKNOWN](#) 0x01
Encoder state is unknown.
- #define [ENC_STATE_MALFUNC](#) 0x02
Encoder is connected and malfunctioning.
- #define [ENC_STATE_REVERS](#) 0x03
Encoder is connected and operational but counts in other direction.
- #define [ENC_STATE_OK](#) 0x04
Encoder is connected and working properly.

Winding state

Motor winding state returned by device query.

See Also

`status_t::windsts`

[`get_status`](#)

`status_t::WindSts`, [`get_status_impl`](#)

- #define [WIND_A.STATE_ABSENT](#) 0x00
Winding A is disconnected.
- #define [WIND_A.STATE_UNKNOWN](#) 0x01
Winding A state is unknown.
- #define [WIND_A.STATE_MALFUNC](#) 0x02
Winding A is short-circuited.
- #define [WIND_A.STATE_OK](#) 0x03
Winding A is connected and working properly.
- #define [WIND_B.STATE_ABSENT](#) 0x00
Winding B is disconnected.
- #define [WIND_B.STATE_UNKNOWN](#) 0x10
Winding B state is unknown.
- #define [WIND_B.STATE_MALFUNC](#) 0x20
Winding B is short-circuited.
- #define [WIND_B.STATE_OK](#) 0x30
Winding B is connected and working properly.

Move command state

Move command (`command_move`, `command_mvr`, `command_left`, `command_right`, `command_stop`, `command_home`, `command_loft`, `command_sstp`) and its state (`run`, `finished`, `error`).

See Also

`status_t::mvcmdsts`

[`get_status`](#)

`status_t::MvCmdSts`, [`get_status_impl`](#)

- #define [MVCMD.NAME_BITS](#) 0x3F
Move command bit mask.
- #define [MVCMD.UKNWN](#) 0x00
Unknown command.
- #define [MVCMD.MOVE](#) 0x01
Command move.
- #define [MVCMD.MOVR](#) 0x02
Command mvr.
- #define [MVCMD.LEFT](#) 0x03
Command left.
- #define [MVCMD.RIGHT](#) 0x04
Command right.
- #define [MVCMD.STOP](#) 0x05
Command stop.
- #define [MVCMD.HOME](#) 0x06
Command home.
- #define [MVCMD.LOFT](#) 0x07
Command loft.
- #define [MVCMD.SSTP](#) 0x08
Command soft stop.
- #define [MVCMD.ERROR](#) 0x40
Finish state (1 - move command have finished with an error, 0 - move command have finished correctly).
- #define [MVCMD.RUNNING](#) 0x80
Move command state (0 - move command have finished, 1 - move command is being executed).

Flags of engine settings

Specify motor shaft movement algorithm and list of limitations. Flags returned by query of engine settings. May be combined with bitwise OR.

See Also

[engine_settings_t::flags](#)
[set_engine_settings](#)
[get_engine_settings](#)
[engine_settings_t::EngineFlags](#), [get_engine_settings](#), [set_engine_settings](#)

- #define [ENGINE_REVERSE](#) 0x01
Reverse flag.
- #define [ENGINE_CURRENT_AS_RMS](#) 0x02
Engine current meaning flag.
- #define [ENGINE_MAX_SPEED](#) 0x04
Max speed flag.
- #define [ENGINE АнтиPLAY](#) 0x08
Play compensation flag.
- #define [ENGINE_ACCEL_ON](#) 0x10
Acceleration enable flag.
- #define [ENGINE_LIMIT_VOLT](#) 0x20
Maximum motor voltage limit enable flag(is only used with DC motor).
- #define [ENGINE_LIMIT_CURR](#) 0x40
Maximum motor current limit enable flag(is only used with DC motor).
- #define [ENGINE_LIMIT_RPM](#) 0x80
Maximum motor speed limit enable flag.

Flags of microstep mode

Specify settings of microstep mode. Using with step motors. Flags returned by query of engine settings. May be combined with bitwise OR

See Also

[engine_settings_t::flags](#)
[set_engine_settings](#)
[get_engine_settings](#)
[engine_settings_t::MicrostepMode](#), [get_engine_settings](#), [set_engine_settings](#)

- #define [MICROSTEP_MODE_FULL](#) 0x01
Full step mode.
- #define [MICROSTEP_MODE_FRAC_2](#) 0x02
1/2 step mode.
- #define [MICROSTEP_MODE_FRAC_4](#) 0x03
1/4 step mode.
- #define [MICROSTEP_MODE_FRAC_8](#) 0x04
1/8 step mode.
- #define [MICROSTEP_MODE_FRAC_16](#) 0x05
1/16 step mode.
- #define [MICROSTEP_MODE_FRAC_32](#) 0x06
1/32 step mode.
- #define [MICROSTEP_MODE_FRAC_64](#) 0x07
1/64 step mode.
- #define [MICROSTEP_MODE_FRAC_128](#) 0x08
1/128 step mode.
- #define [MICROSTEP_MODE_FRAC_256](#) 0x09
1/256 step mode.

Flags of engine type

Specify motor type. Flags returned by query of engine settings.

See Also

[engine_settings_t::flags](#)
[set_entype_settings](#)
[get_entype_settings](#)
[entype_settings_t::EngineType](#), [get_entype_settings](#), [set_entype_settings](#)

- #define [ENGINE_TYPE_NONE](#) 0x00
A value that shouldn't be used.
- #define [ENGINE_TYPE_DC](#) 0x01
DC motor.
- #define [ENGINE_TYPE_2DC](#) 0x02
2 DC motors.
- #define [ENGINE_TYPE_STEP](#) 0x03
Step motor.
- #define [ENGINE_TYPE_TEST](#) 0x04
Duty cycle are fixed.
- #define [ENGINE_TYPE_BRUSHLESS](#) 0x05
Brushless motor.

Flags of driver type

Specify driver type. Flags returned by query of engine settings.

See Also

[engine_settings_t::flags](#)
[set_entype_settings](#)
[get_entype_settings](#)
[entype_settings_t::DriverType](#), [get_entype_settings](#), [set_entype_settings](#)

- #define [DRIVER_TYPE_DISCRETE_FET](#) 0x01
Driver with discrete FET keys.
- #define [DRIVER_TYPE_INTEGRATE](#) 0x02
Driver with integrated IC.
- #define [DRIVER_TYPE_EXTERNAL](#) 0x03
External driver.

Flags of power settings of stepper motor

Specify power settings. Flags returned by query of power settings.

See Also

[power_settings_t::flags](#)
[get_power_settings](#)
[set_power_settings](#)
[power_settings_t::PowerFlags](#), [get_power_settings](#), [set_power_settings](#)

- #define [POWER_REDUCT_ENABLED](#) 0x01
Current reduction enabled after CurrReductDelay, if this flag is set.
- #define [POWER_OFF_ENABLED](#) 0x02
Power off enabled after PowerOffDelay, if this flag is set.
- #define [POWER_SMOOTH_CURRENT](#) 0x04
Current ramp-up/down is performed smoothly during current.set.time, if this flag is set.

Flags of secure settings

Specify secure settings. Flags returned by query of secure settings.

See Also

[secure_settings.t::flags](#)
[get_secure_settings](#)
[set_secure_settings](#)
[secure_settings.t::Flags](#), [get_secure_settings](#), [set_secure_settings](#)

- #define [ALARM_ON_DRIVER_OVERHEATING](#) 0x01
If this flag is set enter Alarm state on driver overheat signal.
- #define [LOW_UPWR_PROTECTION](#) 0x02
If this flag is set turn off motor when voltage is lower than LowUpwrOff.
- #define [H_BRIDGE_ALERT](#) 0x04
If this flag is set then turn off the power unit with a signal problem in one of the transistor bridge.
- #define [ALARM_ON_BORDERS_SWAP_MISSET](#) 0x08
If this flag is set enter Alarm state on borders swap misset.
- #define [ALARM_FLAGS_STICKING](#) 0x10
If this flag is set only a STOP command can turn all alarms to 0.
- #define [USB_BREAK_RECONNECT](#) 0x20
If this flag is set USB brake reconnect module will be enable.

Position setting flags

Flags used in setting of position.

See Also

[get_position](#)
[set_position](#)
[set_position.t::PosFlags](#), [set_position](#)

- #define [SETPOS_IGNORE_POSITION](#) 0x01
Will not reload position in steps/microsteps if this flag is set.
- #define [SETPOS_IGNORE_ENCODER](#) 0x02
Will not reload encoder state if this flag is set.

Feedback type.

See Also

[set_feedback_settings](#)
[get_feedback_settings](#)
[feedback_settings.t::FeedbackType](#), [get_feedback_settings](#), [set_feedback_settings](#)

- #define [FEEDBACK_ENCODER](#) 0x01
Feedback by encoder.
- #define [FEEDBACK_EMF](#) 0x04
Feedback by EMF.
- #define [FEEDBACK_NONE](#) 0x05
Feedback is absent.

Describes feedback flags.

See Also

[set_feedback_settings](#)
[get_feedback_settings](#)
[feedback_settings.t::FeedbackFlags](#), [get_feedback_settings](#), [set_feedback_settings](#)

- #define [FEEDBACK_ENC_REVERSE](#) 0x01
Reverse count of encoder.
- #define [FEEDBACK_ENC_TYPE_BITS](#) 0xC0
Bits of the encoder type.

- #define `FEEDBACK_ENC_TYPE_AUTO` 0x00
Auto detect encoder type.
- #define `FEEDBACK_ENC_TYPE_SINGLE_ENDED` 0x40
Single ended encoder.
- #define `FEEDBACK_ENC_TYPE_DIFFERENTIAL` 0x80
Differential encoder.

Flags for synchronization input setup

See Also

`sync_settings.t::syncin_flags`
`get_sync_settings`
`set_sync_settings`
[sync_in_settings.t::SyncInFlags](#), [get_sync_in_settings](#), [set_sync_in_settings](#)

- #define `SYNCIN_ENABLED` 0x01
Synchronization in mode is enabled, if this flag is set.
- #define `SYNCIN_INVERT` 0x02
Trigger on falling edge if flag is set, on rising edge otherwise.
- #define `SYNCIN_GOTOPOSITION` 0x04
The engine is go to position specified in Position and uPosition, if this flag is set.

Flags of synchronization output

See Also

`sync_settings.t::syncout_flags`
`get_sync_settings`
`set_sync_settings`
[sync_out_settings.t::SyncOutFlags](#), [get_sync_out_settings](#), [set_sync_out_settings](#)

- #define `SYNCOUT_ENABLED` 0x01
Synchronization out pin follows the synchronization logic, if set.
- #define `SYNCOUT_STATE` 0x02
When output state is fixed by negative SYNCOUT_ENABLED flag, the pin state is in accordance with this flag state.
- #define `SYNCOUT_INVERT` 0x04
Low level is active, if set, and high level is active otherwise.
- #define `SYNCOUT_IN_STEPS` 0x08
Use motor steps/encoder pulses instead of milliseconds for output pulse generation if the flag is set.
- #define `SYNCOUT_ONSTART` 0x10
Generate synchronization pulse when movement starts.
- #define `SYNCOUT_ONSTOP` 0x20
Generate synchronization pulse when movement stops.
- #define `SYNCOUT_ONPERIOD` 0x40
Generate synchronization pulse every SyncOutPeriod encoder pulses.

External IO setup flags

See Also

`extio_settings.t::setup_flags`
[get_extio_settings](#)
[set_extio_settings](#)
[extio_settings.t::EXTIOSetupFlags](#), [get_extio_settings](#), [set_extio_settings](#)

- #define `EXTIO_SETUP_OUTPUT` 0x01
EXTIO works as output if flag is set, works as input otherwise.
- #define `EXTIO_SETUP_INVERT` 0x02
Interpret EXTIO states and fronts inverted if flag is set.

External IO mode flags

See Also

[extio_settings.t::extio_mode_flags](#)
[get_extio_settings](#)
[set_extio_settings](#)
[extio_settings.t::EXTIOModeFlags](#), [get_extio_settings](#), [set_extio_settings](#)

- #define [EXTIO_SETUP_MODE_IN_BITS](#) 0x0F
Bits of the behaviour selector when the signal on input goes to the active state.
- #define [EXTIO_SETUP_MODE_IN_NOP](#) 0x00
Do nothing.
- #define [EXTIO_SETUP_MODE_IN_STOP](#) 0x01
Issue STOP command, ceasing the engine movement.
- #define [EXTIO_SETUP_MODE_IN_PWOF](#) 0x02
Issue PWOF command, powering off all engine windings.
- #define [EXTIO_SETUP_MODE_IN_MOVR](#) 0x03
Issue MOVR command with last used settings.
- #define [EXTIO_SETUP_MODE_IN_HOME](#) 0x04
Issue HOME command.
- #define [EXTIO_SETUP_MODE_IN_ALARM](#) 0x05
Set Alarm when the signal goes to the active state.
- #define [EXTIO_SETUP_MODE_OUT_BITS](#) 0xF0
Bits of the output behaviour selection.
- #define [EXTIO_SETUP_MODE_OUT_OFF](#) 0x00
EXTIO pin always set in inactive state.
- #define [EXTIO_SETUP_MODE_OUT_ON](#) 0x10
EXTIO pin always set in active state.
- #define [EXTIO_SETUP_MODE_OUT_MOVING](#) 0x20
EXTIO pin stays active during moving state.
- #define [EXTIO_SETUP_MODE_OUT_ALARM](#) 0x30
EXTIO pin stays active during Alarm state.
- #define [EXTIO_SETUP_MODE_OUT_MOTOR_ON](#) 0x40
EXTIO pin stays active when windings are powered.
- #define [EXTIO_SETUP_MODE_OUT_MOTOR_FOUND](#) 0x50
EXTIO pin stays active when motor is connected (first winding).

Border flags

Specify types of borders and motor behaviour on borders. May be combined with bitwise OR.

See Also

[get_edges_settings](#)
[set_edges_settings](#)
[edges_settings.t::BorderFlags](#), [get_edges_settings](#), [set_edges_settings](#)

- #define [BORDER_IS_ENCODER](#) 0x01
Borders are fixed by predetermined encoder values, if set; borders position on limit switches, if not set.
- #define [BORDER_STOP_LEFT](#) 0x02
Motor should stop on left border.
- #define [BORDER_STOP_RIGHT](#) 0x04
Motor should stop on right border.
- #define [BORDERS_SWAP_MISSET_DETECTION](#) 0x08
Motor should stop on both borders.

Limit switches flags

Specify electrical behaviour of limit switches like order and pulled positions. May be combined with bitwise OR.

See Also

[get_edges_settings](#)
[set_edges_settings](#)
[edges_settings.t::EnderFlags](#), [get_edges_settings](#), [set_edges_settings](#)

- #define [ENDER_SWAP](#) 0x01
First limit switch on the right side, if set; otherwise on the left side.
- #define [ENDER_SW1_ACTIVE_LOW](#) 0x02
1 - Limit switch connected to pin SW1 is triggered by a low level on pin.
- #define [ENDER_SW2_ACTIVE_LOW](#) 0x04
1 - Limit switch connected to pin SW2 is triggered by a low level on pin.

Brake settings flags

Specify behaviour of brake. May be combined with bitwise OR.

See Also

[get_brake_settings](#)
[set_brake_settings](#)
[brake_settings.t::BrakeFlags](#), [get_brake_settings](#), [set_brake_settings](#)

- #define [BRAKE_ENABLED](#) 0x01
Brake control is enabled, if this flag is set.
- #define [BRAKE_ENG_PWROFF](#) 0x02
Brake turns off power of step motor, if this flag is set.

Control flags

Specify motor control settings by joystick or buttons. May be combined with bitwise OR.

See Also

[get_control_settings](#)
[set_control_settings](#)
[control_settings.t::Flags](#), [get_control_settings](#), [set_control_settings](#)

- #define [CONTROL_MODE_BITS](#) 0x03
Bits to control engine by joystick or buttons.
- #define [CONTROL_MODE_OFF](#) 0x00
Control is disabled.
- #define [CONTROL_MODE_JOY](#) 0x01
Control by joystick.
- #define [CONTROL_MODE_LR](#) 0x02
Control by left/right buttons.
- #define [CONTROL_BTN_LEFT_PUSHED_OPEN](#) 0x04
Pushed left button corresponds to open contact, if this flag is set.
- #define [CONTROL_BTN_RIGHT_PUSHED_OPEN](#) 0x08
Pushed right button corresponds to open contact, if this flag is set.

Joystick flags

Control joystick states.

See Also

[set_joystick_settings](#)
[get_joystick_settings](#)
[joystick_settings.t::JoyFlags](#), [get_joystick_settings](#), [set_joystick_settings](#)

- #define [JOY_REVERSE](#) 0x01
Joystick action is reversed.

Position control flags

Specify settings of position control. May be combined with bitwise OR.

See Also

[get_ctp_settings](#)
[set_ctp_settings](#)
[ctp_settings.t::CTPFlags](#), [get_ctp_settings](#), [set_ctp_settings](#)

- #define [CTP_ENABLED](#) 0x01
Position control is enabled, if flag set.
- #define [CTP_BASE](#) 0x02
Position control is based on revolution sensor, if this flag is set; otherwise it is based on encoder.
- #define [CTP_ALARM_ON_ERROR](#) 0x04
Set ALARM on mismatch, if flag set.
- #define [REV_SENS_INV](#) 0x08
Sensor is active when it 0 and invert makes active level 1.
- #define [CTP_ERROR_CORRECTION](#) 0x10
Correct errors which appear when slippage if the flag is set.

Home settings flags

Specify behaviour for home command. May be combined with bitwise OR.

See Also

[get_home_settings](#)
[set_home_settings](#)
[command_home](#)
[home_settings.t::HomeFlags](#), [get_home_settings](#), [set_home_settings](#)

- #define [HOME_DIR_FIRST](#) 0x001
Flag defines direction of 1st motion after execution of home command.
- #define [HOME_DIR_SECOND](#) 0x002
Flag defines direction of 2nd motion.
- #define [HOME_MV_SEC_EN](#) 0x004
Use the second phase of calibration to the home position, if set; otherwise the second phase is skipped.
- #define [HOME_HALF_MV](#) 0x008
If the flag is set, the stop signals are ignored in start of second movement the first half-turn.
- #define [HOME_STOP_FIRST_BITS](#) 0x030
Bits of the first stop selector.
- #define [HOME_STOP_FIRST_REV](#) 0x010
First motion stops by revolution sensor.
- #define [HOME_STOP_FIRST_SYN](#) 0x020
First motion stops by synchronization input.
- #define [HOME_STOP_FIRST_LIM](#) 0x030
First motion stops by limit switch.
- #define [HOME_STOP_SECOND_BITS](#) 0x0C0
Bits of the second stop selector.
- #define [HOME_STOP_SECOND_REV](#) 0x040
Second motion stops by revolution sensor.
- #define [HOME_STOP_SECOND_SYN](#) 0x080
Second motion stops by synchronization input.
- #define [HOME_STOP_SECOND_LIM](#) 0x0C0
Second motion stops by limit switch.
- #define [HOME_USE_FAST](#) 0x100
Use the fast algorithm of calibration to the home position, if set; otherwise the traditional algorithm.

UART parity flags

See Also

[uart_settings.t::UARTSetupFlags](#), [get_uart_settings](#), [set_uart_settings](#)

- #define [UART_PARITY_BITS](#) 0x03
Bits of the parity.
- #define [UART_PARITY_BIT_EVEN](#) 0x00
Parity bit 1, if even.
- #define [UART_PARITY_BIT_ODD](#) 0x01
Parity bit 1, if odd.
- #define [UART_PARITY_BIT_SPACE](#) 0x02
Parity bit always 0.
- #define [UART_PARITY_BIT_MARK](#) 0x03
Parity bit always 1.
- #define [UART_PARITY_BIT_USE](#) 0x04
None parity.
- #define [UART_STOP_BIT](#) 0x08
If set - one stop bit, else two stop bit.

Motor Type flags

See Also

[motor_settings.t::MotorType](#), [get_motor_settings](#), [set_motor_settings](#)

- #define [MOTOR_TYPE_UNKNOWN](#) 0x00
Unknown type of engine.
- #define [MOTOR_TYPE_STEP](#) 0x01
Step engine.
- #define [MOTOR_TYPE_DC](#) 0x02
DC engine.
- #define [MOTOR_TYPE_BLDC](#) 0x03
BLDC engine.

Encoder settings flags

See Also

[encoder_settings.t::EncoderSettings](#), [get_encoder_settings](#), [set_encoder_settings](#)

- #define [ENCSET_DIFFERENTIAL_OUTPUT](#) 0x001
If flag is set the encoder has differential output, else single ended output.
- #define [ENCSET_PUSHPULL_OUTPUT](#) 0x004
If flag is set the encoder has push-pull output, else open drain output.
- #define [ENCSET_INDEXCHANNEL_PRESENT](#) 0x010
If flag is set the encoder has index channel, else encoder hasn't it.
- #define [ENCSET_REVOLUTIONSENSOR_PRESENT](#) 0x040
If flag is set the encoder has revolution sensor, else encoder hasn't it.
- #define [ENCSET_REVOLUTIONSENSOR_ACTIVE_HIGH](#) 0x100
If flag is set the revolution sensor active state is high logic state, else active state is low logic state.

Magnetic brake settings flags

See Also

[accessories_settings.t::MBSettings](#), [get_accessories_settings](#), [set_accessories_settings](#)

- #define [MB_AVAILABLE](#) 0x01
If flag is set the magnetic brake is available.
- #define [MB_POWERED_HOLD](#) 0x02
If this flag is set the magnetic brake is on when powered.

Temperature sensor settings flags

See Also

[accessories_settings_t::LimitSwitchesSettings](#), [get_accessories_settings](#), [set_accessories_settings](#)

- #define [TS_TYPE_BITS](#) 0x07
Bits of the temperature sensor type.
- #define [TS_TYPE_UNKNOWN](#) 0x00
Unknown type of sensor.
- #define [TS_TYPE_THERMOCOUPLE](#) 0x01
Thermocouple.
- #define [TS_TYPE_SEMICONDUCTOR](#) 0x02
The semiconductor temperature sensor.
- #define [TS_AVAILABLE](#) 0x08
If flag is set the temperature sensor is available.
- #define [LS_ON_SW1_AVAILABLE](#) 0x01
If flag is set the limit switch connected to pin SW1 is available.
- #define [LS_ON_SW2_AVAILABLE](#) 0x02
If flag is set the limit switch connected to pin SW2 is available.
- #define [LS_SW1_ACTIVE_LOW](#) 0x04
If flag is set the limit switch connected to pin SW1 is triggered by a low level on pin.
- #define [LS_SW2_ACTIVE_LOW](#) 0x08
If flag is set the limit switch connected to pin SW2 is triggered by a low level on pin.
- #define [LS_SHORTED](#) 0x10
If flag is set the Limit switches is shorted.

Typedefs

- typedef unsigned long long [ulong_t](#)
- typedef long long [long_t](#)
- typedef int [device_t](#)
Type describes device identifier.
- typedef int [result_t](#)
Type specifies result of any operation.
- typedef uint32_t [device_enumeration_t](#)
Type describes device enumeration structure.
- typedef struct [calibration_t](#) [calibration_t](#)
Calibration companion structure.
- typedef struct [device_network_information_t](#) [device_network_information_t](#)
Device network information structure.

Functions

Controller settings setup

Functions for adjusting engine read/write almost all controller settings.

- [result_t](#) [XIMC_API set_feedback_settings](#) ([device_t](#) id, const [feedback_settings_t](#) *feedback_settings)
Feedback settings.
- [result_t](#) [XIMC_API get_feedback_settings](#) ([device_t](#) id, [feedback_settings_t](#) *feedback_settings)
Feedback settings.
- [result_t](#) [XIMC_API set_home_settings](#) ([device_t](#) id, const [home_settings_t](#) *home_settings)
Set home settings.
- [result_t](#) [XIMC_API set_home_settings_calb](#) ([device_t](#) id, const [home_settings_calb_t](#) *home_settings_calb, const [calibration_t](#) *calibration)
- [result_t](#) [XIMC_API get_home_settings](#) ([device_t](#) id, [home_settings_t](#) *home_settings)

- Read home settings.*
- [result_t XIMC_API get_home_settings_calb](#) ([device_t](#) id, [home_settings_calb_t](#) *home_settings_calb, const [calibration_t](#) *calibration)
- [result_t XIMC_API set_move_settings](#) ([device_t](#) id, const [move_settings_t](#) *move_settings)
- Set command setup movement (speed, acceleration, threshold and etc).*
- [result_t XIMC_API set_move_settings_calb](#) ([device_t](#) id, const [move_settings_calb_t](#) *move_settings_calb, const [calibration_t](#) *calibration)
- [result_t XIMC_API get_move_settings](#) ([device_t](#) id, [move_settings_t](#) *move_settings)
- Read command setup movement (speed, acceleration, threshold and etc).*
- [result_t XIMC_API get_move_settings_calb](#) ([device_t](#) id, [move_settings_calb_t](#) *move_settings_calb, const [calibration_t](#) *calibration)
- [result_t XIMC_API set_engine_settings](#) ([device_t](#) id, const [engine_settings_t](#) *engine_settings)
- Set engine settings.*
- [result_t XIMC_API set_engine_settings_calb](#) ([device_t](#) id, const [engine_settings_calb_t](#) *engine_settings_calb, const [calibration_t](#) *calibration)
- [result_t XIMC_API get_engine_settings](#) ([device_t](#) id, [engine_settings_t](#) *engine_settings)
- Read engine settings.*
- [result_t XIMC_API get_engine_settings_calb](#) ([device_t](#) id, [engine_settings_calb_t](#) *engine_settings_calb, const [calibration_t](#) *calibration)
- [result_t XIMC_API set_entype_settings](#) ([device_t](#) id, const [entype_settings_t](#) *entype_settings)
- Set engine type and driver type.*
- [result_t XIMC_API get_entype_settings](#) ([device_t](#) id, [entype_settings_t](#) *entype_settings)
- Return engine type and driver type.*
- [result_t XIMC_API set_power_settings](#) ([device_t](#) id, const [power_settings_t](#) *power_settings)
- Set settings of step motor power control.*
- [result_t XIMC_API get_power_settings](#) ([device_t](#) id, [power_settings_t](#) *power_settings)
- Read settings of step motor power control.*
- [result_t XIMC_API set_secure_settings](#) ([device_t](#) id, const [secure_settings_t](#) *secure_settings)
- Set protection settings.*
- [result_t XIMC_API get_secure_settings](#) ([device_t](#) id, [secure_settings_t](#) *secure_settings)
- Read protection settings.*
- [result_t XIMC_API set_edges_settings](#) ([device_t](#) id, const [edges_settings_t](#) *edges_settings)
- Set border and limit switches settings.*
- [result_t XIMC_API set_edges_settings_calb](#) ([device_t](#) id, const [edges_settings_calb_t](#) *edges_settings_calb, const [calibration_t](#) *calibration)
- [result_t XIMC_API get_edges_settings](#) ([device_t](#) id, [edges_settings_t](#) *edges_settings)
- Read border and limit switches settings.*
- [result_t XIMC_API get_edges_settings_calb](#) ([device_t](#) id, [edges_settings_calb_t](#) *edges_settings_calb, const [calibration_t](#) *calibration)
- [result_t XIMC_API set_pid_settings](#) ([device_t](#) id, const [pid_settings_t](#) *pid_settings)
- Set PID settings.*
- [result_t XIMC_API get_pid_settings](#) ([device_t](#) id, [pid_settings_t](#) *pid_settings)
- Read PID settings.*
- [result_t XIMC_API set_sync_in_settings](#) ([device_t](#) id, const [sync_in_settings_t](#) *sync_in_settings)
- Set input synchronization settings.*
- [result_t XIMC_API set_sync_in_settings_calb](#) ([device_t](#) id, const [sync_in_settings_calb_t](#) *sync_in_settings_calb, const [calibration_t](#) *calibration)
- [result_t XIMC_API get_sync_in_settings](#) ([device_t](#) id, [sync_in_settings_t](#) *sync_in_settings)
- Read input synchronization settings.*
- [result_t XIMC_API get_sync_in_settings_calb](#) ([device_t](#) id, [sync_in_settings_calb_t](#) *sync_in_settings_calb, const [calibration_t](#) *calibration)
- [result_t XIMC_API set_sync_out_settings](#) ([device_t](#) id, const [sync_out_settings_t](#) *sync_out_settings)
- Set output synchronization settings.*
- [result_t XIMC_API set_sync_out_settings_calb](#) ([device_t](#) id, const [sync_out_settings_calb_t](#) *sync_out_settings_calb, const [calibration_t](#) *calibration)
- [result_t XIMC_API get_sync_out_settings](#) ([device_t](#) id, [sync_out_settings_t](#) *sync_out_settings)
- Read output synchronization settings.*
- [result_t XIMC_API get_sync_out_settings_calb](#) ([device_t](#) id, [sync_out_settings_calb_t](#) *sync_out_settings_calb, const [calibration_t](#) *calibration)
- [result_t XIMC_API set_extio_settings](#) ([device_t](#) id, const [extio_settings_t](#) *extio_settings)

- Set EXTIO settings.*
 - [result_t XIMC_API get_extio_settings](#) ([device_t](#) id, [extio_settings_t](#) *extio_settings)
 - Read EXTIO settings.*
 - [result_t XIMC_API set_brake_settings](#) ([device_t](#) id, const [brake_settings_t](#) *brake_settings)
 - Set settings of brake control.*
 - [result_t XIMC_API get_brake_settings](#) ([device_t](#) id, [brake_settings_t](#) *brake_settings)
 - Read settings of brake control.*
 - [result_t XIMC_API set_control_settings](#) ([device_t](#) id, const [control_settings_t](#) *control_settings)
 - Set settings of motor control.*
 - [result_t XIMC_API set_control_settings_calb](#) ([device_t](#) id, const [control_settings_calb_t](#) *control_settings_calb, const [calibration_t](#) *calibration)
 - [result_t XIMC_API get_control_settings](#) ([device_t](#) id, [control_settings_t](#) *control_settings)
 - Read settings of motor control.*
 - [result_t XIMC_API get_control_settings_calb](#) ([device_t](#) id, [control_settings_calb_t](#) *control_settings_calb, const [calibration_t](#) *calibration)
 - [result_t XIMC_API set_joystick_settings](#) ([device_t](#) id, const [joystick_settings_t](#) *joystick_settings)
 - Set settings of joystick.*
 - [result_t XIMC_API get_joystick_settings](#) ([device_t](#) id, [joystick_settings_t](#) *joystick_settings)
 - Read settings of joystick.*
 - [result_t XIMC_API set_ctp_settings](#) ([device_t](#) id, const [ctp_settings_t](#) *ctp_settings)
 - Set settings of control position(is only used with stepper motor).*
 - [result_t XIMC_API get_ctp_settings](#) ([device_t](#) id, [ctp_settings_t](#) *ctp_settings)
 - Read settings of control position(is only used with stepper motor).*
 - [result_t XIMC_API set_uart_settings](#) ([device_t](#) id, const [uart_settings_t](#) *uart_settings)
 - Set UART settings.*
 - [result_t XIMC_API get_uart_settings](#) ([device_t](#) id, [uart_settings_t](#) *uart_settings)
 - Read UART settings.*
 - [result_t XIMC_API set_calibration_settings](#) ([device_t](#) id, const [calibration_settings_t](#) *calibration_settings)
 - Set calibration settings.*
 - [result_t XIMC_API get_calibration_settings](#) ([device_t](#) id, [calibration_settings_t](#) *calibration_settings)
 - Read calibration settings.*
 - [result_t XIMC_API set_controller_name](#) ([device_t](#) id, const [controller_name_t](#) *controller_name)
 - Write user controller name and flags of setting from FRAM.*
 - [result_t XIMC_API get_controller_name](#) ([device_t](#) id, [controller_name_t](#) *controller_name)
 - Read user controller name and flags of setting from FRAM.*
 - [result_t XIMC_API set_nonvolatile_memory](#) ([device_t](#) id, const [nonvolatile_memory_t](#) *nonvolatile_memory)
 - Write userdata into FRAM.*
 - [result_t XIMC_API get_nonvolatile_memory](#) ([device_t](#) id, [nonvolatile_memory_t](#) *nonvolatile_memory)
 - Read userdata from FRAM.*

Group of commands movement control

- [result_t XIMC_API command_stop](#) ([device_t](#) id)
 - Immediately stop the engine, the transition to the STOP, mode key BREAK (winding short-circuited), the regime "retention" is deactivated for DC motors, keeping current in the windings for stepper motors (with Power management settings).*
- [result_t XIMC_API command_add_sync_in_action](#) ([device_t](#) id, const [command_add_sync_in_action_t](#) *the_command_add_sync_in_action)
 - This command adds one element of the FIFO commands that are executed when input clock pulse.*
- [result_t XIMC_API command_add_sync_in_action_calb](#) ([device_t](#) id, const [command_add_sync_in_action_calb_t](#) *the_command_add_sync_in_action_calb, const [calibration_t](#) *calibration)
- [result_t XIMC_API command_power_off](#) ([device_t](#) id)
 - Immediately power off motor regardless its state.*
- [result_t XIMC_API command_move](#) ([device_t](#) id, int Position, int uPosition)
 - Upon receiving the command "move" the engine starts to move with pre-set parameters (speed, acceleration, retention), to the point specified to the Position, uPosition.*
- [result_t XIMC_API command_move_calb](#) ([device_t](#) id, float Position, const [calibration_t](#) *calibration)
- [result_t XIMC_API command_movr](#) ([device_t](#) id, int DeltaPosition, int uDeltaPosition)

Upon receiving the command "movr" engine starts to move with pre-set parameters (speed, acceleration, hold), left or right (depending on the sign of DeltaPosition) by the number of pulses specified in the fields DeltaPosition, uDeltaPosition.

- [result_t XIMC_API command_movr_calb](#) ([device_t](#) id, float DeltaPosition, const [calibration_t](#) *calibration)
- [result_t XIMC_API command_home](#) ([device_t](#) id)

The positive direction is to the right.
- [result_t XIMC_API command_left](#) ([device_t](#) id)

Start continous moving to the left.
- [result_t XIMC_API command_right](#) ([device_t](#) id)

Start continous moving to the right.
- [result_t XIMC_API command_loft](#) ([device_t](#) id)

Upon receiving the command "loft" the engine is shifted from the current point to a distance GENG :: Antipaly, then move to the same point.
- [result_t XIMC_API command_sstp](#) ([device_t](#) id)

Soft stop engine.
- [result_t XIMC_API get_position](#) ([device_t](#) id, [get_position_t](#) *the_get_position)

Reads the value position in steps and micro for stepper motor and encoder steps all engines.
- [result_t XIMC_API get_position_calb](#) ([device_t](#) id, [get_position_calb_t](#) *the_get_position_calb, const [calibration_t](#) *calibration)
- [result_t XIMC_API set_position](#) ([device_t](#) id, const [set_position_t](#) *the_set_position)

Sets any position value in steps and micro for stepper motor and encoder steps of all engines.
- [result_t XIMC_API set_position_calb](#) ([device_t](#) id, const [set_position_calb_t](#) *the_set_position_calb, const [calibration_t](#) *calibration)
- [result_t XIMC_API command_zero](#) ([device_t](#) id)

Sets the current position and the position in which the traffic moves by the move command and movr zero for all cases, except for movement to the target position.

Group of commands to save and load settings

- [result_t XIMC_API command_save_settings](#) ([device_t](#) id)

Save all settings from controller's RAM to controller's flash memory, replacing previous data in controller's flash memory.
- [result_t XIMC_API command_read_settings](#) ([device_t](#) id)

Read all settings from controller's flash memory to controller's RAM, replacing previous data in controller's RAM.
- [result_t XIMC_API command_save_robust_settings](#) ([device_t](#) id)

Save important settings (calibration coefficients and etc.) from controller's RAM to controller's flash memory, replacing previous data in controller's flash memory.
- [result_t XIMC_API command_read_robust_settings](#) ([device_t](#) id)

Read important settings (calibration coefficients and etc.) from controller's flash memory to controller's RAM, replacing previous data in controller's RAM.
- [result_t XIMC_API command_eesave_settings](#) ([device_t](#) id)

Save settings from controller's RAM to stage's EEPROM memory, which spontaneity connected to stage and it isn't change without it mechanical reconstruction.
- [result_t XIMC_API command_eeread_settings](#) ([device_t](#) id)

Read settings from controller's RAM to stage's EEPROM memory, which spontaneity connected to stage and it isn't change without it mechanical reconstruction.
- [result_t XIMC_API command_start_measurements](#) ([device_t](#) id)

Start measurements and buffering of speed, following error.
- [result_t XIMC_API get_measurements](#) ([device_t](#) id, [measurements_t](#) *measurements)

A command to read the data buffer to build a speed graph and a sequence error.
- [result_t XIMC_API get_chart_data](#) ([device_t](#) id, [chart_data_t](#) *chart_data)

Return device electrical parameters, useful for charts.
- [result_t XIMC_API get_serial_number](#) ([device_t](#) id, unsigned int *SerialNumber)

Read device serial number.
- [result_t XIMC_API get_firmware_version](#) ([device_t](#) id, unsigned int *Major, unsigned int *Minor, unsigned int *Release)

Read controller's firmware version.
- [result_t XIMC_API service_command_updf](#) ([device_t](#) id)

Command puts the controller to update the firmware.

Service commands

- `result_t XIMC_API set_serial_number (device_t id, const serial_number_t *serial_number)`
Write device serial number and hardware version to controller's flash memory.
- `result_t XIMC_API get_analog_data (device_t id, analog_data_t *analog_data)`
Read analog data structure that contains raw analog data from ADC embedded on board.
- `result_t XIMC_API get_debug_read (device_t id, debug_read_t *debug_read)`
Read data from firmware for debug purpose.
- `result_t XIMC_API set_debug_write (device_t id, const debug_write_t *debug_write)`
Write data to firmware for debug purpose.

Group of commands to work with EEPROM

- `result_t XIMC_API set_stage_name (device_t id, const stage_name_t *stage_name)`
Write user stage name from EEPROM.
- `result_t XIMC_API get_stage_name (device_t id, stage_name_t *stage_name)`
Read user stage name from EEPROM.
- `result_t XIMC_API set_stage_information (device_t id, const stage_information_t *stage_information)`
Set stage information to EEPROM.
- `result_t XIMC_API get_stage_information (device_t id, stage_information_t *stage_information)`
Read stage information from EEPROM.
- `result_t XIMC_API set_stage_settings (device_t id, const stage_settings_t *stage_settings)`
Set stage settings to EEPROM.
- `result_t XIMC_API get_stage_settings (device_t id, stage_settings_t *stage_settings)`
Read stage settings from EEPROM.
- `result_t XIMC_API set_motor_information (device_t id, const motor_information_t *motor_information)`
Set motor information to EEPROM.
- `result_t XIMC_API get_motor_information (device_t id, motor_information_t *motor_information)`
Read motor information from EEPROM.
- `result_t XIMC_API set_motor_settings (device_t id, const motor_settings_t *motor_settings)`
Set motor settings to EEPROM.
- `result_t XIMC_API get_motor_settings (device_t id, motor_settings_t *motor_settings)`
Read motor settings from EEPROM.
- `result_t XIMC_API set_encoder_information (device_t id, const encoder_information_t *encoder_information)`
Set encoder information to EEPROM.
- `result_t XIMC_API get_encoder_information (device_t id, encoder_information_t *encoder_information)`
Read encoder information from EEPROM.
- `result_t XIMC_API set_encoder_settings (device_t id, const encoder_settings_t *encoder_settings)`
Set encoder settings to EEPROM.
- `result_t XIMC_API get_encoder_settings (device_t id, encoder_settings_t *encoder_settings)`
Read encoder settings from EEPROM.
- `result_t XIMC_API set_hallsensor_information (device_t id, const hallsensor_information_t *hallsensor_information)`
Set hall sensor information to EEPROM.
- `result_t XIMC_API get_hallsensor_information (device_t id, hallsensor_information_t *hallsensor_information)`
Read hall sensor information from EEPROM.
- `result_t XIMC_API set_hallsensor_settings (device_t id, const hallsensor_settings_t *hallsensor_settings)`
Set hall sensor settings to EEPROM.
- `result_t XIMC_API get_hallsensor_settings (device_t id, hallsensor_settings_t *hallsensor_settings)`
Read hall sensor settings from EEPROM.
- `result_t XIMC_API set_gear_information (device_t id, const gear_information_t *gear_information)`
Set gear information to EEPROM.
- `result_t XIMC_API get_gear_information (device_t id, gear_information_t *gear_information)`
Read gear information from EEPROM.
- `result_t XIMC_API set_gear_settings (device_t id, const gear_settings_t *gear_settings)`
Set gear settings to EEPROM.
- `result_t XIMC_API get_gear_settings (device_t id, gear_settings_t *gear_settings)`

- Read gear settings from EEPROM.*
- `result_t XIMC_API set_accessories_settings (device_t id, const accessories_settings_t *accessories_settings)`
- Set additional accessories information to EEPROM.*
- `result_t XIMC_API get_accessories_settings (device_t id, accessories_settings_t *accessories_settings)`
- Read additional accessories information from EEPROM.*
- `result_t XIMC_API get_bootloader_version (device_t id, unsigned int *Major, unsigned int *Minor, unsigned int *Release)`
- Read controller's firmware version.*
- `result_t XIMC_API get_init_random (device_t id, init_random_t *init_random)`
- Read random number from controller.*
- `result_t XIMC_API get_globally_unique_identifier (device_t id, globally_unique_identifier_t *globally_unique_identifier)`
- This value is unique to each individual die but is not a random value.*
- `result_t XIMC_API command_change_motor (device_t id, const command_change_motor_t *the_command_change_motor)`
- Change motor - command for switching output relay.*
- `result_t XIMC_API goto_firmware (device_t id, uint8_t *ret)`
- Reboot to firmware.*
- `result_t XIMC_API has_firmware (const char *uri, uint8_t *ret)`
- Check for firmware on device.*
- `result_t XIMC_API command_update_firmware (const char *uri, const uint8_t *data, uint32_t data_size)`
- Update firmware.*
- `result_t XIMC_API write_key (const char *uri, uint8_t *key)`
- Write controller key.*
- `result_t XIMC_API command_reset (device_t id)`
- Reset controller.*
- `result_t XIMC_API command_clear_fram (device_t id)`
- Clear controller FRAM.*

Boards and drivers control

Functions for searching and opening/closing devices

- `typedef char * pchar`
- Nevermind.*
- `typedef void(XIMC_CALLCONV * logging_callback_t)(int loglevel, const wchar_t *message, void *user_data)`
- Logging callback prototype.*
- `device_t XIMC_API open_device (const char *uri)`
- Open a device with OS uri uri and return identifier of the device which can be used in calls.*
- `result_t XIMC_API close_device (device_t *id)`
- Close specified device.*
- `result_t XIMC_API probe_device (const char *uri)`
- Check if a device with OS uri uri is XIMC device.*
- `result_t XIMC_API set_bindy_key (const char *keyfilepath)`
- Set network encryption layer (bindy) key.*
- `device_enumeration_t XIMC_API enumerate_devices (int enumerate_flags, const char *hints)`
- Enumerate all devices that looks like valid.*
- `result_t XIMC_API free_enumerate_devices (device_enumeration_t device_enumeration)`
- Free memory returned by enumerate_devices.*
- `int XIMC_API get_device_count (device_enumeration_t device_enumeration)`
- Get device count.*
- `pchar XIMC_API get_device_name (device_enumeration_t device_enumeration, int device_index)`
- Get device name from the device enumeration.*

- [result_t XIMC_API get_enumerate_device_serial](#) ([device_enumeration_t](#) device_enumeration, int device_index, uint32_t *serial)
Get device serial number from the device enumeration.
- [result_t XIMC_API get_enumerate_device_information](#) ([device_enumeration_t](#) device_enumeration, int device_index, [device_information_t](#) *device_information)
Get device information from the device enumeration.
- [result_t XIMC_API get_enumerate_device_controller_name](#) ([device_enumeration_t](#) device_enumeration, int device_index, [controller_name_t](#) *controller_name)
Get controller name from the device enumeration.
- [result_t XIMC_API get_enumerate_device_stage_name](#) ([device_enumeration_t](#) device_enumeration, int device_index, [stage_name_t](#) *stage_name)
Get stage name from the device enumeration.
- [result_t XIMC_API get_enumerate_device_network_information](#) ([device_enumeration_t](#) device_enumeration, int device_index, [device_network_information_t](#) *device_network_information)
Get device network information from the device enumeration.
- [result_t XIMC_API reset_locks](#) ()
Reset library locks in a case of deadlock.
- [result_t XIMC_API ximc_fix_usbser_sys](#) (const char *device_uri)
Fix for errors in Windows USB driver stack.
- void [XIMC_API msec.sleep](#) (unsigned int msec)
Sleeps for a specified amount of time.
- void [XIMC_API ximc_version](#) (char *version)
Returns a library version.
- void [XIMC_API logging_callback_stderr_wide](#) (int loglevel, const wchar_t *message, void *user_data)
Simple callback for logging to stderr in wide chars.
- void [XIMC_API logging_callback_stderr_narrow](#) (int loglevel, const wchar_t *message, void *user_data)
Simple callback for logging to stderr in narrow (single byte) chars.
- void [XIMC_API set_logging_callback](#) ([logging_callback_t](#) logging_callback, void *user_data)
Sets a logging callback.
- [result_t XIMC_API get_status](#) ([device_t](#) id, [status_t](#) *status)
Return device state.
- [result_t XIMC_API get_status_calb](#) ([device_t](#) id, [status_calb_t](#) *status, const [calibration_t](#) *calibration)
Calibrated device state.
- [result_t XIMC_API get_device_information](#) ([device_t](#) id, [device_information_t](#) *device_information)
Return device information.
- [result_t XIMC_API command_wait_for_stop](#) ([device_t](#) id, uint32_t refresh_interval_ms)
Wait for stop.
- [result_t XIMC_API command_homezero](#) ([device_t](#) id)
Make home command, wait until it is finished and make zero command.

6.1.1 Detailed Description

Header file for libximc library.

6.1.2 Macro Definition Documentation

6.1.2.1 #define ALARM_ON_DRIVER_OVERHEATING 0x01

If this flag is set enter Alarm state on driver overheat signal.

6.1.2.2 `#define BORDER_IS_ENCODER 0x01`

Borders are fixed by predetermined encoder values, if set; borders position on limit switches, if not set.

6.1.2.3 `#define BORDER_STOP_LEFT 0x02`

Motor should stop on left border.

6.1.2.4 `#define BORDER_STOP_RIGHT 0x04`

Motor should stop on right border.

6.1.2.5 `#define BORDERS_SWAP_MISSET_DETECTION 0x08`

Motor should stop on both borders.

Need to save motor then wrong border settings is set

6.1.2.6 `#define BRAKE_ENABLED 0x01`

Brake control is enabled, if this flag is set.

6.1.2.7 `#define BRAKE_ENG_PWROFF 0x02`

Brake turns off power of step motor, if this flag is set.

6.1.2.8 `#define CONTROL_BTN_LEFT_PUSHED_OPEN 0x04`

Pushed left button corresponds to open contact, if this flag is set.

6.1.2.9 `#define CONTROL_BTN_RIGHT_PUSHED_OPEN 0x08`

Pushed right button corresponds to open contact, if this flag is set.

6.1.2.10 `#define CONTROL_MODE_BITS 0x03`

Bits to control engine by joystick or buttons.

6.1.2.11 `#define CONTROL_MODE_JOY 0x01`

Control by joystick.

6.1.2.12 `#define CONTROL_MODE_LR 0x02`

Control by left/right buttons.

6.1.2.13 `#define CONTROL_MODE_OFF 0x00`

Control is disabled.

6.1.2.14 `#define CTP_ALARM_ON_ERROR 0x04`

Set ALARM on mismatch, if flag set.

6.1.2.15 `#define CTP_BASE 0x02`

Position control is based on revolution sensor, if this flag is set; otherwise it is based on encoder.

6.1.2.16 `#define CTP_ENABLED 0x01`

Position control is enabled, if flag set.

6.1.2.17 `#define CTP_ERROR_CORRECTION 0x10`

Correct errors which appear when slippage if the flag is set.

It works only with the encoder. Incompatible with flag CTP_ALARM_ON_ERROR.

6.1.2.18 `#define DRIVER_TYPE_DISCRETE_FET 0x01`

Driver with discrete FET keys.

Default option.

6.1.2.19 `#define DRIVER_TYPE_EXTERNAL 0x03`

External driver.

6.1.2.20 `#define DRIVER_TYPE_INTEGRATE 0x02`

Driver with integrated IC.

6.1.2.21 `#define EEPROM_PRECEDENCE 0x01`

If the flag is set settings from external EEPROM override controller settings.

6.1.2.22 `#define ENC_STATE_ABSENT 0x00`

Encoder is absent.

6.1.2.23 `#define ENC_STATE_MALFUNC 0x02`

Encoder is connected and malfunctioning.

6.1.2.24 `#define ENC_STATE_OK 0x04`

Encoder is connected and working properly.

6.1.2.25 `#define ENC_STATE_REVERS 0x03`

Encoder is connected and operational but counts in other direction.

6.1.2.26 `#define ENC_STATE_UNKNOWN 0x01`

Encoder state is unknown.

6.1.2.27 `#define ENDER_SW1_ACTIVE_LOW 0x02`

1 - Limit switch connected to pin SW1 is triggered by a low level on pin.

6.1.2.28 `#define ENDER_SW2_ACTIVE_LOW 0x04`

1 - Limit switch connected to pin SW2 is triggered by a low level on pin.

6.1.2.29 `#define ENDER_SWAP 0x01`

First limit switch on the right side, if set; otherwise on the left side.

6.1.2.30 `#define ENGINE_ACCEL_ON 0x10`

Acceleration enable flag.

If it set, motion begins with acceleration and ends with deceleration.

6.1.2.31 `#define ENGINE_ANTIPLAY 0x08`

Play compensation flag.

If it set, engine makes backlash (play) compensation procedure and reach the predetermined position accurately on low speed.

6.1.2.32 `#define ENGINE_CURRENT_AS_RMS 0x02`

Engine current meaning flag.

If the flag is unset, then engine current value is interpreted as maximum amplitude value. If the flag is set, then engine current value is interpreted as root mean square current value (for stepper) or as the current value calculated from the maximum heat dissipation (bldc).

6.1.2.33 `#define ENGINE_LIMIT_CURR 0x40`

Maximum motor current limit enable flag(is only used with DC motor).

6.1.2.34 `#define ENGINE_LIMIT_RPM 0x80`

Maximum motor speed limit enable flag.

6.1.2.35 `#define ENGINE_LIMIT_VOLT 0x20`

Maximum motor voltage limit enable flag(is only used with DC motor).

6.1.2.36 `#define ENGINE_MAX_SPEED 0x04`

Max speed flag.

If it is set, engine uses maximum speed achievable with the present engine settings as nominal speed.

6.1.2.37 `#define ENGINE_REVERSE 0x01`

Reverse flag.

It determines motor shaft rotation direction that corresponds to feedback counts increasing. If not set (default), motor shaft rotation direction under positive voltage corresponds to feedback counts increasing and vice versa. Change it if you see that positive directions on motor and feedback are opposite.

6.1.2.38 `#define ENGINE_TYPE_2DC 0x02`

2 DC motors.

6.1.2.39 `#define ENGINE_TYPE_BRUSHLESS 0x05`

Brushless motor.

6.1.2.40 `#define ENGINE_TYPE_DC 0x01`

DC motor.

6.1.2.41 `#define ENGINE_TYPE_NONE 0x00`

A value that shouldn't be used.

6.1.2.42 `#define ENGINE_TYPE_STEP 0x03`

Step motor.

6.1.2.43 `#define ENGINE_TYPE_TEST 0x04`

Duty cycle are fixed.

Used only manufacturer.

6.1.2.44 `#define ENUMERATE_PROBE 0x01`

Check if a device with OS name name is XIMC device.

Be carefully with this flag because it sends some data to the device.

6.1.2.45 `#define EXTIO_SETUP_INVERT 0x02`

Interpret EXTIO states and fronts inverted if flag is set.

Falling front as input event and low logic level as active state.

6.1.2.46 `#define EXTIO_SETUP_MODE_IN_ALARM 0x05`

Set Alarm when the signal goes to the active state.

6.1.2.47 `#define EXTIO_SETUP_MODE_IN_BITS 0x0F`

Bits of the behaviour selector when the signal on input goes to the active state.

6.1.2.48 `#define EXTIO_SETUP_MODE_IN_HOME 0x04`

Issue HOME command.

6.1.2.49 `#define EXTIO_SETUP_MODE_IN_MOVR 0x03`

Issue MOVR command with last used settings.

6.1.2.50 `#define EXTIO_SETUP_MODE_IN_NOP 0x00`

Do nothing.

6.1.2.51 `#define EXTIO_SETUP_MODE_IN_PWOF 0x02`

Issue PWOF command, powering off all engine windings.

6.1.2.52 `#define EXTIO_SETUP_MODE_IN_STOP 0x01`

Issue STOP command, ceasing the engine movement.

6.1.2.53 `#define EXTIO_SETUP_MODE_OUT_ALARM 0x30`

EXTIO pin stays active during Alarm state.

6.1.2.54 `#define EXTIO_SETUP_MODE_OUT_BITS 0xF0`

Bits of the output behaviour selection.

6.1.2.55 `#define EXTIO_SETUP_MODE_OUT_MOTOR_FOUND 0x50`

EXTIO pin stays active when motor is connected (first winding).

6.1.2.56 `#define EXTIO_SETUP_MODE_OUT_MOTOR_ON 0x40`

EXTIO pin stays active when windings are powered.

6.1.2.57 `#define EXTIO_SETUP_MODE_OUT_MOVING 0x20`

EXTIO pin stays active during moving state.

6.1.2.58 `#define EXTIO_SETUP_MODE_OUT_OFF 0x00`

EXTIO pin always set in inactive state.

6.1.2.59 `#define EXTIO_SETUP_MODE_OUT_ON 0x10`

EXTIO pin always set in active state.

6.1.2.60 `#define EXTIO_SETUP_OUTPUT 0x01`

EXTIO works as output if flag is set, works as input otherwise.

6.1.2.61 `#define FEEDBACK_EMF 0x04`

Feedback by EMF.

6.1.2.62 `#define FEEDBACK_ENC_REVERSE 0x01`

Reverse count of encoder.

6.1.2.63 `#define FEEDBACK_ENC_TYPE_AUTO 0x00`

Auto detect encoder type.

6.1.2.64 `#define FEEDBACK_ENC_TYPE_BITS 0xC0`

Bits of the encoder type.

6.1.2.65 `#define FEEDBACK_ENC_TYPE_DIFFERENTIAL 0x80`

Differential encoder.

6.1.2.66 `#define FEEDBACK_ENC_TYPE_SINGLE_ENDED 0x40`

Single ended encoder.

6.1.2.67 `#define FEEDBACK_ENCODER 0x01`

Feedback by encoder.

6.1.2.68 `#define FEEDBACK_NONE 0x05`

Feedback is absent.

6.1.2.69 `#define H_BRIDGE_ALERT 0x04`

If this flag is set then turn off the power unit with a signal problem in one of the transistor bridge.

6.1.2.70 `#define HOME_DIR_FIRST 0x001`

Flag defines direction of 1st motion after execution of home command.

Direction is right, if set; otherwise left.

6.1.2.71 `#define HOME_DIR_SECOND 0x002`

Flag defines direction of 2nd motion.

Direction is right, if set; otherwise left.

6.1.2.72 `#define HOME_HALF_MV 0x008`

If the flag is set, the stop signals are ignored in start of second movement the first half-turn.

6.1.2.73 `#define HOME_MV_SEC_EN 0x004`

Use the second phase of calibration to the home position, if set; otherwise the second phase is skipped.

6.1.2.74 `#define HOME_STOP_FIRST_BITS 0x030`

Bits of the first stop selector.

6.1.2.75 `#define HOME_STOP_FIRST_LIM 0x030`

First motion stops by limit switch.

6.1.2.76 `#define HOME_STOP_FIRST_REV 0x010`

First motion stops by revolution sensor.

6.1.2.77 `#define HOME_STOP_FIRST_SYN 0x020`

First motion stops by synchronization input.

6.1.2.78 `#define HOME_STOP_SECOND_BITS 0x0C0`

Bits of the second stop selector.

6.1.2.79 `#define HOME_STOP_SECOND_LIM 0x0C0`

Second motion stops by limit switch.

6.1.2.80 `#define HOME_STOP_SECOND_REV 0x040`

Second motion stops by revolution sensor.

6.1.2.81 `#define HOME_STOP_SECOND_SYN 0x080`

Second motion stops by synchronization input.

6.1.2.82 `#define HOME_USE_FAST 0x100`

Use the fast algorithm of calibration to the home position, if set; otherwise the traditional algorithm.

6.1.2.83 `#define JOY_REVERSE 0x01`

Joystick action is reversed.

Joystick deviation to the upper values correspond to negative speeds and vice versa.

6.1.2.84 `#define LOW_UPWR_PROTECTION 0x02`

If this flag is set turn off motor when voltage is lower than LowUpwrOff.

6.1.2.85 `#define MICROSTEP_MODE_FRAC_128 0x08`

1/128 step mode.

6.1.2.86 `#define MICROSTEP_MODE_FRAC_16 0x05`

1/16 step mode.

6.1.2.87 `#define MICROSTEP_MODE_FRAC_2 0x02`

1/2 step mode.

6.1.2.88 `#define MICROSTEP_MODE_FRAC_256 0x09`

1/256 step mode.

6.1.2.89 `#define MICROSTEP_MODE_FRAC_32 0x06`

1/32 step mode.

6.1.2.90 `#define MICROSTEP_MODE_FRAC_4 0x03`

1/4 step mode.

6.1.2.91 `#define MICROSTEP_MODE_FRAC_64 0x07`

1/64 step mode.

6.1.2.92 `#define MICROSTEP_MODE_FRAC_8 0x04`

1/8 step mode.

6.1.2.93 `#define MICROSTEP_MODE_FULL 0x01`

Full step mode.

6.1.2.94 `#define MOVE_STATE_ANTIPLAY 0x04`

Motor is playing compensation, if flag set.

6.1.2.95 `#define MOVE_STATE_MOVING 0x01`

This flag indicates that controller is trying to move the motor.

Don't use this flag for waiting of completion of the movement command. Use `MVCMD_RUNNING` flag from the `MvCmdSts` field instead.

6.1.2.96 `#define MOVE_STATE_TARGET_SPEED 0x02`

Target speed is reached, if flag set.

6.1.2.97 `#define MVCMD_ERROR 0x40`

Finish state (1 - move command have finished with an error, 0 - move command have finished correctly).

This flags is actual when `MVCMD_RUNNING` signals movement finish.

6.1.2.98 `#define MVCMD_HOME 0x06`

Command home.

6.1.2.99 `#define MVCMD_LEFT 0x03`

Command left.

6.1.2.100 `#define MVCMD_LOFT 0x07`

Command loft.

6.1.2.101 `#define MVCMD_MOVE 0x01`

Command move.

6.1.2.102 `#define MVCMD_MOVR 0x02`

Command movr.

6.1.2.103 `#define MVCMD_NAME_BITS 0x3F`

Move command bit mask.

6.1.2.104 `#define MVCMD_RIGHT 0x04`

Command rigt.

6.1.2.105 `#define MVCMD_RUNNING 0x80`

Move command state (0 - move command have finished, 1 - move command is being executed).

6.1.2.106 `#define MVCMD_SSTP 0x08`

Command soft stop.

6.1.2.107 `#define MVCMD_STOP 0x05`

Command stop.

6.1.2.108 `#define MVCMD_UKNWN 0x00`

Unknown command.

6.1.2.109 `#define POWER_OFF_ENABLED 0x02`

Power off enabled after PowerOffDelay, if this flag is set.

6.1.2.110 `#define POWER_REDUCT_ENABLED 0x01`

Current reduction enabled after CurrReductDelay, if this flag is set.

6.1.2.111 `#define POWER_SMOOTH_CURRENT 0x04`

Current ramp-up/down is performed smoothly during current_set_time, if this flag is set.

6.1.2.112 `#define PWR_STATE_MAX 0x05`

Motor windings are powered by maximum current driver can provide at this voltage.

6.1.2.113 `#define PWR_STATE_NORM 0x03`

Motor windings are powered by nominal current.

6.1.2.114 `#define PWR_STATE_OFF 0x01`

Motor windings are disconnected from the driver.

6.1.2.115 `#define PWR_STATE_REDUCT 0x04`

Motor windings are powered by reduced current to lower power consumption.

6.1.2.116 `#define PWR_STATE_UNKNOWN 0x00`

Unknown state, should never happen.

6.1.2.117 `#define REV_SENS_INV 0x08`

Sensor is active when it 0 and invert makes active level 1.
That is, if you do not invert, it is normal logic - 0 is the activation.

6.1.2.118 `#define SETPOS_IGNORE_ENCODER 0x02`

Will not reload encoder state if this flag is set.

6.1.2.119 `#define SETPOS_IGNORE_POSITION 0x01`

Will not reload position in steps/microsteps if this flag is set.

6.1.2.120 `#define STATE_ALARM 0x000040`

Controller is in alarm state indicating that something dangerous had happened.
Most commands are ignored in this state. To reset the flag a STOP command must be issued.

6.1.2.121 `#define STATE_BORDERS_SWAP_MISSET 0x008000`

Engine stuck at the wrong edge.

6.1.2.122 `#define STATE_BRAKE 0x0200`

State of Brake pin.

6.1.2.123 `#define STATE_BUTTON_LEFT 0x0008`

Button "left" state (1 if pressed).

6.1.2.124 `#define STATE_BUTTON_RIGHT 0x0004`

Button "right" state (1 if pressed).

6.1.2.125 `#define STATE_CONTR 0x00003F`

Flags of controller states.

6.1.2.126 `#define STATE_CONTROLLER_OVERHEAT 0x000200`

Controller overheat.

6.1.2.127 `#define STATE_CTP_ERROR 0x000080`

Control position error(is only used with stepper motor).

6.1.2.128 `#define STATE_CURRENT_MOTOR0 0x000000`

Motor 0.

6.1.2.129 `#define STATE_CURRENT_MOTOR1 0x040000`

Motor 1.

6.1.2.130 `#define STATE_CURRENT_MOTOR2 0x080000`

Motor 2.

6.1.2.131 `#define STATE_CURRENT_MOTOR3 0x0C0000`

Motor 3.

6.1.2.132 `#define STATE_CURRENT_MOTOR_BITS 0x0C0000`

Bits indicating the current operating motor on boards with multiple outputs for engine mounting.

6.1.2.133 `#define STATE_DIG_SIGNAL 0xFFFF`

Flags of digital signals.

6.1.2.134 `#define STATE_EEPROM_CONNECTED 0x000010`

EEPROM with settings is connected.

6.1.2.135 `#define STATE_ENC_A 0x2000`

State of encoder A pin.

6.1.2.136 `#define STATE_ENC_B 0x4000`

State of encoder B pin.

6.1.2.137 `#define STATE_ERRC 0x000001`

Command error encountered.

6.1.2.138 `#define STATE_ERRD 0x000002`

Data integrity error encountered.

6.1.2.139 `#define STATE_ERRV 0x000004`

Value error encountered.

6.1.2.140 `#define STATE_GPIO_LEVEL 0x0020`

State of external GPIO pin.

6.1.2.141 `#define STATE_GPIO_PINOUT 0x0010`

External GPIO works as Out, if flag set; otherwise works as In.

6.1.2.142 `#define STATE_LEFT_EDGE 0x0002`

Engine stuck at the left edge.

6.1.2.143 `#define STATE_LOW_USB_VOLTAGE 0x002000`

USB voltage is insufficient for normal operation.

6.1.2.144 `#define STATE_OVERLOAD_POWER_CURRENT 0x000800`

Power current exceeds safe limit.

6.1.2.145 `#define STATE_OVERLOAD_POWER_VOLTAGE 0x000400`

Power voltage exceeds safe limit.

6.1.2.146 `#define STATE_OVERLOAD_USB_CURRENT 0x004000`

USB current exceeds safe limit.

6.1.2.147 `#define STATE_OVERLOAD_USB_VOLTAGE 0x001000`

USB voltage exceeds safe limit.

6.1.2.148 `#define STATE_POWER_OVERHEAT 0x000100`

Power driver overheat.

6.1.2.149 `#define STATE_REV_SENSOR 0x0400`

State of Revolution sensor pin.

6.1.2.150 `#define STATE_RIGHT_EDGE 0x0001`

Engine stuck at the right edge.

6.1.2.151 `#define STATE_SECUR 0x73FFC0`

Flags of security.

6.1.2.152 `#define STATE_SYNC_INPUT 0x0800`

State of Sync input pin.

6.1.2.153 `#define STATE_SYNC_OUTPUT 0x1000`

State of Sync output pin.

6.1.2.154 `#define SYNCIN_ENABLED 0x01`

Synchronization in mode is enabled, if this flag is set.

6.1.2.155 `#define SYNCIN_GOTOPOSITION 0x04`

The engine is go to position specified in Position and uPosition, if this flag is set.

And it is shift on the Position and uPosition, if this flag is unset

6.1.2.156 `#define SYNCIN_INVERT 0x02`

Trigger on falling edge if flag is set, on rising edge otherwise.

6.1.2.157 `#define SYNCOUT_ENABLED 0x01`

Synchronization out pin follows the synchronization logic, if set.

It governed by SYNCOUT_STATE flag otherwise.

6.1.2.158 `#define SYNCOUT_IN_STEPS 0x08`

Use motor steps/encoder pulses instead of milliseconds for output pulse generation if the flag is set.

6.1.2.159 `#define SYNCOUT_INVERT 0x04`

Low level is active, if set, and high level is active otherwise.

6.1.2.160 `#define SYNCOUT_ONPERIOD 0x40`

Generate synchronization pulse every SyncOutPeriod encoder pulses.

6.1.2.161 `#define SYNCOUT_ONSTART 0x10`

Generate synchronization pulse when movement starts.

6.1.2.162 `#define SYNCOUT_ONSTOP 0x20`

Generate synchronization pulse when movement stops.

6.1.2.163 `#define SYNCOUT_STATE 0x02`

When output state is fixed by negative SYNCOUT_ENABLED flag, the pin state is in accordance with this flag state.

6.1.2.164 `#define UART_PARITY_BITS 0x03`

Bits of the parity.

6.1.2.165 `#define WIND_A_STATE_ABSENT 0x00`

Winding A is disconnected.

6.1.2.166 `#define WIND_A_STATE_MALFUNC 0x02`

Winding A is short-circuited.

6.1.2.167 `#define WIND_A_STATE_OK 0x03`

Winding A is connected and working properly.

6.1.2.168 `#define WIND_A_STATE_UNKNOWN 0x01`

Winding A state is unknown.

6.1.2.169 `#define WIND_B_STATE_ABSENT 0x00`

Winding B is disconnected.

6.1.2.170 `#define WIND_B_STATE_MALFUNC 0x20`

Winding B is short-circuited.

6.1.2.171 `#define WIND_B_STATE_OK 0x30`

Winding B is connected and working properly.

6.1.2.172 `#define WIND_B_STATE_UNKNOWN 0x10`

Winding B state is unknown.

6.1.2.173 `#define XIMC_API`

Library import macro Macros allows to automatically import function from shared library.

It automatically expands to `__declspec(dllexport)` on `msvc` when including header file

6.1.3 Typedef Documentation

6.1.3.1 `typedef void(XIMC_CALLCONV * logging_callback_t)(int loglevel, const wchar_t *message, void *user_data)`

Logging callback prototype.

Parameters

<i>loglevel</i>	a loglevel
<i>message</i>	a message

6.1.4 Function Documentation

6.1.4.1 **result_t XIMC_API** close_device (**device_t** * id)

Close specified device.

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

6.1.4.2 **result_t XIMC_API** command_add_sync_in_action (**device_t** id, const **command_add_sync_in_action_t** * the_command_add_sync_in_action)

This command adds one element of the FIFO commands that are executed when input clock pulse.

Each pulse synchronization or perform that action, which is described in SSNI, if the buffer is empty, or the oldest loaded into the buffer action to temporarily replace the speed and coordinate in SSNI. In the latter case this action is erased from the buffer. The number of remaining empty buffer elements can be found in the structure of GETS.

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

6.1.4.3 **result_t XIMC_API** command_change_motor (**device_t** id, const **command_change_motor_t** * the_command_change_motor)

Change motor - command for switching output relay.

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

6.1.4.4 **result_t XIMC_API** command_clear_fram (**device_t** id)

Clear controller FRAM.

Can be used by manufacturer only

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

6.1.4.5 **result_t XIMC_API** command_eeread_settings (**device_t** id)

Read settings from controller's RAM to stage's EEPROM memory, which spontaneity connected to stage and it isn't change without it mechanical reconstruction.

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

6.1.4.6 **result_t XIMC_API** command_eesave_settings (**device_t** id)

Save settings from controller's RAM to stage's EEPROM memory, which spontaneity connected to stage and it isn't change without it mechanical reconstruction.

Can be used by manufacturer only.

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

6.1.4.7 **result_t XIMC_API** command_home (**device_t** id)

The positive direction is to the right.

A value of zero reverses the direction of the direction of the flag, the set speed. Restriction imposed by the trailer, act the same, except that the limit switch contact does not stop. Limit the maximum speed, acceleration and deceleration function. 1) moves the motor according to the speed FastHome, uFastHome and flag HOME_DIR_FAST until limit switch, if the flag is set HOME_STOP_ENDS, until the signal from the input synchronization if the flag HOME_STOP_SYNC (as accurately as possible is important to catch the moment of operation limit switch) or until the signal is received from the speed sensor, if the flag HOME_STOP_REV_SN 2) then moves according to the speed SlowHome, uSlowHome and flag HOME_DIR_SLOW until signal from the clock input, if the flag HOME_MV_SEC. If the flag HOME_MV_SEC reset skip this paragraph. 3) then move the motor according to the speed FastHome, uFastHome and flag HOME_DIR_SLOW a distance HomeDelta, uHomeDelta. description of flags and variable see in description for commands GHOM/SHOM

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

See Also

[home_settings_t](#)
[get_home_settings](#)
[set_home_settings](#)

6.1.4.8 **result_t XIMC_API** command_homezero (**device_t** id)

Make home command, wait until it is finished and make zero command.

This is a convinient way to calibrate zero position.

Parameters

	<i>id</i>	an identifier of device
<i>out</i>	<i>ret</i>	RESULT_OK if controller has finished home & zero correctly or result of first controller query that returned anything other than RESULT_OK.

6.1.4.9 **result_t XIMC_API** command_left (**device_t** id)

Start continous moving to the left.

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

6.1.4.10 **result_t XIMC_API** command_loft (**device_t** id)

Upon receiving the command "loft" the engine is shifted from the current point to a distance GENG :: Antiplay, then move to the same point.

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

6.1.4.11 **result_t XIMC_API** command_move (**device_t** id, int Position, int uPosition)

Upon receiving the command "move" the engine starts to move with pre-set parameters (speed, acceleration, retention), to the point specified to the Position, uPosition.

For stepper motor uPosition sets the microstep, for DC motor this field is not used.

Parameters

<i>Position</i>	position to move.
<i>uPosition</i>	part of the position to move, microsteps. Range: -255..255.
<i>id</i>	an identifier of device

6.1.4.12 **result_t XIMC_API** command_movr (**device_t** id, int DeltaPosition, int uDeltaPosition)

Upon receiving the command "movr" engine starts to move with pre-set parameters (speed, acceleration, hold), left or right (depending on the sign of DeltaPosition) by the number of pulses specified in the fields DeltaPosition, uDeltaPosition.

For stepper motor uDeltaPosition sets the microstep, for DC motor this field is not used.

Parameters

<i>DeltaPosition</i>	shift from initial position.
<i>uDeltaPosition</i>	part of the offset shift, microsteps. Range: -255..255.
<i>id</i>	an identifier of device

6.1.4.13 **result_t XIMC_API** command_power_off (**device_t** id)

Immediately power off motor regardless its state.

Shouldn't be used during motion as the motor could be power on again automatically to continue movement. The command is designed for manual motor power off. When automatic power off after stop is required, use power management system.

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

See Also

[get_power_settings](#)
[set_power_settings](#)

6.1.4.14 result_t XIMC_API command_read_robust_settings (**device_t** id)

Read important settings (calibration coefficients and etc.) from controller's flash memory to controller's RAM, replacing previous data in controller's RAM.

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

6.1.4.15 result_t XIMC_API command_read_settings (**device_t** id)

Read all settings from controller's flash memory to controller's RAM, replacing previous data in controller's RAM.

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

6.1.4.16 result_t XIMC_API command_reset (**device_t** id)

Reset controller.

Can be used by manufacturer only

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

6.1.4.17 result_t XIMC_API command_right (**device_t** id)

Start continous moving to the right.

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

6.1.4.18 result_t XIMC_API command_save_robust_settings (**device_t** id)

Save important settings (calibration coefficients and etc.) from controller's RAM to controller's flash memory, replacing previous data in controller's flash memory.

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

6.1.4.19 result_t XIMC_API command_save_settings (**device_t** id)

Save all settings from controller's RAM to controller's flash memory, replacing previous data in controller's flash memory.

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

6.1.4.20 **result_t XIMC_API** command_sstp (**device_t** id)

Soft stop engine.

The motor stops with deceleration speed.

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

6.1.4.21 **result_t XIMC_API** command_start_measurements (**device_t** id)

Start measurements and buffering of speed, following error.

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

6.1.4.22 **result_t XIMC_API** command_stop (**device_t** id)

Immediately stop the engine, the transition to the STOP, mode key BREAK (winding short-circuited), the regime "retention" is deactivated for DC motors, keeping current in the windings for stepper motors (with Power management settings).

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

6.1.4.23 **result_t XIMC_API** command_update_firmware (const char * uri, const uint8_t * data, uint32_t data_size)

Update firmware.

Service command

Parameters

<i>uri</i>	a uri of device
<i>data</i>	firmware byte stream
<i>data_size</i>	size of byte stream

6.1.4.24 **result_t XIMC_API** command_wait_for_stop (**device_t** id, uint32_t refresh_interval_ms)

Wait for stop.

Parameters

	<i>id</i>	an identifier of device
	<i>refresh_interval_ms</i>	Status refresh interval. The function waits this number of milliseconds between get_status requests to the controller. Recommended value of this parameter is 10 ms. Use values of less than 3 ms only when necessary - small refresh interval values do not significantly increase response time of the function, but they create substantially more traffic in controller-computer data channel.
out	<i>ret</i>	RESULT_OK if controller has stopped and result of the first get_status command which returned anything other than RESULT_OK otherwise.

6.1.4.25 **result_t XIMC_API** command_zero (**device_t** id)

Sets the current position and the position in which the traffic moves by the move command and movr zero for all cases, except for movement to the target position.

In the latter case, set the zero current position and the target position counted so that the absolute position of the destination is the same. That is, if we were at 400 and moved to 500, then the command Zero makes the current position of 0, and the position of the destination - 100. Does not change the mode of movement that is if the motion is carried, it continues, and if the engine is in the "hold", the type of retention remains.

Parameters

<i>id</i>	an identifier of device
-----------	-------------------------

6.1.4.26 **device_enumeration_t XIMC_API** enumerate_devices (int enumerate_flags, const char * hints)

Enumerate all devices that looks like valid.

Parameters

in	<i>enumerate_flags</i>	enumerate devices flags
in	<i>hints</i>	extended information hints is a string of form "key=value\nkey2=value2". Un-recognized key-value pairs are ignored. Key list: addr - used together with ENUMERATE_NETWORK flag. Non-null value is a remote host name or a comma-separated list of host names which contain the devices to be found, absent value means broadcast discovery. adapter_addr - used together with ENUMERATE_NETWORK flag. Non-null value is a IP address of network adapter. Remote ximc device must be on the same local network as the adapter. To enumerate network devices you must call set_bindy_key first.

6.1.4.27 **result_t XIMC_API** free_enumerate_devices (**device_enumeration_t** device_enumeration)

Free memory returned by *enumerate_devices*.

Parameters

in	<i>device_enumeration</i>	opaque pointer to an enumeration device data
----	---------------------------	--

6.1.4.28 **result_t XIMC_API** get_accessories_settings (**device_t** id, **accessories_settings_t** * accessories_settings)

Read additional accessories information from EEPROM.

Parameters

	<i>id</i>	an identifier of device
out	<i>accessories_settings</i>	structure contains information about additional accessories

6.1.4.29 **result_t XIMC_API** get_analog_data (**device_t** id, **analog_data_t** * analog_data)

Read analog data structure that contains raw analog data from ADC embedded on board.

This function used for device testing and deep recalibraton by manufacturer only.

Parameters

	<i>id</i>	an identifier of device
out	<i>analog_data</i>	analog data coefficients

6.1.4.30 **result_t XIMC_API** get_bootloader_version (**device_t** id, unsigned int * Major, unsigned int * Minor, unsigned int * Release)

Read controller's firmware version.

Parameters

	<i>id</i>	an identifier of device
out	<i>Major</i>	major version
out	<i>Minor</i>	minor version
out	<i>Release</i>	release version

6.1.4.31 **result_t XIMC_API** get_brake_settings (**device_t** id, **brake_settings_t** * brake_settings)

Read settings of brake control.

Parameters

	<i>id</i>	an identifier of device
out	<i>brake_settings</i>	structure contains settings of brake control

6.1.4.32 **result_t XIMC_API** get_calibration_settings (**device_t** id, **calibration_settings_t** * calibration_settings)

Read calibration settings.

This function fill structure with calibration settings.

See Also

[calibration_settings_t](#)

Parameters

	<i>id</i>	an identifier of device
out	<i>calibration_settings</i>	calibration settings

6.1.4.33 **result_t XIMC_API** get_chart_data (**device_t** id, **chart_data_t** * chart_data)

Return device electrical parameters, useful for charts.

Useful function that fill structure with snapshot of controller voltages and currents.

See Also

[chart_data_t](#)

Parameters

	<i>id</i>	an identifier of device
out	<i>chart_data</i>	structure with snapshot of controller parameters.

6.1.4.34 **result_t XIMC_API** get_control_settings (**device_t** id, **control_settings_t** * control_settings)

Read settings of motor control.

When choosing CTL_MODE = 1 switches motor control with the joystick. In this mode, the joystick to the maximum engine tends Move at MaxSpeed [i], where i = 0 if the previous use This mode is not selected another i. Buttons switch the room rate i. When CTL_MODE = 2 is switched on motor control using the Left / right. When you click on the button motor starts to move in the appropriate direction at a speed MaxSpeed [0], at the end of time Timeout [i] motor move at a speed MaxSpeed [i+1]. at Transition from MaxSpeed [i] on MaxSpeed [i +1] to acceleration, as usual.

Parameters

	<i>id</i>	an identifier of device
out	<i>control_settings</i>	structure contains settings motor control by joystick or buttons left/right.

6.1.4.35 **result_t XIMC_API** get_controller_name (**device_t** id, **controller_name_t** * controller_name)

Read user controller name and flags of setting from FRAM.

Parameters

	<i>id</i>	an identifier of device
out	<i>controller_name</i>	structure contains previously set user controller name

6.1.4.36 **result_t XIMC_API** get_ctp_settings (**device_t** id, **ctp_settings_t** * ctp_settings)

Read settings of control position(is only used with stepper motor).

When controlling the step motor with encoder (CTP_BASE 0) it is possible to detect the loss of steps. The controller knows the number of steps per revolution (GENG :: StepsPerRev) and the encoder resolution (GFBS :: IPT). When the control (flag CTP_ENABLED), the controller stores the current position in the footsteps of SM and the current position of the encoder. Further, at each step of the position encoder is converted into steps and if the difference is greater CTPMinError, a flag STATE_CTP_ERROR. When controlling the step motor with speed sensor (CTP_BASE 1), the position is controlled by him. The active edge of input clock controller stores the current value of steps. Further, at each turn checks how many steps shifted. When a mismatch CTPMinError a flag STATE_CTP_ERROR.

Parameters

	<i>id</i>	an identifier of device
out	<i>ctp_settings</i>	structure contains settings of control position

6.1.4.37 **result_t XIMC_API** get_debug_read (**device_t** id, **debug_read_t** * debug_read)

Read data from firmware for debug purpose.

Its use depends on context, firmware version and previous history.

Parameters

	<i>id</i>	an identifier of device
out	<i>debug_read</i>	Debug data.

6.1.4.38 `int XIMC_API get_device_count (device_enumeration.t device_enumeration)`

Get device count.

Parameters

in	<i>device_enumeration</i>	opaque pointer to an enumeration device data
----	---------------------------	--

6.1.4.39 `result.t XIMC_API get_device_information (device.t id, device_information.t * device_information)`

Return device information.

All fields must point to allocated string buffers with at least 10 bytes. Works with both raw or initialized device.

Parameters

	<i>id</i>	an identifier of device
out	<i>device_information</i>	device information Device information.

See Also

[get_device_information](#)

6.1.4.40 `pchar XIMC_API get_device_name (device_enumeration.t device_enumeration, int device_index)`

Get device name from the device enumeration.

Returns *device_index* device name.

Parameters

in	<i>device_enumeration</i>	opaque pointer to an enumeration device data
in	<i>device_index</i>	device index

6.1.4.41 `result.t XIMC_API get_edges_settings (device.t id, edges_settings.t * edges_settings)`

Read border and limit switches settings.

See Also

[set_edges_settings](#)

Parameters

	<i>id</i>	an identifier of device
out	<i>edges_settings</i>	edges settings, specify types of borders, motor behaviour and electrical behaviour of limit switches

6.1.4.42 **result_t XIMC_API** get_encoder_information (**device_t** id, **encoder_information_t** * encoder_information)

Read encoder information from EEPROM.

Parameters

	<i>id</i>	an identifier of device
out	<i>encoder_information</i>	structure contains information about encoder

6.1.4.43 **result_t XIMC_API** get_encoder_settings (**device_t** id, **encoder_settings_t** * encoder_settings)

Read encoder settings from EEPROM.

Parameters

	<i>id</i>	an identifier of device
out	<i>encoder_settings</i>	structure contains encoder settings

6.1.4.44 **result_t XIMC_API** get_engine_settings (**device_t** id, **engine_settings_t** * engine_settings)

Read engine settings.

This function fill structure with set of useful motor settings stored in controller's memory. These settings specify motor shaft movement algorithm, list of limitations and rated characteristics.

See Also

[set_engine_settings](#)

Parameters

	<i>id</i>	an identifier of device
out	<i>engine_settings</i>	engine settings

6.1.4.45 **result_t XIMC_API** get_entype_settings (**device_t** id, **entype_settings_t** * entype_settings)

Return engine type and driver type.

Parameters

	<i>id</i>	an identifier of device
out	<i>EngineType</i>	engine type
out	<i>DriverType</i>	driver type

6.1.4.46 **result_t XIMC_API** get_enumerate_device_controller_name (**device_enumeration_t** device_enumeration, int device_index, **controller_name_t** * controller_name)

Get controller name from the device enumeration.

Returns *device_index* device controller name.

Parameters

in	<i>device_enumeration</i>	opaque pointer to an enumeration device data
in	<i>device_index</i>	device index
out	<i>controller_name</i>	controller name

6.1.4.47 **result_t XIMC_API** get_enumerate_device_information (**device_enumeration_t** device_enumeration, int device_index, **device_information_t** * device_information)

Get device information from the device enumeration.

Returns *device_index* device information.

Parameters

in	<i>device_enumeration</i>	opaque pointer to an enumeration device data
in	<i>device_index</i>	device index
out	<i>device_information</i>	device information data

6.1.4.48 **result_t XIMC_API** get_enumerate_device_network_information (**device_enumeration_t** device_enumeration, int device_index, **device_network_information_t** * device_network_information)

Get device network information from the device enumeration.

Returns *device_index* device network information.

Parameters

in	<i>device_enumeration</i>	opaque pointer to an enumeration device data
in	<i>device_index</i>	device index
out	<i>device_network_information</i>	device network information data

6.1.4.49 **result_t XIMC_API** get_enumerate_device_serial (**device_enumeration_t** device_enumeration, int device_index, uint32_t * serial)

Get device serial number from the device enumeration.

Returns *device_index* device serial number.

Parameters

in	<i>device_enumeration</i>	opaque pointer to an enumeration device data
in	<i>device_index</i>	device index
out	<i>serial</i>	device serial number

6.1.4.50 **result_t XIMC_API** get_enumerate_device_stage_name (**device_enumeration_t** device_enumeration, int device_index, **stage_name_t** * stage_name)

Get stage name from the device enumeration.

Returns *device_index* device stage name.

Parameters

in	<i>device_enumeration</i>	opaque pointer to an enumeration device data
in	<i>device_index</i>	device index
out	<i>stage_name</i>	stage name

6.1.4.51 **result_t XIMC_API** get_extio_settings (**device_t** id, **extio_settings_t** * extio_settings)

Read EXTIO settings.

This function reads a structure with a set of EXTIO settings from controller's memory.

See Also

[set_extio_settings](#)

Parameters

	<i>id</i>	an identifier of device
out	<i>extio_settings</i>	EXTIO settings

6.1.4.52 **result_t XIMC_API** get_feedback_settings (**device_t** id, **feedback_settings_t** * feedback_settings)

Feedback settings.

Parameters

	<i>id</i>	an identifier of device
out	<i>IPS</i>	number of encoder counts per shaft revolution. Range: 1..65535. The field is obsolete, it is recommended to write 0 to IPS and use the extended CountsPerTurn field. You may need to update the controller firmware to the latest version.
out	<i>FeedbackType</i>	type of feedback
out	<i>FeedbackFlags</i>	flags of feedback
out	<i>CountsPerTurn</i>	number of encoder counts per shaft revolution. Range: 1..4294967295. To use the CountsPerTurn field, write 0 in the IPS field, otherwise the value from the IPS field will be used.

6.1.4.53 **result_t XIMC_API** get_firmware_version (**device_t** id, unsigned int * Major, unsigned int * Minor, unsigned int * Release)

Read controller's firmware version.

Parameters

	<i>id</i>	an identifier of device
out	<i>Major</i>	major version
out	<i>Minor</i>	minor version
out	<i>Release</i>	release version

6.1.4.54 **result_t XIMC_API** get_gear_information (**device_t** id, **gear_information_t** * gear_information)

Read gear information from EEPROM.

Parameters

	<i>id</i>	an identifier of device
out	<i>gear_information</i>	structure contains information about step gearhead

6.1.4.55 **result_t XIMC_API** get_gear_settings (**device_t** id, **gear_settings_t** * gear_settings)

Read gear settings from EEPROM.

Parameters

	<i>id</i>	an identifier of device
out	<i>gear_settings</i>	structure contains step gearhead settings

6.1.4.56 **result_t XIMC_API** get_globally_unique_identifier (**device_t** id, **globally_unique_identifier_t** * globally_unique_identifier)

This value is unique to each individual die but is not a random value.

This unique device identifier can be used to initiate secure boot processes or as a serial number for USB or other end applications.

Parameters

	<i>id</i>	an identifier of device
out	<i>the</i>	result of fields 0-3 concatenated defines the unique 128-bit device identifier.

6.1.4.57 **result_t XIMC_API** get_hallsensor_information (**device_t** id, **hallsensor_information_t** * hallsensor_information)

Read hall sensor information from EEPROM.

Parameters

	<i>id</i>	an identifier of device
out	<i>hallsensor_information</i>	structure contains information about hall sensor

6.1.4.58 **result_t XIMC_API** get_hallsensor_settings (**device_t** id, **hallsensor_settings_t** * hallsensor_settings)

Read hall sensor settings from EEPROM.

Parameters

	<i>id</i>	an identifier of device
out	<i>hallsensor_settings</i>	structure contains hall sensor settings

6.1.4.59 **result_t XIMC_API** get_home_settings (**device_t** id, **home_settings_t** * home_settings)

Read home settings.

This function fill structure with settings of calibrating position.

See Also

[home_settings_t](#)

Parameters

	<i>id</i>	an identifier of device
out	<i>home_settings</i>	calibrating position settings

6.1.4.60 **result_t XIMC_API** get_init_random (**device_t** id, **init_random_t** * init_random)



Read random number from controller.

Parameters

	<i>id</i>	an identifier of device
out	<i>random</i>	sequence generated by the controller

6.1.4.61 **result_t XIMC_API** get_joystick_settings (**device_t** id, **joystick_settings_t** * joystick_settings)

Read settings of joystick.

If joystick position is outside DeadZone limits from the central position a movement with speed, defined by the joystick DeadZone edge to 100% deviation, begins. Joystick positions inside DeadZone limits correspond to zero speed (soft stop of motion) and positions beyond Low and High limits correspond MaxSpeed [i] or -MaxSpeed [i] (see command SCTL), where i = 0 by default and can be changed with left/right buttons (see command SCTL). If next speed in list is zero (both integer and microstep parts), the button press is ignored. First speed in list shouldn't be zero. The DeadZone ranges are illustrated on the following picture.  The relationship between the deviation and the rate is exponential, allowing no switching speed combine high mobility and accuracy. The following picture illustrates this:  The nonlinearity parameter is adjustable. Setting it to zero makes deviation/speed relation linear.

Parameters

	<i>id</i>	an identifier of device
out	<i>joystick_settings</i>	structure contains joystick settings

6.1.4.62 **result_t XIMC_API** get_measurements (**device_t** id, **measurements_t** * measurements)

A command to read the data buffer to build a speed graph and a sequence error.

Filling the buffer starts with the command "start_measurements". The buffer holds 25 points, the points are taken with a period of 1 ms. To create a robust system, read data every 20 ms, if the buffer is completely full, then it is recommended to repeat the readings every 5 ms until the buffer again becomes filled with 20 points.

See Also

[get_measurements_t](#)

Parameters

	<i>id</i>	an identifier of device
out	<i>get_- measurements</i>	structure with buffer and its length.

6.1.4.63 **result_t XIMC_API** get_motor_information (**device_t** id, **motor_information_t** * motor_information)

Read motor information from EEPROM.

Parameters

	<i>id</i>	an identifier of device
out	<i>motor_- information</i>	structure contains motor information

6.1.4.64 **result_t XIMC_API** get_motor_settings (**device_t** id, **motor_settings_t** * motor_settings)

Read motor settings from EEPROM.

Parameters

	<i>id</i>	an identifier of device
out	<i>motor_settings</i>	structure contains motor settings

6.1.4.65 **result_t XIMC_API** get_move_settings (**device_t** id, **move_settings_t** * move_settings)

Read command setup movement (speed, acceleration, threshold and etc).

Parameters

	<i>id</i>	an identifier of device
out	<i>move_settings</i>	structure contains move settings: speed, acceleration, deceleration etc.

6.1.4.66 **result_t XIMC_API** get_nonvolatile_memory (**device_t** id, **nonvolatile_memory_t** * nonvolatile_memory)

Read userdata from FRAM.

Parameters

	<i>id</i>	an identifier of device
out	<i>nonvolatile_- memory</i>	structure contains previously set userdata

6.1.4.67 **result_t XIMC_API** get_pid_settings (**device_t** id, **pid_settings_t** * pid_settings)

Read PID settings.

This function fill structure with set of motor PID settings stored in controller's memory. These settings specify behaviour of PID routine for positioner. These factors are slightly different for different positioners. All boards are supplied with standard set of PID setting on controller's flash memory.

See Also

[set_pid_settings](#)

Parameters

	<i>id</i>	an identifier of device
out	<i>pid_settings</i>	pid settings

6.1.4.68 **result_t XIMC_API** get_position (**device_t** id, **get_position_t** * the_get_position)

Reads the value position in steps and micro for stepper motor and encoder steps all engines.

Parameters

	<i>id</i>	an identifier of device
out	<i>position</i>	structure contains move settings: speed, acceleration, deceleration etc.

6.1.4.69 **result_t XIMC_API** get_power_settings (**device_t** id, **power_settings_t** * power_settings)

Read settings of step motor power control.

Used with stepper motor only.

Parameters

	<i>id</i>	an identifier of device
out	<i>power_settings</i>	structure contains settings of step motor power control

6.1.4.70 **result_t XIMC_API** get_secure_settings (**device_t** id, **secure_settings_t** * secure_settings)

Read protection settings.

Parameters

	<i>id</i>	an identifier of device
out	<i>secure_settings</i>	critical parameter settings to protect the hardware

See Also

`status_t::flags`

6.1.4.71 **result_t XIMC_API** get_serial_number (**device_t** id, unsigned int * SerialNumber)

Read device serial number.

Parameters

	<i>id</i>	an identifier of device
out	<i>serial</i>	serial number

6.1.4.72 **result_t XIMC_API** get_stage_information (**device_t** id, **stage_information_t** * stage_information)

Read stage information from EEPROM.

Parameters

	<i>id</i>	an identifier of device
out	<i>stage_information</i>	structure contains stage information

6.1.4.73 **result_t XIMC_API** get_stage_name (**device_t** id, **stage_name_t** * stage_name)

Read user stage name from EEPROM.

Parameters

	<i>id</i>	an identifier of device
out	<i>stage_name</i>	structure contains previously set user stage name

6.1.4.74 **result_t XIMC_API** get_stage_settings (**device_t** id, **stage_settings_t** * stage_settings)

Read stage settings from EEPROM.

Parameters

	<i>id</i>	an identifier of device
out	<i>stage_settings</i>	structure contains stage settings

6.1.4.75 **result_t XIMC_API** get_status (**device_t** id, **status_t** * status)

Return device state.

Parameters

	<i>id</i>	an identifier of device
out	<i>status</i>	structure with snapshot of controller status Device state. Useful structure that contains current controller status, including speed, position and boolean flags.

See Also

[get_status](#)

6.1.4.76 **result_t XIMC_API** get_status_calb (**device_t** id, **status_calb_t** * status, const **calibration_t** * calibration)

Calibrated device state.

Useful structure that contains current controller status, including speed, position and boolean flags.

See Also

[get_status](#)

6.1.4.77 **result_t XIMC_API** get_sync_in_settings (**device_t** id, **sync_in_settings_t** * sync_in_settings)

Read input synchronization settings.

This function fill structure with set of input synchronization settings, modes, periods and flags, that specify behaviour of input synchronization. All boards are supplied with standard set of these settings.

See Also

[set_sync_in_settings](#)

Parameters

	<i>id</i>	an identifier of device
out	<i>sync_in_settings</i>	synchronization settings

6.1.4.78 **result_t XIMC_API** get_sync_out_settings (**device_t** id, **sync_out_settings_t** * sync_out_settings)

Read output synchronization settings.

This function fill structure with set of output synchronization settings, modes, periods and flags, that specify behaviour of output synchronization. All boards are supplied with standard set of these settings.

See Also

[set_sync_out_settings](#)

Parameters

	<i>id</i>	an identifier of device
out	<i>sync_out_settings</i>	synchronization settings

6.1.4.79 **result_t XIMC_API** get_uart_settings (**device_t** id, **uart_settings_t** * uart_settings)

Read UART settings.

This function fill structure with UART settings.

See Also

[uart_settings_t](#)

Parameters

	<i>Speed</i>	UART speed
out	<i>uart_settings</i>	UART settings

6.1.4.80 **result_t XIMC_API** goto_firmware (**device_t** id, uint8_t * ret)

Reboot to firmware.

Parameters

	<i>id</i>	an identifier of device
--	-----------	-------------------------

out	ret	RESULT_OK, if reboot to firmware is possible. Reboot is done after reply to this command. RESULT_NO_FIRMWARE, if firmware is not found. RESULT_ALREADY_IN_FIRMWARE, if this command was sent when controller is already in firmware.
-----	-----	--

6.1.4.81 **result_t XIMC_API** has_firmware (const char * uri, uint8_t * ret)

Check for firmware on device.

Parameters

	uri	a uri of device
out	ret	non-zero if firmware existed

6.1.4.82 void **XIMC_API** logging_callback_stderr_narrow (int loglevel, const wchar_t * message, void * user_data)

Simple callback for logging to stderr in narrow (single byte) chars.

Parameters

loglevel	a loglevel
message	a message

6.1.4.83 void **XIMC_API** logging_callback_stderr_wide (int loglevel, const wchar_t * message, void * user_data)

Simple callback for logging to stderr in wide chars.

Parameters

loglevel	a loglevel
message	a message

6.1.4.84 void **XIMC_API** msec_sleep (unsigned int msec)

Sleeps for a specified amount of time.

Parameters

msec	time in milliseconds
------	----------------------

6.1.4.85 **device_t XIMC_API** open_device (const char * uri)

Open a device with OS uri *uri* and return identifier of the device which can be used in calls.

Parameters

in	<i>uri</i>	a device uri Device uri has form "xi-com:port" or "xi-net://host/serial" or "xi-emu:///file". In case of USB-COM port the "port" is the OS device uri. For example "xi-com:\\.\\COM3" in Windows or "xi-com:/dev/tty.s123" in Linux/Mac. In case of network device the "host" is an IPv4 address or fully qualified domain uri (FQDN), "serial" is the device serial number in hexadecimal system. For example "xi-net://192.168.0.1/00001234" or "xi-net://hostname.com/89ABCDEF". Note: to open network device you must call set_bindy_key first. In case of virtual device the "file" is the full filename with device memory state, if it doesn't exist then it is initialized with default values. For example "xi-emu:///C:/dir/file.bin" in Windows or "xi-emu:///home/user/file.bin" in Linux/Mac.
----	------------	--

6.1.4.86 **result_t XIMC_API** probe_device (const char * uri)

Check if a device with OS uri *uri* is XIMC device.

Be carefully with this call because it sends some data to the device.

Parameters

in	<i>uri</i>	- a device uri
----	------------	----------------

6.1.4.87 **result_t XIMC_API** service_command_updf (**device_t** id)

Command puts the controller to update the firmware.

After receiving this command, the firmware board sets a flag (for loader), sends echo reply and restarts the controller.

6.1.4.88 **result_t XIMC_API** set_accessories_settings (**device_t** id, const **accessories_settings_t** * accessories_settings)

Set additional accessories information to EEPROM.

Can be used by manufacturer only.

Parameters

	<i>id</i>	an identifier of device
in	<i>accessories_settings</i>	structure contains information about additional accessories

6.1.4.89 **result_t XIMC_API** set_bindy_key (const char * keyfilepath)

Set network encryption layer (bindy) key.

Parameters

in	<i>keyfilepath</i>	full path to the bindy keyfile When using network-attached devices this function must be called before enumerate_devices and open_device functions.
----	--------------------	---

6.1.4.90 **result_t XIMC_API** set_brake_settings (**device_t** id, const **brake_settings_t** * brake_settings)

Set settings of brake control.

Parameters

	<i>id</i>	an identifier of device
<i>in</i>	<i>brake_settings</i>	structure contains settings of brake control

6.1.4.91 **result_t XIMC_API** set_calibration_settings (**device_t** id, const **calibration_settings_t** * calibration_settings)

Set calibration settings.

This function send structure with calibration settings to controller's memory.

See Also

[calibration_settings_t](#)

Parameters

	<i>id</i>	an identifier of device
<i>in</i>	<i>calibration_-settings</i>	calibration settings

6.1.4.92 **result_t XIMC_API** set_control_settings (**device_t** id, const **control_settings_t** * control_settings)

Set settings of motor control.

When choosing CTL_MODE = 1 switches motor control with the joystick. In this mode, the joystick to the maximum engine tends Move at MaxSpeed [i], where i = 0 if the previous use This mode is not selected another i. Buttons switch the room rate i. When CTL_MODE = 2 is switched on motor control using the Left / right. When you click on the button motor starts to move in the appropriate direction at a speed MaxSpeed [0], at the end of time Timeout [i] motor move at a speed MaxSpeed [i+1]. at Transition from MaxSpeed [i] on MaxSpeed [i +1] to acceleration, as usual.

Parameters

	<i>id</i>	an identifier of device
<i>in</i>	<i>control_settings</i>	structure contains settings motor control by joystick or buttons left/right.

6.1.4.93 **result_t XIMC_API** set_controller_name (**device_t** id, const **controller_name_t** * controller_name)

Write user controller name and flags of setting from FRAM.

Parameters

	<i>id</i>	an identifier of device
<i>in</i>	<i>controller_name</i>	structure contains previously set user controller name

6.1.4.94 **result_t XIMC_API** set_ctp_settings (**device_t** id, const **ctp_settings_t** * ctp_settings)

Set settings of control position(is only used with stepper motor).

When controlling the step motor with encoder (CTP.BASE 0) it is possible to detect the loss of steps. The controller knows the number of steps per revolution (GENG :: StepsPerRev) and the encoder resolution (GFBS :: IPT). When the control (flag CTP.ENABLED), the controller stores the current position in the footsteps of SM and the current position of the encoder. Further, at each step of the position encoder is converted into steps and if the difference is

greater CTPMinError, a flag STATE_CTP_ERROR. When controlling the step motor with speed sensor (CTP_BASE 1), the position is controlled by him. The active edge of input clock controller stores the current value of steps. Further, at each turn checks how many steps shifted. When a mismatch CTPMinError a flag STATE_CTP_ERROR.

Parameters

	<i>id</i>	an identifier of device
<i>in</i>	<i>ctp_settings</i>	structure contains settings of control position

6.1.4.95 **result_t XIMC_API** set_debug_write (**device_t** id, const **debug_write_t** * debug_write)

Write data to firmware for debug purpose.

Parameters

	<i>id</i>	an identifier of device
<i>in</i>	<i>debug_write</i>	Debug data.

6.1.4.96 **result_t XIMC_API** set_edges_settings (**device_t** id, const **edges_settings_t** * edges_settings)

Set border and limit switches settings.

See Also

[set_edges_settings](#)

Parameters

	<i>id</i>	an identifier of device
<i>in</i>	<i>edges_settings</i>	edges settings, specify types of borders, motor behaviour and electrical behaviour of limit switches

6.1.4.97 **result_t XIMC_API** set_encoder_information (**device_t** id, const **encoder_information_t** * encoder_information)

Set encoder information to EEPROM.

Can be used by manufacturer only.

Parameters

	<i>id</i>	an identifier of device
<i>in</i>	<i>encoder_information</i>	structure contains information about encoder

6.1.4.98 **result_t XIMC_API** set_encoder_settings (**device_t** id, const **encoder_settings_t** * encoder_settings)

Set encoder settings to EEPROM.

Can be used by manufacturer only.

Parameters

	<i>id</i>	an identifier of device
in	<i>encoder_settings</i>	structure contains encoder settings

6.1.4.99 **result.t XIMC_API** set_engine_settings (**device.t** id, const **engine_settings.t** * engine_settings)

Set engine settings.

This function send structure with set of engine settings to controller's memory. These settings specify motor shaft movement algorithm, list of limitations and rated characteristics. Use it when you change motor, encoder, positioner etc. Please note that wrong engine settings lead to device malfunction, can lead to irreversible damage of board.

See Also

[get_engine_settings](#)

Parameters

	<i>id</i>	an identifier of device
in	<i>engine_settings</i>	engine settings

6.1.4.100 **result.t XIMC_API** set_entype_settings (**device.t** id, const **entype_settings.t** * entype_settings)

Set engine type and driver type.

Parameters

	<i>id</i>	an identifier of device
in	<i>EngineType</i>	engine type
in	<i>DriverType</i>	driver type

6.1.4.101 **result.t XIMC_API** set_extio_settings (**device.t** id, const **extio_settings.t** * extio_settings)

Set EXTIO settings.

This function writes a structure with a set of EXTIO settings to controller's memory. By default input event are signalled through rising front and output states are signalled by high logic state.

See Also

[get_extio_settings](#)

Parameters

	<i>id</i>	an identifier of device
in	<i>extio_settings</i>	EXTIO settings

6.1.4.102 **result.t XIMC_API** set_feedback_settings (**device.t** id, const **feedback_settings.t** * feedback_settings)

Feedback settings.

Parameters

	<i>id</i>	an identifier of device
in	<i>IPS</i>	number of encoder counts per shaft revolution. Range: 1..65535. The field is obsolete, it is recommended to write 0 to IPS and use the extended CountsPerTurn field. You may need to update the controller firmware to the latest version.
in	<i>FeedbackType</i>	type of feedback
in	<i>FeedbackFlags</i>	flags of feedback
in	<i>CountsPerTurn</i>	number of encoder counts per shaft revolution. Range: 1..4294967295. To use the CountsPerTurn field, write 0 in the IPS field, otherwise the value from the IPS field will be used.

6.1.4.103 **result.t XIMC_API** set_gear_information (**device.t** id, const **gear_information.t** * gear_information)

Set gear information to EEPROM.

Can be used by manufacturer only.

Parameters

	<i>id</i>	an identifier of device
in	<i>gear_information</i>	structure contains information about step gearhead

6.1.4.104 **result.t XIMC_API** set_gear_settings (**device.t** id, const **gear_settings.t** * gear_settings)

Set gear settings to EEPROM.

Can be used by manufacturer only.

Parameters

	<i>id</i>	an identifier of device
in	<i>gear_settings</i>	structure contains step gearhead settings

6.1.4.105 **result.t XIMC_API** set_hallsensor_information (**device.t** id, const **hallsensor_information.t** * hallsensor_information)

Set hall sensor information to EEPROM.

Can be used by manufacturer only.

Parameters

	<i>id</i>	an identifier of device
in	<i>hallsensor_information</i>	structure contains information about hall sensor

6.1.4.106 **result.t XIMC_API** set_hallsensor_settings (**device.t** id, const **hallsensor_settings.t** * hallsensor_settings)

Set hall sensor settings to EEPROM.

Can be used by manufacturer only.

Parameters

	<i>id</i>	an identifier of device
<i>in</i>	<i>hallsensor_settings</i>	structure contains hall sensor settings

6.1.4.107 **result.t XIMC_API** set_home_settings (**device.t** id, const **home_settings.t** * home_settings)

Set home settings.

This function send structure with calibrating position settings to controller's memory.

See Also

[home_settings.t](#)

Parameters

	<i>id</i>	an identifier of device
<i>in</i>	<i>home_settings</i>	calibrating position settings

6.1.4.108 **result.t XIMC_API** set_joystick_settings (**device.t** id, const **joystick_settings.t** * joystick_settings)

Set settings of joystick.

If joystick position is outside DeadZone limits from the central position a movement with speed, defined by the joystick DeadZone edge to 100% deviation, begins. Joystick positions inside DeadZone limits correspond to zero speed (soft stop of motion) and positions beyond Low and High limits correspond MaxSpeed [i] or -MaxSpeed [i] (see command SCTL), where i = 0 by default and can be changed with left/right buttons (see command SCTL). If next speed in list is zero (both integer and microstep parts), the button press is ignored. First speed in list shouldn't be zero. The DeadZone ranges are illustrated on the following picture. [!attachments/download/5563/range25p.png!](#) The relationship between the deviation and the rate is exponential, allowing no switching speed combine high mobility and accuracy. The following picture illustrates this: [!attachments/download/3092/ExpJoystick.png!](#) The nonlinearity parameter is adjustable. Setting it to zero makes deviation/speed relation linear.

Parameters

	<i>id</i>	an identifier of device
<i>in</i>	<i>joystick_settings</i>	structure contains joystick settings

6.1.4.109 **void XIMC_API** set_logging_callback (**logging_callback.t** logging_callback, void * user_data)

Sets a logging callback.

Call resets a callback to default (stderr, syslog) if NULL passed.

Parameters

<i>logging_callback</i>	a callback for log messages
-------------------------	-----------------------------

6.1.4.110 **result.t XIMC_API** set_motor_information (**device.t** id, const **motor_information.t** * motor_information)

Set motor information to EEPROM.

Can be used by manufacturer only.

Parameters

	<i>id</i>	an identifier of device
<i>in</i>	<i>motor_-information</i>	structure contains motor information

6.1.4.111 **result.t XIMC_API** set_motor_settings (**device.t** id, const **motor.settings.t** * motor_settings)

Set motor settings to EEPROM.

Can be used by manufacturer only.

Parameters

	<i>id</i>	an identifier of device
<i>in</i>	<i>motor_settings</i>	structure contains motor information

6.1.4.112 **result.t XIMC_API** set_move_settings (**device.t** id, const **move.settings.t** * move_settings)

Set command setup movement (speed, acceleration, threshold and etc).

Parameters

	<i>id</i>	an identifier of device
<i>in</i>	<i>move.settings</i>	structure contains move settings: speed, acceleration, deceleration etc.

6.1.4.113 **result.t XIMC_API** set_nonvolatile_memory (**device.t** id, const **nonvolatile.memory.t** * nonvolatile_memory)

Write userdata into FRAM.

Parameters

	<i>id</i>	an identifier of device
<i>in</i>	<i>nonvolatile_-memory</i>	structure contains previously set userdata

6.1.4.114 **result.t XIMC_API** set_pid_settings (**device.t** id, const **pid.settings.t** * pid_settings)

Set PID settings.

This function send structure with set of PID factors to controller's memory. These settings specify behaviour of PID routine for positioner. These factors are slightly different for different positioners. All boards are supplied with standard set of PID setting on controller's flash memory. Please use it for loading new PID settings when you change positioner. Please note that wrong PID settings lead to device malfunction.

See Also

[get_pid_settings](#)

Parameters

	<i>id</i>	an identifier of device
<i>in</i>	<i>pid.settings</i>	pid settings

6.1.4.115 **result.t XIMC_API** set_position (**device.t** id, const **set_position.t** * the_set_position)

Sets any position value in steps and micro for stepper motor and encoder steps of all engines.

It means, that changing main indicator of position.

Parameters

	<i>id</i>	an identifier of device
out	<i>position</i>	structure contains move settings: speed, acceleration, deceleration etc.

6.1.4.116 **result.t XIMC_API** set_power_settings (**device.t** id, const **power_settings.t** * power_settings)

Set settings of step motor power control.

Used with stepper motor only.

Parameters

	<i>id</i>	an identifier of device
in	<i>power_settings</i>	structure contains settings of step motor power control

6.1.4.117 **result.t XIMC_API** set_secure_settings (**device.t** id, const **secure_settings.t** * secure_settings)

Set protection settings.

Parameters

	<i>id</i>	an identifier of device
	<i>secure_settings</i>	structure with secure data

See Also

status.t::flags

6.1.4.118 **result.t XIMC_API** set_serial_number (**device.t** id, const **serial_number.t** * serial_number)

Write device serial number and hardware version to controller's flash memory.

Along with the new serial number and hardware version a "Key" is transmitted. The SN and hardware version are changed and saved when keys match. Can be used by manufacturer only.

Parameters

	<i>id</i>	an identifier of device
in	<i>serial</i>	number structure contains new serial number and secret key.

6.1.4.119 **result.t XIMC_API** set_stage_information (**device.t** id, const **stage_information.t** * stage_information)

Set stage information to EEPROM.

Can be used by manufacturer only.

Parameters

	<i>id</i>	an identifier of device
in	<i>stage_information</i>	structure contains stage information

6.1.4.120 **result.t XIMC_API** set_stage_name (**device.t** id, const **stage_name.t** * stage_name)

Write user stage name from EEPROM.

Parameters

	<i>id</i>	an identifier of device
in	<i>stage_name</i>	structure contains previously set user stage name

6.1.4.121 **result.t XIMC_API** set_stage_settings (**device.t** id, const **stage_settings.t** * stage_settings)

Set stage settings to EEPROM.

Can be used by manufacturer only

Parameters

	<i>id</i>	an identifier of device
in	<i>stage_settings</i>	structure contains stage settings

6.1.4.122 **result.t XIMC_API** set_sync_in_settings (**device.t** id, const **sync.in.settings.t** * sync.in.settings)

Set input synchronization settings.

This function send structure with set of input synchronization settings, that specify behaviour of input synchronization, to controller's memory. All boards are supplied with standard set of these settings.

See Also

[get_sync_in_settings](#)

Parameters

	<i>id</i>	an identifier of device
in	<i>sync.in.settings</i>	synchronization settings

6.1.4.123 **result.t XIMC_API** set_sync_out_settings (**device.t** id, const **sync.out.settings.t** * sync.out.settings)

Set output synchronization settings.

This function send structure with set of output synchronization settings, that specify behaviour of output synchronization, to controller's memory. All boards are supplied with standard set of these settings.

See Also

[get_sync_out_settings](#)

Parameters

	<i>id</i>	an identifier of device
in	<i>sync_out_settings</i>	synchronization settings

6.1.4.124 **result.t XIMC_API** set_uart_settings (**device.t** id, const **uart.settings.t** * uart_settings)

Set UART settings.

This function send structure with UART settings to controller's memory.

See Also

[uart.settings.t](#)

Parameters

	<i>Speed</i>	UART speed
in	<i>uart_settings</i>	UART settings

6.1.4.125 **result.t XIMC_API** write_key (const char * uri, uint8_t * key)

Write controller key.

Can be used by manufacturer only

Parameters

	<i>uri</i>	a uri of device
in	<i>key</i>	protection key. Range: 0..4294967295

6.1.4.126 **result.t XIMC_API** ximc_fix_usbser_sys (const char * device_uri)

Fix for errors in Windows USB driver stack.

USB subsystem on Windows does not always work correctly. The following bugs are possible: the device cannot be opened at all, or the device can be opened and written to, but it will not respond with data. These errors can be fixed by device reconnection or removal-rescan in device manager. [ximc.fix_usbser_sys\(\)](#) is a shortcut function to do the remove-rescan process. You should call this function if libximc library cannot open the device which was not physically removed from the system or if the device does not respond.

6.1.4.127 void **XIMC_API** ximc_version (char * version)

Returns a library version.

Parameters

<i>version</i>	a buffer to hold a version string, 32 bytes is enough
----------------	---

Index

- A1Voltage
 - [analog_data.t, 13](#)
- A1Voltage_ADC
 - [analog_data.t, 13](#)
- A2Voltage
 - [analog_data.t, 13](#)
- A2Voltage_ADC
 - [analog_data.t, 13](#)
- ACurrent
 - [analog_data.t, 13](#)
- ACurrent_ADC
 - [analog_data.t, 13](#)
- Accel
 - [move_settings_calb.t, 50](#)
 - [move_settings.t, 51](#)
- accessories_settings.t, [10](#)
 - [LimitSwitchesSettings, 11](#)
 - [MBRatedCurrent, 11](#)
 - [MBRatedVoltage, 11](#)
 - [MBSSettings, 11](#)
 - [MBTorque, 11](#)
 - [MagneticBrakeInfo, 11](#)
 - [TSGrad, 11](#)
 - [TSMMax, 11](#)
 - [TSMMin, 11](#)
 - [TSSettings, 11](#)
 - [TemperatureSensorInfo, 11](#)
- Accuracy
 - [sync_out_settings_calb.t, 67](#)
 - [sync_out_settings.t, 68](#)
- [analog_data.t, 12](#)
 - [A1Voltage, 13](#)
 - [A1Voltage_ADC, 13](#)
 - [A2Voltage, 13](#)
 - [A2Voltage_ADC, 13](#)
 - [ACurrent, 13](#)
 - [ACurrent_ADC, 13](#)
 - [B1Voltage, 13](#)
 - [B1Voltage_ADC, 14](#)
 - [B2Voltage, 14](#)
 - [B2Voltage_ADC, 14](#)
 - [BCurrent, 14](#)
 - [BCurrent_ADC, 14](#)
 - [FullCurrent, 14](#)
 - [FullCurrent_ADC, 14](#)
 - [Joy, 14](#)
 - [Joy_ADC, 14](#)
 - [L, 14](#)
 - [L5, 14](#)
 - [L5_ADC, 14](#)
 - [Pot, 15](#)
 - [R, 15](#)
 - [SupVoltage, 15](#)
 - [SupVoltage_ADC, 15](#)
 - [Temp, 15](#)
 - [Temp_ADC, 15](#)
- Antiplay
 - [engine_settings_calb.t, 31](#)
 - [engine_settings.t, 32](#)
- AntiplaySpeed
 - [move_settings_calb.t, 50](#)
 - [move_settings.t, 51](#)
- B1Voltage
 - [analog_data.t, 13](#)
- B1Voltage_ADC
 - [analog_data.t, 14](#)
- B2Voltage
 - [analog_data.t, 14](#)
- B2Voltage_ADC
 - [analog_data.t, 14](#)
- BCurrent
 - [analog_data.t, 14](#)
- BCurrent_ADC
 - [analog_data.t, 14](#)
- BORDER_IS_ENCODER
 - [ximc.h, 91](#)
- BORDER_STOP_LEFT
 - [ximc.h, 92](#)
- BORDER_STOP_RIGHT
 - [ximc.h, 92](#)
- BRAKE_ENABLED
 - [ximc.h, 92](#)
- BRAKE_ENG_PWROFF
 - [ximc.h, 92](#)
- BorderFlags
 - [edges_settings_calb.t, 27](#)
 - [edges_settings.t, 28](#)
- brake_settings.t, [15](#)
 - [BrakeFlags, 16](#)
 - [t1, 16](#)
 - [t2, 16](#)
 - [t3, 16](#)
 - [t4, 16](#)
- BrakeFlags
 - [brake_settings.t, 16](#)
- CONTROL_MODE_BITS
 - [ximc.h, 92](#)

CONTROL_MODE_JOY
 ximc.h, 92

CONTROL_MODE_LR
 ximc.h, 92

CONTROL_MODE_OFF
 ximc.h, 92

CSS1_A
 calibration_settings.t, 17

CSS1_B
 calibration_settings.t, 17

CSS2_A
 calibration_settings.t, 17

CSS2_B
 calibration_settings.t, 17

CTP_ALARM_ON_ERROR
 ximc.h, 92

CTP_BASE
 ximc.h, 93

CTP_ENABLED
 ximc.h, 93

CTP_ERROR_CORRECTION
 ximc.h, 93

CTPFlags
 ctp_settings.t, 24

CTPMinError
 ctp_settings.t, 24

calibration_settings.t, 16
 CSS1_A, 17
 CSS1_B, 17
 CSS2_A, 17
 CSS2_B, 17
 FullCurrent_A, 17
 FullCurrent_B, 17

calibration.t, 17

chart_data.t, 18
 DutyCycle, 18
 Joy, 18
 Pot, 19
 WindingCurrentA, 19
 WindingCurrentB, 19
 WindingCurrentC, 19
 WindingVoltageA, 19
 WindingVoltageB, 19
 WindingVoltageC, 19

close_device
 ximc.h, 107

ClutterTime
 sync_in_settings.calb.t, 65
 sync_in_settings.t, 66

CmdBufFreeSpace
 status.calb.t, 61
 status.t, 63

command_add_sync_in_action
 ximc.h, 107

command_add_sync_in_action.calb.t, 19
 Position, 20
 Time, 20

command_add_sync_in_action.t, 20
 Time, 20
 uPosition, 20

command_change_motor
 ximc.h, 107

command_change_motor.t, 20

command_clear_fram
 ximc.h, 107

command_eeread_settings
 ximc.h, 107

command_eesave_settings
 ximc.h, 107

command_home
 ximc.h, 108

command_homezero
 ximc.h, 108

command_left
 ximc.h, 108

command_loft
 ximc.h, 108

command_move
 ximc.h, 109

command_movr
 ximc.h, 109

command_power_off
 ximc.h, 109

command_read_robust_settings
 ximc.h, 109

command_read_settings
 ximc.h, 110

command_reset
 ximc.h, 110

command_right
 ximc.h, 110

command_save_robust_settings
 ximc.h, 110

command_save_settings
 ximc.h, 110

command_sstp
 ximc.h, 110

command_start_measurements
 ximc.h, 111

command_stop
 ximc.h, 111

command_update_firmware
 ximc.h, 111

command_wait_for_stop
 ximc.h, 111

command_zero
 ximc.h, 112

control_settings.calb.t, 21
 Flags, 21
 MaxClickTime, 21
 MaxSpeed, 21
 Timeout, 21

control_settings.t, 21
 Flags, 22
 MaxClickTime, 22
 MaxSpeed, 22

- Timeout, [22](#)
- uDeltaPosition, [23](#)
- uMaxSpeed, [23](#)
- controller_name_t, [23](#)
 - ControllerName, [23](#)
 - CtrlFlags, [23](#)
- ControllerName
 - controller_name_t, [23](#)
- CountsPerTurn
 - feedback_settings_t, [35](#)
- CriticalIpwr
 - secure_settings_t, [55](#)
- CriticalUsb
 - secure_settings_t, [55](#)
- CriticalT
 - secure_settings_t, [55](#)
- CriticalUpwr
 - secure_settings_t, [55](#)
- CriticalUusb
 - secure_settings_t, [55](#)
- ctp_settings_t, [23](#)
 - CTPFlags, [24](#)
 - CTPMinError, [24](#)
- CtrlFlags
 - controller_name_t, [23](#)
- CurPosition
 - status_calb_t, [61](#)
 - status_t, [63](#)
- CurSpeed
 - status_calb_t, [61](#)
 - status_t, [64](#)
- CurT
 - status_calb_t, [61](#)
 - status_t, [64](#)
- CurrReductDelay
 - power_settings_t, [53](#)
- CurrentSetTime
 - power_settings_t, [53](#)
- DRIVER_TYPE_EXTERNAL
 - ximc.h, [93](#)
- DeadZone
 - joystick_settings_t, [44](#)
- debug_read_t, [24](#)
 - DebugData, [25](#)
- debug_write_t, [25](#)
 - DebugData, [25](#)
- DebugData
 - debug_read_t, [25](#)
 - debug_write_t, [25](#)
- Decel
 - move_settings_calb_t, [50](#)
 - move_settings_t, [51](#)
- DetentTorque
 - motor_settings_t, [48](#)
- device_information_t, [25](#)
 - Major, [26](#)
 - Minor, [26](#)
 - Release, [26](#)
- device_network_information_t, [26](#)
- DriverType
 - entype_settings_t, [34](#)
- DutyCycle
 - chart_data_t, [18](#)
- EEPROM_PRECEDENCE
 - ximc.h, [93](#)
- ENC_STATE_ABSENT
 - ximc.h, [93](#)
- ENC_STATE_MALFUNC
 - ximc.h, [93](#)
- ENC_STATE_OK
 - ximc.h, [93](#)
- ENC_STATE_REVERS
 - ximc.h, [93](#)
- ENC_STATE_UNKNOWN
 - ximc.h, [93](#)
- ENDER_SW1_ACTIVE_LOW
 - ximc.h, [94](#)
- ENDER_SW2_ACTIVE_LOW
 - ximc.h, [94](#)
- ENDER_SWAP
 - ximc.h, [94](#)
- ENGINE_ACCEL_ON
 - ximc.h, [94](#)
- ENGINE_ANTIPLAY
 - ximc.h, [94](#)
- ENGINE_LIMIT_CURR
 - ximc.h, [94](#)
- ENGINE_LIMIT_RPM
 - ximc.h, [94](#)
- ENGINE_LIMIT_VOLT
 - ximc.h, [94](#)
- ENGINE_MAX_SPEED
 - ximc.h, [94](#)
- ENGINE_REVERSE
 - ximc.h, [95](#)
- ENGINE_TYPE_2DC
 - ximc.h, [95](#)
- ENGINE_TYPE_DC
 - ximc.h, [95](#)
- ENGINE_TYPE_NONE
 - ximc.h, [95](#)
- ENGINE_TYPE_STEP
 - ximc.h, [95](#)
- ENGINE_TYPE_TEST
 - ximc.h, [95](#)
- ENUMERATE_PROBE
 - ximc.h, [95](#)
- EXTIO_SETUP_INVERT
 - ximc.h, [95](#)
- EXTIO_SETUP_OUTPUT
 - ximc.h, [97](#)
- EXTIOModeFlags
 - extio_settings_t, [34](#)
- EXTIOSetupFlags
 - extio_settings_t, [34](#)
- edges_settings_calb_t, [27](#)

- BorderFlags, [27](#)
- EnderFlags, [27](#)
- LeftBorder, [27](#)
- RightBorder, [27](#)
- edges_settings_t, [27](#)
 - BorderFlags, [28](#)
 - EnderFlags, [28](#)
 - LeftBorder, [28](#)
 - RightBorder, [28](#)
 - uLeftBorder, [28](#)
 - uRightBorder, [28](#)
- Efficiency
 - gear_settings_t, [37](#)
- EncPosition
 - get_position_calb_t, [38](#)
 - get_position_t, [38](#)
 - set_position_calb_t, [56](#)
 - set_position_t, [57](#)
 - status_calb_t, [61](#)
 - status_t, [64](#)
- EncSts
 - status_calb_t, [61](#)
 - status_t, [64](#)
- encoder_information_t, [28](#)
 - Manufacturer, [29](#)
 - PartNumber, [29](#)
- encoder_settings_t, [29](#)
 - EncoderSettings, [30](#)
 - MaxCurrentConsumption, [30](#)
 - MaxOperatingFrequency, [30](#)
 - SupplyVoltageMax, [30](#)
 - SupplyVoltageMin, [30](#)
- EncoderSettings
 - encoder_settings_t, [30](#)
- EnderFlags
 - edges_settings_calb_t, [27](#)
 - edges_settings_t, [28](#)
- engine_settings_calb_t, [30](#)
 - Antiplay, [31](#)
 - EngineFlags, [31](#)
 - MicrostepMode, [31](#)
 - NomCurrent, [31](#)
 - NomSpeed, [31](#)
 - NomVoltage, [31](#)
 - StepsPerRev, [31](#)
- engine_settings_t, [31](#)
 - Antiplay, [32](#)
 - EngineFlags, [32](#)
 - MicrostepMode, [32](#)
 - NomCurrent, [32](#)
 - NomSpeed, [33](#)
 - NomVoltage, [33](#)
 - StepsPerRev, [33](#)
 - uNomSpeed, [33](#)
- EngineFlags
 - engine_settings_calb_t, [31](#)
 - engine_settings_t, [32](#)
- EngineType
 - entype_settings_t, [34](#)
 - entype_settings_t, [33](#)
 - DriverType, [34](#)
 - EngineType, [34](#)
 - enumerate_devices
 - ximc.h, [112](#)
 - Error
 - measurements_t, [45](#)
 - ExpFactor
 - joystick_settings_t, [44](#)
 - extio_settings_t, [34](#)
 - EXTIOModeFlags, [34](#)
 - EXTIOSetupFlags, [34](#)
- FEEDBACK_EMF
 - ximc.h, [97](#)
- FEEDBACK_ENC_REVERSE
 - ximc.h, [97](#)
- FEEDBACK_ENCODER
 - ximc.h, [97](#)
- FEEDBACK_NONE
 - ximc.h, [97](#)
- FastHome
 - home_settings_calb_t, [41](#)
 - home_settings_t, [42](#)
- feedback_settings_t, [34](#)
 - CountsPerTurn, [35](#)
 - FeedbackFlags, [35](#)
 - FeedbackType, [35](#)
 - IPS, [35](#)
- FeedbackFlags
 - feedback_settings_t, [35](#)
- FeedbackType
 - feedback_settings_t, [35](#)
- Flags
 - control_settings_calb_t, [21](#)
 - control_settings_t, [22](#)
 - secure_settings_t, [55](#)
 - status_calb_t, [62](#)
 - status_t, [64](#)
- free_enumerate_devices
 - ximc.h, [112](#)
- FullCurrent
 - analog_data_t, [14](#)
- FullCurrent_A
 - calibration_settings_t, [17](#)
- FullCurrent_ADC
 - analog_data_t, [14](#)
- FullCurrent_B
 - calibration_settings_t, [17](#)
- GPIOFlags
 - status_calb_t, [62](#)
 - status_t, [64](#)
- gear_information_t, [35](#)
 - Manufacturer, [36](#)
 - PartNumber, [36](#)
- gear_settings_t, [36](#)
 - Efficiency, [37](#)

- InputInertia, [37](#)
- MaxOutputBacklash, [37](#)
- RatedInputSpeed, [37](#)
- RatedInputTorque, [37](#)
- ReductionIn, [37](#)
- ReductionOut, [37](#)
- get_accessories_settings
 - ximc.h, [112](#)
- get_analog_data
 - ximc.h, [112](#)
- get_bootloader_version
 - ximc.h, [113](#)
- get_brake_settings
 - ximc.h, [113](#)
- get_calibration_settings
 - ximc.h, [113](#)
- get_chart_data
 - ximc.h, [113](#)
- get_control_settings
 - ximc.h, [114](#)
- get_controller_name
 - ximc.h, [114](#)
- get_ctp_settings
 - ximc.h, [114](#)
- get_debug_read
 - ximc.h, [114](#)
- get_device_count
 - ximc.h, [115](#)
- get_device_information
 - ximc.h, [115](#)
- get_device_name
 - ximc.h, [115](#)
- get_edges_settings
 - ximc.h, [115](#)
- get_encoder_information
 - ximc.h, [116](#)
- get_encoder_settings
 - ximc.h, [116](#)
- get_engine_settings
 - ximc.h, [116](#)
- get_entype_settings
 - ximc.h, [116](#)
- get_enumerate_device_controller_name
 - ximc.h, [116](#)
- get_enumerate_device_information
 - ximc.h, [117](#)
- get_enumerate_device_network_information
 - ximc.h, [117](#)
- get_enumerate_device_serial
 - ximc.h, [117](#)
- get_enumerate_device_stage_name
 - ximc.h, [117](#)
- get_extio_settings
 - ximc.h, [118](#)
- get_feedback_settings
 - ximc.h, [118](#)
- get_firmware_version
 - ximc.h, [118](#)
- get_gear_information
 - ximc.h, [118](#)
- get_gear_settings
 - ximc.h, [119](#)
- get_globally_unique_identifier
 - ximc.h, [119](#)
- get_hallsensor_information
 - ximc.h, [119](#)
- get_hallsensor_settings
 - ximc.h, [119](#)
- get_home_settings
 - ximc.h, [119](#)
- get_init_random
 - ximc.h, [120](#)
- get_joystick_settings
 - ximc.h, [120](#)
- get_measurements
 - ximc.h, [120](#)
- get_motor_information
 - ximc.h, [121](#)
- get_motor_settings
 - ximc.h, [121](#)
- get_move_settings
 - ximc.h, [121](#)
- get_nonvolatile_memory
 - ximc.h, [121](#)
- get_pid_settings
 - ximc.h, [121](#)
- get_position
 - ximc.h, [122](#)
- get_position_calb_t, [38](#)
 - EncPosition, [38](#)
 - Position, [38](#)
- get_position_t, [38](#)
 - EncPosition, [38](#)
- get_power_settings
 - ximc.h, [122](#)
- get_secure_settings
 - ximc.h, [122](#)
- get_serial_number
 - ximc.h, [122](#)
- get_stage_information
 - ximc.h, [122](#)
- get_stage_name
 - ximc.h, [123](#)
- get_stage_settings
 - ximc.h, [123](#)
- get_status
 - ximc.h, [123](#)
- get_status_calb
 - ximc.h, [123](#)
- get_sync_in_settings
 - ximc.h, [123](#)
- get_sync_out_settings
 - ximc.h, [124](#)
- get_uart_settings
 - ximc.h, [124](#)
- globally_unique_identifier_t, [38](#)

- UniqueID0, [39](#)
- UniqueID1, [39](#)
- UniqueID2, [39](#)
- UniqueID3, [39](#)
- goto_firmware
 - ximc.h, [124](#)
- H_BRIDGE_ALERT
 - ximc.h, [97](#)
- HOME_DIR_FIRST
 - ximc.h, [97](#)
- HOME_DIR_SECOND
 - ximc.h, [98](#)
- HOME_HALF_MV
 - ximc.h, [98](#)
- HOME_MV_SEC_EN
 - ximc.h, [98](#)
- HOME_STOP_FIRST_LIM
 - ximc.h, [98](#)
- HOME_STOP_FIRST_REV
 - ximc.h, [98](#)
- HOME_STOP_FIRST_SYN
 - ximc.h, [98](#)
- HOME_USE_FAST
 - ximc.h, [98](#)
- hallsensor_information_t, [39](#)
 - Manufacturer, [40](#)
 - PartNumber, [40](#)
- hallsensor_settings_t, [40](#)
 - MaxCurrentConsumption, [41](#)
 - MaxOperatingFrequency, [41](#)
 - SupplyVoltageMax, [41](#)
 - SupplyVoltageMin, [41](#)
- has_firmware
 - ximc.h, [125](#)
- HoldCurrent
 - power_settings_t, [54](#)
- home_settings_calb_t, [41](#)
 - FastHome, [41](#)
 - HomeDelta, [41](#)
 - HomeFlags, [41](#)
 - SlowHome, [41](#)
- home_settings_t, [42](#)
 - FastHome, [42](#)
 - HomeDelta, [42](#)
 - HomeFlags, [42](#)
 - SlowHome, [42](#)
 - uFastHome, [43](#)
 - uHomeDelta, [43](#)
 - uSlowHome, [43](#)
- HomeDelta
 - home_settings_calb_t, [41](#)
 - home_settings_t, [42](#)
- HomeFlags
 - home_settings_calb_t, [41](#)
 - home_settings_t, [42](#)
- HorizontalLoadCapacity
 - stage_settings_t, [59](#)
- IPS
 - feedback_settings_t, [35](#)
- init_random_t, [43](#)
 - key, [43](#)
- InputInertia
 - gear_settings_t, [37](#)
- lpwr
 - status_calb_t, [62](#)
 - status_t, [64](#)
- lusb
 - status_calb_t, [62](#)
 - status_t, [64](#)
- JOY_REVERSE
 - ximc.h, [99](#)
- Joy
 - analog_data_t, [14](#)
 - chart_data_t, [18](#)
- Joy_ADC
 - analog_data_t, [14](#)
- JoyCenter
 - joystick_settings_t, [44](#)
- JoyFlags
 - joystick_settings_t, [44](#)
- JoyHighEnd
 - joystick_settings_t, [44](#)
- JoyLowEnd
 - joystick_settings_t, [45](#)
- joystick_settings_t, [43](#)
 - DeadZone, [44](#)
 - ExpFactor, [44](#)
 - JoyCenter, [44](#)
 - JoyFlags, [44](#)
 - JoyHighEnd, [44](#)
 - JoyLowEnd, [45](#)
- Key
 - serial_number_t, [56](#)
- key
 - init_random_t, [43](#)
- L
 - analog_data_t, [14](#)
- L5
 - analog_data_t, [14](#)
- L5_ADC
 - analog_data_t, [14](#)
- LOW_UPWR_PROTECTION
 - ximc.h, [99](#)
- LeadScrewPitch
 - stage_settings_t, [59](#)
- LeftBorder
 - edges_settings_calb_t, [27](#)
 - edges_settings_t, [28](#)
- Length
 - measurements_t, [45](#)
- LimitSwitchesSettings
 - accessories_settings_t, [11](#)
- logging_callback_stderr_narrow

- ximc.h, [125](#)
- logging_callback_stderr_wide
 - ximc.h, [125](#)
- logging_callback_t
 - ximc.h, [106](#)
- LowUpwrOff
 - secure_settings_t, [55](#)
- MBRatedCurrent
 - accessories_settings_t, [11](#)
- MBRatedVoltage
 - accessories_settings_t, [11](#)
- MBSettings
 - accessories_settings_t, [11](#)
- MBTorque
 - accessories_settings_t, [11](#)
- MICROSTEP_MODE_FULL
 - ximc.h, [99](#)
- MOVE_STATE_ANTIPLAY
 - ximc.h, [99](#)
- MOVE_STATE_MOVING
 - ximc.h, [100](#)
- MVCMD_ERROR
 - ximc.h, [100](#)
- MVCMD_HOME
 - ximc.h, [100](#)
- MVCMD_LEFT
 - ximc.h, [100](#)
- MVCMD_LOFT
 - ximc.h, [100](#)
- MVCMD_MOVE
 - ximc.h, [100](#)
- MVCMD_MOVR
 - ximc.h, [100](#)
- MVCMD_NAME_BITS
 - ximc.h, [100](#)
- MVCMD_RIGHT
 - ximc.h, [100](#)
- MVCMD_RUNNING
 - ximc.h, [100](#)
- MVCMD_SSTP
 - ximc.h, [101](#)
- MVCMD_STOP
 - ximc.h, [101](#)
- MVCMD_UKNWN
 - ximc.h, [101](#)
- MagneticBrakeInfo
 - accessories_settings_t, [11](#)
- Major
 - device_information_t, [26](#)
 - serial_number_t, [56](#)
- Manufacturer
 - encoder_information_t, [29](#)
 - gear_information_t, [36](#)
 - hallsensor_information_t, [40](#)
 - motor_information_t, [46](#)
 - stage_information_t, [58](#)
- MaxClickTime
 - control_settings_calb_t, [21](#)
- control_settings_t, [22](#)
- MaxCurrent
 - motor_settings_t, [48](#)
- MaxCurrentConsumption
 - encoder_settings_t, [30](#)
 - hallsensor_settings_t, [41](#)
 - stage_settings_t, [60](#)
- MaxCurrentTime
 - motor_settings_t, [48](#)
- MaxOperatingFrequency
 - encoder_settings_t, [30](#)
 - hallsensor_settings_t, [41](#)
- MaxOutputBacklash
 - gear_settings_t, [37](#)
- MaxSpeed
 - control_settings_calb_t, [21](#)
 - control_settings_t, [22](#)
 - motor_settings_t, [48](#)
 - stage_settings_t, [60](#)
- measurements_t, [45](#)
 - Error, [45](#)
 - Length, [45](#)
 - Speed, [45](#)
- MechanicalTimeConstant
 - motor_settings_t, [48](#)
- MicrostepMode
 - engine_settings_calb_t, [31](#)
 - engine_settings_t, [32](#)
- MinimumUusb
 - secure_settings_t, [55](#)
- Minor
 - device_information_t, [26](#)
 - serial_number_t, [56](#)
- motor_information_t, [46](#)
 - Manufacturer, [46](#)
 - PartNumber, [46](#)
- motor_settings_t, [46](#)
 - DetentTorque, [48](#)
 - MaxCurrent, [48](#)
 - MaxCurrentTime, [48](#)
 - MaxSpeed, [48](#)
 - MechanicalTimeConstant, [48](#)
 - MotorType, [48](#)
 - NoLoadCurrent, [48](#)
 - NoLoadSpeed, [48](#)
 - NominalCurrent, [48](#)
 - NominalPower, [48](#)
 - NominalSpeed, [49](#)
 - NominalTorque, [49](#)
 - NominalVoltage, [49](#)
 - Phases, [49](#)
 - Poles, [49](#)
 - RotorInertia, [49](#)
 - SpeedConstant, [49](#)
 - SpeedTorqueGradient, [49](#)
 - StallTorque, [49](#)
 - TorqueConstant, [49](#)
 - WindingInductance, [50](#)

- WindingResistance, [50](#)
- MotorType
 - motor_settings.t, [48](#)
- move_settings_calb.t, [50](#)
 - Accel, [50](#)
 - AntiplaySpeed, [50](#)
 - Decel, [50](#)
 - Speed, [50](#)
- move_settings.t, [51](#)
 - Accel, [51](#)
 - AntiplaySpeed, [51](#)
 - Decel, [51](#)
 - Speed, [51](#)
 - uAntiplaySpeed, [51](#)
 - uSpeed, [52](#)
- MoveSts
 - status_calb.t, [62](#)
 - status.t, [64](#)
- msec_sleep
 - ximc.h, [125](#)
- MvCmdSts
 - status_calb.t, [62](#)
 - status.t, [64](#)
- NoLoadCurrent
 - motor_settings.t, [48](#)
- NoLoadSpeed
 - motor_settings.t, [48](#)
- NomCurrent
 - engine_settings_calb.t, [31](#)
 - engine_settings.t, [32](#)
- NomSpeed
 - engine_settings_calb.t, [31](#)
 - engine_settings.t, [33](#)
- NomVoltage
 - engine_settings_calb.t, [31](#)
 - engine_settings.t, [33](#)
- NominalCurrent
 - motor_settings.t, [48](#)
- NominalPower
 - motor_settings.t, [48](#)
- NominalSpeed
 - motor_settings.t, [49](#)
- NominalTorque
 - motor_settings.t, [49](#)
- NominalVoltage
 - motor_settings.t, [49](#)
- nonvolatile_memory.t, [52](#)
 - UserData, [52](#)
- open_device
 - ximc.h, [125](#)
- POWER_OFF_ENABLED
 - ximc.h, [101](#)
- POWER_REDUCT_ENABLED
 - ximc.h, [101](#)
- POWER_SMOOTH_CURRENT
 - ximc.h, [101](#)
- PWR_STATE_MAX
 - ximc.h, [101](#)
- PWR_STATE_NORM
 - ximc.h, [101](#)
- PWR_STATE_OFF
 - ximc.h, [101](#)
- PWR_STATE_REDUCT
 - ximc.h, [101](#)
- PWR_STATE_UNKNOWN
 - ximc.h, [101](#)
- PWRSts
 - status_calb.t, [62](#)
 - status.t, [64](#)
- PartNumber
 - encoder_information.t, [29](#)
 - gear_information.t, [36](#)
 - hallsensor_information.t, [40](#)
 - motor_information.t, [46](#)
 - stage_information.t, [58](#)
- Phases
 - motor_settings.t, [49](#)
- pid_settings.t, [52](#)
- Poles
 - motor_settings.t, [49](#)
- PosFlags
 - set_position_calb.t, [56](#)
 - set_position.t, [57](#)
- Position
 - command_add_sync_in_action_calb.t, [20](#)
 - get_position_calb.t, [38](#)
 - set_position_calb.t, [57](#)
 - sync_in_settings_calb.t, [65](#)
- PositionerName
 - stage_name.t, [59](#)
- Pot
 - analog_data.t, [15](#)
 - chart_data.t, [19](#)
- power_settings.t, [53](#)
 - CurrReductDelay, [53](#)
 - CurrentSetTime, [53](#)
 - HoldCurrent, [54](#)
 - PowerFlags, [54](#)
 - PowerOffDelay, [54](#)
- PowerFlags
 - power_settings.t, [54](#)
- PowerOffDelay
 - power_settings.t, [54](#)
- probe_device
 - ximc.h, [126](#)
- R
 - analog_data.t, [15](#)
- REV_SENS_INV
 - ximc.h, [101](#)
- RatedInputSpeed
 - gear_settings.t, [37](#)
- RatedInputTorque
 - gear_settings.t, [37](#)
- ReductionIn

- gear_settings.t, [37](#)
- ReductionOut
 - gear_settings.t, [37](#)
- Release
 - device_information.t, [26](#)
 - serial_number.t, [56](#)
- RightBorder
 - edges_settings_calb.t, [27](#)
 - edges_settings.t, [28](#)
- RotorInertia
 - motor_settings.t, [49](#)
- SN
 - serial_number.t, [56](#)
- STATE_ALARM
 - ximc.h, [102](#)
- STATE_BRAKE
 - ximc.h, [102](#)
- STATE_BUTTON_LEFT
 - ximc.h, [102](#)
- STATE_BUTTON_RIGHT
 - ximc.h, [102](#)
- STATE_CONTR
 - ximc.h, [102](#)
- STATE_CTP_ERROR
 - ximc.h, [102](#)
- STATE_CURRENT_MOTOR0
 - ximc.h, [102](#)
- STATE_CURRENT_MOTOR1
 - ximc.h, [102](#)
- STATE_CURRENT_MOTOR2
 - ximc.h, [103](#)
- STATE_CURRENT_MOTOR3
 - ximc.h, [103](#)
- STATE_DIG_SIGNAL
 - ximc.h, [103](#)
- STATE_ENC_A
 - ximc.h, [103](#)
- STATE_ENC_B
 - ximc.h, [103](#)
- STATE_ERRC
 - ximc.h, [103](#)
- STATE_ERRD
 - ximc.h, [103](#)
- STATE_ERRV
 - ximc.h, [103](#)
- STATE_GPIO_LEVEL
 - ximc.h, [103](#)
- STATE_GPIO_PINOUT
 - ximc.h, [103](#)
- STATE_LEFT_EDGE
 - ximc.h, [104](#)
- STATE_POWER_OVERHEAT
 - ximc.h, [104](#)
- STATE_REV_SENSOR
 - ximc.h, [104](#)
- STATE_RIGHT_EDGE
 - ximc.h, [104](#)
- STATE_SECUR
 - ximc.h, [104](#)
- STATE_SYNC_INPUT
 - ximc.h, [104](#)
- STATE_SYNC_OUTPUT
 - ximc.h, [104](#)
- SYNCIN_ENABLED
 - ximc.h, [105](#)
- SYNCIN_GOTOPOSITION
 - ximc.h, [105](#)
- SYNCIN_INVERT
 - ximc.h, [105](#)
- SYNCOUT_ENABLED
 - ximc.h, [105](#)
- SYNCOUT_IN_STEPS
 - ximc.h, [105](#)
- SYNCOUT_INVERT
 - ximc.h, [105](#)
- SYNCOUT_ONPERIOD
 - ximc.h, [105](#)
- SYNCOUT_ONSTART
 - ximc.h, [105](#)
- SYNCOUT_ONSTOP
 - ximc.h, [105](#)
- SYNCOUT_STATE
 - ximc.h, [105](#)
- secure_settings.t, [54](#)
 - CriticalIpwr, [55](#)
 - Criticalusb, [55](#)
 - CriticalT, [55](#)
 - CriticalUpwr, [55](#)
 - CriticalUusb, [55](#)
 - Flags, [55](#)
 - LowUpwrOff, [55](#)
 - MinimumUusb, [55](#)
- serial_number.t, [55](#)
 - Key, [56](#)
 - Major, [56](#)
 - Minor, [56](#)
 - Release, [56](#)
 - SN, [56](#)
- service_command_updf
 - ximc.h, [126](#)
- set_accessories_settings
 - ximc.h, [126](#)
- set_bindy_key
 - ximc.h, [126](#)
- set_brake_settings
 - ximc.h, [126](#)
- set_calibration_settings
 - ximc.h, [127](#)
- set_control_settings
 - ximc.h, [127](#)
- set_controller_name
 - ximc.h, [127](#)
- set_ctp_settings
 - ximc.h, [127](#)
- set_debug_write
 - ximc.h, [128](#)

- set_edges_settings
 - ximc.h, [128](#)
- set_encoder_information
 - ximc.h, [128](#)
- set_encoder_settings
 - ximc.h, [128](#)
- set_engine_settings
 - ximc.h, [129](#)
- set_entype_settings
 - ximc.h, [129](#)
- set_extio_settings
 - ximc.h, [129](#)
- set_feedback_settings
 - ximc.h, [129](#)
- set_gear_information
 - ximc.h, [130](#)
- set_gear_settings
 - ximc.h, [130](#)
- set_hallsensor_information
 - ximc.h, [130](#)
- set_hallsensor_settings
 - ximc.h, [130](#)
- set_home_settings
 - ximc.h, [131](#)
- set_joystick_settings
 - ximc.h, [131](#)
- set_logging_callback
 - ximc.h, [131](#)
- set_motor_information
 - ximc.h, [131](#)
- set_motor_settings
 - ximc.h, [132](#)
- set_move_settings
 - ximc.h, [132](#)
- set_nonvolatile_memory
 - ximc.h, [132](#)
- set_pid_settings
 - ximc.h, [132](#)
- set_position
 - ximc.h, [133](#)
- set_position_calb_t, [56](#)
 - EncPosition, [56](#)
 - PosFlags, [56](#)
 - Position, [57](#)
- set_position_t, [57](#)
 - EncPosition, [57](#)
 - PosFlags, [57](#)
- set_power_settings
 - ximc.h, [133](#)
- set_secure_settings
 - ximc.h, [133](#)
- set_serial_number
 - ximc.h, [133](#)
- set_stage_information
 - ximc.h, [133](#)
- set_stage_name
 - ximc.h, [134](#)
- set_stage_settings
 - ximc.h, [134](#)
- set_sync_in_settings
 - ximc.h, [134](#)
- set_sync_out_settings
 - ximc.h, [134](#)
- set_uart_settings
 - ximc.h, [135](#)
- SlowHome
 - home_settings_calb_t, [41](#)
 - home_settings_t, [42](#)
- Speed
 - measurements_t, [45](#)
 - move_settings_calb_t, [50](#)
 - move_settings_t, [51](#)
 - sync_in_settings_calb_t, [65](#)
 - sync_in_settings_t, [66](#)
- SpeedConstant
 - motor_settings_t, [49](#)
- SpeedTorqueGradient
 - motor_settings_t, [49](#)
- stage_information_t, [57](#)
 - Manufacturer, [58](#)
 - PartNumber, [58](#)
- stage_name_t, [58](#)
 - PositionerName, [59](#)
- stage_settings_t, [59](#)
 - HorizontalLoadCapacity, [59](#)
 - LeadScrewPitch, [59](#)
 - MaxCurrentConsumption, [60](#)
 - MaxSpeed, [60](#)
 - SupplyVoltageMax, [60](#)
 - SupplyVoltageMin, [60](#)
 - TravelRange, [60](#)
 - Units, [60](#)
 - VerticalLoadCapacity, [60](#)
- StallTorque
 - motor_settings_t, [49](#)
- status_calb_t, [60](#)
 - CmdBufFreeSpace, [61](#)
 - CurPosition, [61](#)
 - CurSpeed, [61](#)
 - CurT, [61](#)
 - EncPosition, [61](#)
 - EncSts, [61](#)
 - Flags, [62](#)
 - GPIOFlags, [62](#)
 - Ipwr, [62](#)
 - Iusb, [62](#)
 - MoveSts, [62](#)
 - MvCmdSts, [62](#)
 - PWRSts, [62](#)
 - Upwr, [62](#)
 - Uusb, [62](#)
 - WindSts, [62](#)
- status_t, [62](#)
 - CmdBufFreeSpace, [63](#)
 - CurPosition, [63](#)
 - CurSpeed, [64](#)

- CurT, [64](#)
- EncPosition, [64](#)
- EncSts, [64](#)
- Flags, [64](#)
- GPIOFlags, [64](#)
- Ipwr, [64](#)
- Iusb, [64](#)
- MoveSts, [64](#)
- MvCmdSts, [64](#)
- PWRSts, [64](#)
- uCurPosition, [64](#)
- uCurSpeed, [65](#)
- Upwr, [65](#)
- Uusb, [65](#)
- WindSts, [65](#)
- StepsPerRev
 - engine_settings_calb.t, [31](#)
 - engine_settings.t, [33](#)
- SupVoltage
 - analog_data.t, [15](#)
- SupVoltage_ADC
 - analog_data.t, [15](#)
- SupplyVoltageMax
 - encoder_settings.t, [30](#)
 - hallsensor_settings.t, [41](#)
 - stage_settings.t, [60](#)
- SupplyVoltageMin
 - encoder_settings.t, [30](#)
 - hallsensor_settings.t, [41](#)
 - stage_settings.t, [60](#)
- sync_in_settings_calb.t, [65](#)
 - ClutterTime, [65](#)
 - Position, [65](#)
 - Speed, [65](#)
 - SyncInFlags, [65](#)
- sync_in_settings.t, [66](#)
 - ClutterTime, [66](#)
 - Speed, [66](#)
 - SyncInFlags, [66](#)
 - uPosition, [66](#)
 - uSpeed, [67](#)
- sync_out_settings_calb.t, [67](#)
 - Accuracy, [67](#)
 - SyncOutFlags, [67](#)
 - SyncOutPeriod, [67](#)
 - SyncOutPulseSteps, [67](#)
- sync_out_settings.t, [68](#)
 - Accuracy, [68](#)
 - SyncOutFlags, [68](#)
 - SyncOutPeriod, [68](#)
 - SyncOutPulseSteps, [68](#)
 - uAccuracy, [68](#)
- SyncInFlags
 - sync_in_settings_calb.t, [65](#)
 - sync_in_settings.t, [66](#)
- SyncOutFlags
 - sync_out_settings_calb.t, [67](#)
 - sync_out_settings.t, [68](#)
- SyncOutPeriod
 - sync_out_settings_calb.t, [67](#)
 - sync_out_settings.t, [68](#)
- SyncOutPulseSteps
 - sync_out_settings_calb.t, [67](#)
 - sync_out_settings.t, [68](#)
- t1
 - brake_settings.t, [16](#)
- t2
 - brake_settings.t, [16](#)
- t3
 - brake_settings.t, [16](#)
- t4
 - brake_settings.t, [16](#)
- TSGrad
 - accessories_settings.t, [11](#)
- TSMAX
 - accessories_settings.t, [11](#)
- TSMIN
 - accessories_settings.t, [11](#)
- TSSettings
 - accessories_settings.t, [11](#)
- Temp
 - analog_data.t, [15](#)
- Temp_ADC
 - analog_data.t, [15](#)
- TemperatureSensorInfo
 - accessories_settings.t, [11](#)
- Time
 - command_add_sync_in_action_calb.t, [20](#)
 - command_add_sync_in_action.t, [20](#)
- Timeout
 - control_settings_calb.t, [21](#)
 - control_settings.t, [22](#)
- TorqueConstant
 - motor_settings.t, [49](#)
- TravelRange
 - stage_settings.t, [60](#)
- UART_PARITY_BITS
 - ximc.h, [105](#)
- UARTSetupFlags
 - uart_settings.t, [69](#)
- uAccuracy
 - sync_out_settings.t, [68](#)
- uAntiplaySpeed
 - move_settings.t, [51](#)
- uCurPosition
 - status.t, [64](#)
- uCurSpeed
 - status.t, [65](#)
- uDeltaPosition
 - control_settings.t, [23](#)
- uFastHome
 - home_settings.t, [43](#)
- uHomeDelta
 - home_settings.t, [43](#)
- uLeftBorder

- edges_settings.t, 28
- uMaxSpeed
 - control_settings.t, 23
- uNomSpeed
 - engine_settings.t, 33
- uPosition
 - command_add_sync_in_action.t, 20
 - sync_in_settings.t, 66
- uRightBorder
 - edges_settings.t, 28
- uSlowHome
 - home_settings.t, 43
- uSpeed
 - move_settings.t, 52
 - sync_in_settings.t, 67
- uart_settings.t, 69
 - UARTSetupFlags, 69
- UniqueID0
 - globally_unique_identifier.t, 39
- UniqueID1
 - globally_unique_identifier.t, 39
- UniqueID2
 - globally_unique_identifier.t, 39
- UniqueID3
 - globally_unique_identifier.t, 39
- Units
 - stage_settings.t, 60
- Upwr
 - status_calb.t, 62
 - status.t, 65
- UserData
 - nonvolatile_memory.t, 52
- Uusb
 - status_calb.t, 62
 - status.t, 65
- VerticalLoadCapacity
 - stage_settings.t, 60
- WIND_A_STATE_ABSENT
 - ximc.h, 105
- WIND_A_STATE_OK
 - ximc.h, 106
- WIND_B_STATE_ABSENT
 - ximc.h, 106
- WIND_B_STATE_OK
 - ximc.h, 106
- WindSts
 - status_calb.t, 62
 - status.t, 65
- WindingCurrentA
 - chart_data.t, 19
- WindingCurrentB
 - chart_data.t, 19
- WindingCurrentC
 - chart_data.t, 19
- WindingInductance
 - motor_settings.t, 50
- WindingResistance
 - motor_settings.t, 50
- WindingVoltageA
 - chart_data.t, 19
- WindingVoltageB
 - chart_data.t, 19
- WindingVoltageC
 - chart_data.t, 19
- write_key
 - ximc.h, 135
- XIMC_API
 - ximc.h, 106
- ximc.h, 70
 - BORDER_IS_ENCODER, 91
 - BORDER_STOP_LEFT, 92
 - BORDER_STOP_RIGHT, 92
 - BRAKE_ENABLED, 92
 - BRAKE_ENG_PWROFF, 92
 - CONTROL_MODE_BITS, 92
 - CONTROL_MODE_JOY, 92
 - CONTROL_MODE_LR, 92
 - CONTROL_MODE_OFF, 92
 - CTP_ALARM_ON_ERROR, 92
 - CTP_BASE, 93
 - CTP_ENABLED, 93
 - close_device, 107
 - command_add_sync_in_action, 107
 - command_change_motor, 107
 - command_clear_fram, 107
 - command_eeread_settings, 107
 - command_eesave_settings, 107
 - command_home, 108
 - command_homezero, 108
 - command_left, 108
 - command_loft, 108
 - command_move, 109
 - command_movr, 109
 - command_power_off, 109
 - command_read_robust_settings, 109
 - command_read_settings, 110
 - command_reset, 110
 - command_right, 110
 - command_save_robust_settings, 110
 - command_save_settings, 110
 - command_sstp, 110
 - command_start_measurements, 111
 - command_stop, 111
 - command_update_firmware, 111
 - command_wait_for_stop, 111
 - command_zero, 112
 - EEPROM_PRECEDENCE, 93
 - ENC_STATE_ABSENT, 93
 - ENC_STATE_MALFUNC, 93
 - ENC_STATE_OK, 93
 - ENC_STATE_REVERS, 93
 - ENC_STATE_UNKNOWN, 93
 - ENDER_SWAP, 94
 - ENGINE_ACCEL_ON, 94
 - ENGINE_ANTIPLAY, 94

ENGINE_LIMIT_CURR, 94
ENGINE_LIMIT_RPM, 94
ENGINE_LIMIT_VOLT, 94
ENGINE_MAX_SPEED, 94
ENGINE_REVERSE, 95
ENGINE_TYPE_2DC, 95
ENGINE_TYPE_DC, 95
ENGINE_TYPE_NONE, 95
ENGINE_TYPE_STEP, 95
ENGINE_TYPE_TEST, 95
ENUMERATE_PROBE, 95
EXTIO_SETUP_INVERT, 95
EXTIO_SETUP_OUTPUT, 97
enumerate_devices, 112
FEEDBACK_EMF, 97
FEEDBACK_ENCODER, 97
FEEDBACK_NONE, 97
free_enumerate_devices, 112
get_accessories_settings, 112
get_analog_data, 112
get_bootloader_version, 113
get_brake_settings, 113
get_calibration_settings, 113
get_chart_data, 113
get_control_settings, 114
get_controller_name, 114
get_ctp_settings, 114
get_debug_read, 114
get_device_count, 115
get_device_information, 115
get_device_name, 115
get_edges_settings, 115
get_encoder_information, 116
get_encoder_settings, 116
get_engine_settings, 116
get_entype_settings, 116
get_enumerate_device_controller_name, 116
get_enumerate_device_information, 117
get_enumerate_device_network_information, 117
get_enumerate_device_serial, 117
get_enumerate_device_stage_name, 117
get_extio_settings, 118
get_feedback_settings, 118
get_firmware_version, 118
get_gear_information, 118
get_gear_settings, 119
get_globally_unique_identifier, 119
get_hallsensor_information, 119
get_hallsensor_settings, 119
get_home_settings, 119
get_init_random, 120
get_joystick_settings, 120
get_measurements, 120
get_motor_information, 121
get_motor_settings, 121
get_move_settings, 121
get_nonvolatile_memory, 121
get_pid_settings, 121
get_position, 122
get_power_settings, 122
get_secure_settings, 122
get_serial_number, 122
get_stage_information, 122
get_stage_name, 123
get_stage_settings, 123
get_status, 123
get_status_calb, 123
get_sync_in_settings, 123
get_sync_out_settings, 124
get_uart_settings, 124
goto_firmware, 124
H_BRIDGE_ALERT, 97
HOME_DIR_FIRST, 97
HOME_DIR_SECOND, 98
HOME_HALF_MV, 98
HOME_MV_SEC_EN, 98
HOME_USE_FAST, 98
has_firmware, 125
JOY_REVERSE, 99
LOW_UPWR_PROTECTION, 99
logging_callback_stderr_narrow, 125
logging_callback_stderr_wide, 125
logging_callback_t, 106
MICROSTEP_MODE_FULL, 99
MOVE_STATE_ANTIPLAY, 99
MOVE_STATE_MOVING, 100
MVCMD_ERROR, 100
MVCMD_HOME, 100
MVCMD_LEFT, 100
MVCMD_LOFT, 100
MVCMD_MOVE, 100
MVCMD_MOVR, 100
MVCMD_NAME_BITS, 100
MVCMD_RIGHT, 100
MVCMD_RUNNING, 100
MVCMD_SSTP, 101
MVCMD_STOP, 101
MVCMD_UKNWN, 101
msec_sleep, 125
open_device, 125
POWER_OFF_ENABLED, 101
PWR_STATE_MAX, 101
PWR_STATE_NORM, 101
PWR_STATE_OFF, 101
PWR_STATE_REDUCT, 101
PWR_STATE_UNKNOWN, 101
probe_device, 126
REV_SENS_INV, 101
STATE_ALARM, 102
STATE_BRAKE, 102
STATE_BUTTON_LEFT, 102
STATE_BUTTON_RIGHT, 102
STATE_CONTR, 102
STATE_CTP_ERROR, 102
STATE_CURRENT_MOTOR0, 102
STATE_CURRENT_MOTOR1, 102

STATE_CURRENT_MOTOR2, [103](#)
STATE_CURRENT_MOTOR3, [103](#)
STATE_DIG_SIGNAL, [103](#)
STATE_ENC_A, [103](#)
STATE_ENC_B, [103](#)
STATE_ERRC, [103](#)
STATE_ERRD, [103](#)
STATE_ERRV, [103](#)
STATE_GPIO_LEVEL, [103](#)
STATE_GPIO_PINOUT, [103](#)
STATE_LEFT_EDGE, [104](#)
STATE_REV_SENSOR, [104](#)
STATE_RIGHT_EDGE, [104](#)
STATE_SECUR, [104](#)
STATE_SYNC.INPUT, [104](#)
STATE_SYNC.OUTPUT, [104](#)
SYNCIN_ENABLED, [105](#)
SYNCIN.GOTOPOSITION, [105](#)
SYNCIN.INVERT, [105](#)
SYNCOUT_ENABLED, [105](#)
SYNCOUT.IN.STEPS, [105](#)
SYNCOUT.INVERT, [105](#)
SYNCOUT.ONPERIOD, [105](#)
SYNCOUT.ONSTART, [105](#)
SYNCOUT.ONSTOP, [105](#)
SYNCOUT.STATE, [105](#)
service_command_updf, [126](#)
set_accessories.settings, [126](#)
set_bindy_key, [126](#)
set_brake.settings, [126](#)
set_calibration.settings, [127](#)
set_control.settings, [127](#)
set_controller_name, [127](#)
set_ctp.settings, [127](#)
set_debug.write, [128](#)
set_edges.settings, [128](#)
set_encoder_information, [128](#)
set_encoder.settings, [128](#)
set_engine.settings, [129](#)
set_entype.settings, [129](#)
set_extio.settings, [129](#)
set_feedback.settings, [129](#)
set_gear_information, [130](#)
set_gear.settings, [130](#)
set_hallsensor_information, [130](#)
set_hallsensor.settings, [130](#)
set_home.settings, [131](#)
set_joystick.settings, [131](#)
set_logging_callback, [131](#)
set_motor_information, [131](#)
set_motor.settings, [132](#)
set_move.settings, [132](#)
set_nonvolatile_memory, [132](#)
set_pid.settings, [132](#)
set_position, [133](#)
set_power.settings, [133](#)
set_secure.settings, [133](#)
set_serial_number, [133](#)
set_stage_information, [133](#)
set_stage_name, [134](#)
set_stage.settings, [134](#)
set_sync_in.settings, [134](#)
set_sync_out.settings, [134](#)
set_uart.settings, [135](#)
UART_PARITY_BITS, [105](#)
WIND_A.STATE_OK, [106](#)
WIND_B.STATE_OK, [106](#)
write_key, [135](#)
XIMC_API, [106](#)
ximc_fix_usbser_sys, [135](#)
ximc_version, [135](#)
ximc_fix_usbser_sys
 ximc.h, [135](#)
ximc_version
 ximc.h, [135](#)